

5.

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 lowa City, IA 52240

Date of Inspecti	on: 9/30/	2021		Regi	stration #SP52 -073- OS	8		
Facility Name:	Facility Name: Comfort Suites				Pool Spa Other gistration #SP52- 073 O S &			
Facility Physical	Address:	Jui tes			ool Spa Other			
2	Address: 431 Jam	es 87,	1		stration# Pool			
	alville				inty: Johnson State: Zip:			
Person Contacte	Person Contacted: Sopan Patel Name of CPO(s) Sopan Patel			E-Ma	nil:		IA	52241
Name of CRO(s)	sopan r	atel			Dopanspa-	+degr	mail.	com
Marile of Cro(s)	Sopan P.	atel			,	O		
	SYSTEMS AND SECON							AND THE PROPERTY OF THE PROPER
Disinfection make				- 52				
Accu-	Tab Powe	er basa u.	4.0 103	a '	Ecolal sold d	١		_
Туре:			au		COU TIME SOUTH OF	a spenser	N-2	40
□ Bromine □ T	richlor Golding Hom	and the state of t			um Hypochlorite 🔲 CI (ga	-		
		ochlorite 🔲 Sodium F	typochlorite 🔟	Lithiu	ım Hypochlorite 🔲 CI (ga	s) 🗌 Other: _		
WATER CHEMIST	RY *	e digi digi ada	ir i			ar and	5 16	
Type (Pool, Spa,	Free Chlorine	Bromine	pH	\$650×\$56	Cyanuric Acid	Controlle	er	Spa Temperature
Plunge Pool, etc.)	Pool 1.0-8.0	Pool 2.0-18.0	Pool 7.2-7.8		Pool 0-40	ORP 700-8		<= 104°
ກ /	Spa 2.0-8.0	Spa 4.0-18.0	Spa 7.2-7.8	-	Spa 0- 40	pH 7.2-7.	.8	
Pool	3.2		7.4					
Spa	3,6		7.4					1020
y: S = Satisfa	actory U = Unsati	isfactory N/A =	Not Applicabl	 e				
CILITY RECORDS			•••	6.		6 (6)	ه دا	
S U N/A				U,	certificates.	cerunea opera	ator, lifegu	ard, first-aid, & CPR
15.9(1) The swimming pool or spa is currently registered.			7.		2) & 15.51(5)e(2): Monthl	ly microbiological	
15.4(2)a(1)-(6) & 15.51(2)a(1)-(6):Water quality			8.	analyses results.				
readings recorde	ed are in the correct ra	nge (or closures noted	when	0.	complaints, accidents,	s) & 15.51(5)e(4 iniuries & illne	4J: Facility	maintains reports of
out of range).	4(3)+(1) (C) C	Loop Lu			required.			
D 15.4(2)e(1)-(6): Swimming pool: ORP and pH at opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total			9.	☐ ☐ 15.4(6)f(4) & 15.51(5)e(!	5): Dates &	quantities of	
alkalinity and cyanuric acid weekly; calcium hardness & bacteria			10.	chemical additions, inc	iuding resupply	of chemic	cal feed systems,	
testing monthly.				backwashed, cleaned, c	or a filter cartric	dge was ch	anged.	
15.4(4)h(1)3 & 15.51(4)f(2)3: Submerged outlet (VGB) certification of compliance (main drain, equalizer, feature outlets,			11.	[년 [15.4(6)f(6) & 15.51(5)e(8	3): GFCI red	ceptacles & breakers	
etc.) is on-site.	amphance (main urain,	equalizer, reature out	iets,	12.	are tested at least 1x/m	e tested at least 1x/month and dates of test dates recorded. 15.4(6)f(7) & 15.51(5)e(9): MSDS for chemicals on-site,		
15.4(4)h(3)1-3 & 15.51(4)f(4)1-3: SVRS product			٠٧.	reviewed annually, and	ງ & 15.51(5)e(9 date(s) of rovic	y): MSDS fo	or chemicals on-site,	
information that demonstrates compliance is on-site. SVRS tested			13.	□ 15.4(6)i(1))-(6) & 15.51(5 <mark>)</mark>	g(1)-(6): C	perations manual	
monthly and the test date(s) recorded.				on-site (water testing pr	rocedures, back	wash, vac	uuming. etc.).	

FΔC	CILITY RECORDS CONT.	21.	15.5(18)c: Each section of a multi-section pool is
1710	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6)l: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by	22	pool.
	staff, and date(s) of review recorded.	23.	not more than 25ft apart in shallow water.
15.	of zones of surveillance responsibility.	24.	☐ 15.4(4)j(3): Depth markers not more than 25ft apart
16	7 15.51(2)e(3):Spa temperature recorded when water		around the deep end of swimming pool.
10.	quality testing is done (104° or less-closures noted when out of temp	25.	~ ~ ~ ·
	range).		is not permitted (not more than 25ft apart).
17.		26.	15.4(4)j(7): Letters, numbers & graphics marked on
	every 2 hours; free CI (Br) and temperature 2x daily+; combined CI		decks and slip resistant.
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	
	calcium hardness at each fill & bacteria testing monthly		resistant, have durable and cleanable surface, are free of litter,
18.	15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal	28	obstructions & tripping hazards. 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	20.	projections or obstructions.
	gal 1x every three weeks.	29.	☐ 15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
DO.	DL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
PUC	S , U N/A	30.	☐ 15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1.	15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall, building enclosure or combination not less than 4ft high.
	adjusting weirs and removable baskets.	31.	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `
2.	☐ ☐ 15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		ground & the top of the lowest horizontal support is at least 45
	openings visible in water less than 8ft deep.	22	inches.
3.	15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	wide provided for emergency purposes.
	cleaning.	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
4.	15.4(4)b(1): Ladders or recessed steps provided in the		15.4(4)I(5) & 15.51(4)k(4): Gates/doors are self-
	deep portion of pool. Stairs, ladders, recessed steps, or ramps provided in the shallow portion if more than 2ft deep.		closing and self-latching (where lifeguards are not provided).
5.		35.	☐ ☐ 15.4(4)I(5): Indoor pool enclosed by barrier at least
J,	are securely anchored.		3ft high if there are sleeping rooms, hallways, apartments,
6.	☐ ☐ 15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		condominiums or permanent recreation areas used by children that
	from the pool wall. The bottom end of ladder is within one inch of		open directly into the swimming pool area.
	the pool wall and covered with a smooth non-metallic cap.	36.	15.4(4))(6): Wave pool has a continuous barrier at
7.	✓ ☐ 15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		least 42 inches high along the full length of each side of the wave pool.
_	are slip resistant.	37.	□ 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,	37.	pool deck equipped with (GFCI) at the outlet or at the breaker
0	ladders, ramps, or stairs installed on each side. 15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have		serving the outlet.
9.	securely anchored grab rails or handrails.	38.	☐ ☐ 15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10.	15.4(4)b(8): Stairs have slip resistant color contrasting		for indoor or outdoor pools/spas used after sunset (overhead and/or
	stripe at least 1 inch wide marked at the leading edge of each tread.		underwater lights) are functional.
11.	☐ ☐ 15.4(4)e: Elevated lifeguard chairs (where required)	39.	15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
	are provided.		signs posted at two locations (No Diving, No Rough Play, No
12.		40.	Running) 15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
13.	15.4(4)f(4): First-aid kit containing bandages, 4x4	40.	accompanied by an adult) sign posted at each swimming pool entry
	bandage compress, self-adhering gauze bandage, disposable gloves & chemical cold compress. Signage if required.		where lifeguards are not provided.
14.		41.	15.5(4)h & 15.51(4)h(3): At least one hose bib
14.	lifeguards)		provided for flushing the deck(built or reconstructed since March 14,
15.	✓ ☐ 15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
	telephone with instruction. Signage posted as required.	4 2.	,,,,
16.	,	47	preventers provided on all hose bibs on the deck.
	maintained at the skimming level.	43.	☐ ☐ ☑ 15.4(4)c(2): Starting blocks removed, covered, or a sign posted to prevent use by the public during general use periods.
17.	15.4(4)h & 15.51(4)f: Fully submerged outlets not	44.	15.5(4)d & 15.52(4)b: The decks drain away from the
10	missing or broken. 15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer		swimming pool/spa (built or reconstructed since March 10, 1993).
TQ.	openings VGB compliant or the equalizers plugged.	45.	☐ ☐ ☑ 15.5(13)f(3): Where pool depth changes from shallow
19	15.4(4)i(1): The bottom and sides of pool are white or		to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
	light color.		depth (built or reconstructed since March 14, 1990).
20.	15.4(4)i(3): The shallow & deep water (5ft) or change	46.	
	in slope is marked by a float line with floats spaced no more than 5ft		safe, sanitary manner.

apart.

SP/		ME	ECHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed 104°F.	1.	S U N/A 15.4(1)a & 15.51(1)a: Filtration system is in good working condition.
2.	15.51(4)]: Agitation system control out of reach of	2.	☐ 15.4(1)b(1) & 15.51(1)c: The recirculation system is
3.	persons and timer is 10 minutes or less. 15.51(5)b: Spa rules sign (8 required stipulations)	3.	operating continuously (except for backwashing or servicing). 15.4(1)b(1) & 15.51(1)c: The circulation system flow
4.	posted. D	4.	meter(s) are functional. 15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and
5.	numbers 3in high). 15.52(12)a: A spa has at least one stairway, ramp,	5.	after) filter pump 15.4(1)c & 15.51(1)f: Wastewater and backwash is
	ladder or set of recessed steps designating a point of entry (built or reconstructed since March 14, 1990).	6.	discharged through an air break or air gap. 15.4(1)d(1) & 15.51(1)g(1): Water supplied to a
6.	[] 15.52(12)a(1)2: Spa stair steps have two hand/grab rails, one on each side of the steps (built or reconstructed since		pool/spa is discharged to the system through an air gap or a reduced principle backflow device.
	March 10, 1993).	7.	☐ ☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	[] 15.52(12)c: An emergency shutoff switch near the spa (built or reconstructed since 1999).	8.	preventers provided on hose bibs in mechanical room. 15.4(1)e(1) & 15.51(1)h(1): Electric water heaters
18//	DING Pools	9.	have UL seal. 15.4(1)e(2) & 15.51(1)h(2): Gas-fired heaters have
VVP	S U N/A	٥.	AGA seal and equipped with a pressure relief valve.
1.	15.4(4)h: Fully submerged outlets not missing or	10.	15.4(1)e(3) & 15.51(1)h(3): Fuel-burning water heaters are vented to the outside.
2.	broken. 15.4(4)h(1)2: Fully submerged outlet covers/grates	11.	15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning
	not removable without the use of tools. [equipment has opening(s) to the outside for providing combustion
3.	L L 15.4(4)(4): Wading pool within 50 ft of a pool has a barrier at least 36 inches high separating it from the pool or has	12.	air. 15.4(2)g: Knowledgeable person in testing
	written alternate management plan on-site.		water/operating water treatment equipment available when pool is
4.	☐ ☑ 15.4(4)(5): Gates/doors are self-closing and self-latching (where lifeguards are not provided).	13	open for use. D 15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming
5.	15.4(6)d(1): 'No Lifeguard' (Children must be	10,	pool/spa facility has water testing equipment for free chlorine &
-	accompanied by an adult) sign posted at each wading pool entry		combined chlorine, or total bromine; pH; total alkalinity; calcium
	where lifeguards are not provided.		hardness; & cyanuric acid.
6.	15.4(4)j(4):Maximum depth of wading pool at each entrance and one location inside enclosure (letters or numbers 3in	14.	with numerical analog or digital display NO ORA DISPLAT
	high).	15.	15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection feed equipment installed and operational.
DIV	ING BOARDS	16.	15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
	S U N/A		feed equipment installed and operational (built or reconstructed
1.	[] [] 15.4(4)c(6): Diving boards/platforms have slip-resistant surfaces.	17	since July 1, 1998). 1. I 15.4(3)b(2): A vacuum cleaning system is provided.
2.	☐ ☐ 15.4(4)c(8)-[9]: Diving board handrails and guard rails		☐ 15.4(6)j & 15.51(5)i: A schematic drawing of the
	present and secure.		recirculation system is posted or clear labeling of piping with flow
3.	15.4(4)c(10): Diving board supports, platforms &		direction and water status (unfiltered, treated, backwashed).
	steps have no obvious visual structural problems.	CHI	EMICAL STORAGE
WA	<u>TER SLIDES</u>		S / U N/A
	S U N/A	1.	☐ ☐ 15.4(4)a(2) & 15.51(4)a(2): Swimming pool/spa
1.	☐ ☐ 15.4(4)d(5): Water slide has a lifeguard (or shallow water guard where applicable) at the top and bottom of slide.	2.	chemicals properly stored & handled. 15.4(4)a(4) & 15.51(4)a(4): Chemical storage
2.	15.4(4)o(1): Water slide support structures are free of	۷.	containers clearly labeled.
	obvious structyral defects.	3.	15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	15.4(4)o(2): The walkable surface of flume is smooth and continuous.		warning placed at the entrances to rooms where chemical are used or stored.
4.	15.4(4)o(3): The walkable surface of flume has no	4.	☐ ☐ 15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single
	sharp edges within reach of a user while in the proper sliding	_	submerged outlet that is not unblockable is equipped with a SVRS.
5.	position. 15.4(6)e (1)-(6): Water slide rules are posted near the	5.	☐ ☐ 15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more than 15 V equipped with a GFCI.
	slide.	6.	15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	15.5(17)b(1): Plunge pool depth is at least 3ft and no more than 4ft.		gallons have secondary containment (built or reconstructed since May 4, 2005).
7.	☐ ☐ 15.5(17)b(4): Landing area for a water slide is		
	designated by a float line or a painted area.		

<u>CHLORINE GAS</u>			15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S U N/A		preventers p	provided on all hose bibs in the bathhouse.
1.	gas room has an exhaust		
system.		SPRAY PADS	
	ake provided near the ceiling.	S U N	/A
	ust fan shall be operated from		15.5(19)a: The surface of a spray pad shall be
a switch labeled "Chlorine Exhaust Fa			and durable. Padding specifically designed for spray pads
	n in a nearby location outside	•	= , , , , , , , , , , , , , , , , , , ,
the chlorine room or building.			with play features.
	e from exhaust system outside		15.5(19)b: The spray pad surface shall slope to drain.
of pool enclosure		Deck or othe	er areas outside the spray pad shall not drain into the
5. 🔲 🔲 🗹 15.4(4)n(1)5: Artificial 🛚	lighting provided in chlorine	spray pad.	,
room		3. 🗌 🗍 🗹	15.5(19)c: Unless the spray pad is supervised by
•	bottle of commercial strength		a sign shall be posted near the spray pad that
ammonia solution for leak detection.	bottle of commercial strength		lo running on or around the spray pad, No rough play,
	10- d 1- 10- 4-l 0b		pervision. Parents are responsible for supervising their
	gas cylinders are individually		pervision. Farents are responsible for supervising their
anchored with safety chains or straps		children.	7
			15.5(19)d: Spray pads drains shall be gravity outlets.
BATHHOUSE		At least two	drains or a single drain that is unblockable shall be
S U N/A		provided.	
	sing rooms & sanitary facilities	5. 🗌 🗎 🗹	15.5(19)e(2): On independent treatment systems the
are clean & free of debris.			accessible for cleaning and inspection.
_/	resistant and maintained		15.5(19)e(3): On independent treatment systems the
	esistant and maintained		
without standing water.			treatment system and play feature pump and piping
3. 📝 🗍 📋 15.4(5)c: Carpet not in	wet areas of the	system shall	
bathhouse/dressing area.			15.5(19)e(5): On independent treatment systems the
4. 🔃 🗌 🔲 15.4(5)d: Lavatories, sh	owers & sanitary facilities	play feature	pump system shall be designed so that it will not
functional.		operate if the	e recirculation system in not operating.
	avatory and indoor shower		
fixtures.		IOWA SMOKEFREE	AIR ACT
6. 🔽 🔲 🔲 15.4(4)m(1) & 15.51(4)	i(1): Electrical outlets in the	\$.U	
public dressing, lavatory, and shower:		. /	o Code \$143D. No violations absenced (No ovidence of
			va Code §142D: No violations observed (No evidence of
receptacles at the outlet or breaker se			rohibited areas, no ashtrays present, signs posted at
	provided within the bathhouse	entrances)	
(built or reconstructed since March 14	ł, 1990) .		
Comments/Recommendations:			
comments, necommendations			
	 		
	•		
			
Comments/Recommendations:			
,			
	•		
			
	· · · · · · · · · · · · · · · · · · ·		

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Pool/Spa Representative

9-30-2

9/30/21

Date

JCPH Representative

Date

*The inspection reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION

Enforcement 641 15.6(135I)

Facility Name: Comfort suites

Date of Inspection: 9/30/21 Inspector: James Lacina

The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within 30 days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to lowa Code 1351 and 641 IAC 15.6.

Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Controller is not displaying ORP data

Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Spa temperature exceeds 1040 (currently at 105°).

Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 5: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
Deficiency 7: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	y the facility to indicate how the deficiencies will be corrected)
Deficiency 8: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
Deficiency 9: (Cite 641 IAC Chapter 15 violation and mann	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 10:</u> (Cite 641 IAC Chapter 15 violation and mar	nner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	the facility to indicate how the deficiencies will be corrected)
*** Additional identified deficiencies may be listed on a	attached pages.
The deficiencies noted during the inspection shall be accordingly of this document to:	ddressed by completing this Corrective Action Plan within days and submitting an
	Johnson County Public Health Attn: James Lacina 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240
Pool Representative:	Date:

<u>Deficiency 6</u>: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Page 7 of 7 Rev. 9/14/2021 JP

<u>Deficiency 7</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) .
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 8</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 9:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 10: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)