

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 Iowa City, IA 52240

Date of Inspection:				Registration # SPS 2 - 0 5 8 Pool Spa Other			
Facility Name: Comfort Suites			R	Registration # □ Pool Spa □ Other			
I Facility Physical Address:				City: Coralville S2241			
				-Mail:	3 (
	Sopari Pa	lel					
Manager on Duty:			Ε	E-Mail:			
Name of CPO(s): So pan Patel			E	E-Mail: Sopan. S. patel@gmail.com			
Jupan Marci				sopan s. parete j.			
CHEMICAL FEED	SYSTEMS AND SECOND	ARY DISINFECTANT	Fi 1.		Transfer of the same		
Disinfection make	e and model #:						
Accu-Tab Powerbase (Model 1030/Pool); Eco-Lab (Model N-280)(Spa)							
Type:							
☐ Bromine ☐ T	richlor Calcium Hvn	ochlorite Sodium H	vpochlorite	Lithium Hypochlorite 🔲 C	l (gas) \ \ \ Other:		
	Tonior Lei carciain hyp	osmorite Doddallin	, position to		. (849)		
WATER CHEMIST	RY			Tell Internal			
Type (Pool, Spa,	Free Chlorine	Bromine	рН	Cyanuric Actd	Controller	Spa Temperature	
Plunge Pool, etc.)	Pool 1.0-8.0	Pool 2.0-18.0	Pool 7.2-7.8	Pool 0-40	ORP 700-880	<= 104°	
	Spa 2.0-8.0 Fc1 - 2.46	Spa 4.0-18.0	Spa 7.2-7.8	Spa 0- 40	pH 7.2-7.8		
Pool	701-347		7.6	CH- 161			
Spa	Fc1 - 2.15 701 - 2.71		7.6	ALK- 180		102.30	
(ey: S = Satisi	factory U = Unsat	icfactory N/A –	Not Applicable				
		isiactory N/A =	reor Applicable				
S U N/A	<u>s</u>			6. ☑ ☐ 15.4 (certificates.	(6)h: Certified operato	r, lifeguard, first-aid, & CPR	
	5.9(1) The swimming po	ool or spa is currently			(6)f(2) & 15.51(5)e(2):	Monthly microbiological	
registered.				analyses results.			
	5.4(2)a(1)-(6) & 15.51(2					Facility maintains reports of	
out of range).	ded are in the correct ra	inge (or closures noted	wnen	required.	ents, injuries, & iliness.	. Reports submitted as	
3.				9. 15.4	(6)f(4) & 15.51(5)e(5):	Dates & quantities of	
opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total			total	chemical addition	s, including resupply o	f chemical feed systems.	
alkalinity and cyanuric acid weekly; calcium hardness & bacteria					Dates when filters were		
testing monthly. 1. 15.4(4)h(1)3 & 15.51(4)f(2)3: Submerged outlet (VGB)			t (VGB)		ned, or a filter cartridge (6)f(6) & 15.51(5)e(8):	e was cnanged. GFCI receptacles & breaker	
certification of compliance (main drain, equalizer, feature outlets,					1x/month and dates o		
etc.) is on-site				12. 🔽 🔲 🔲 15.4	(6)f(7) & 15.51(5)e(9):	MSDS for chemicals on-site	
	5.4(4)h(3)1-3 & 15.51(4				, and date(s) of review		
	at demonstrates compli le test date(s) recorded		ested			(1)-(6): Operations manual vash, vacuuming, etc.).	
monthly and th	e test date(s) recorded	•		on-site (water test	ing procedures, backw	vasn, vacuuming, etc.).	

FAC	CILITY RECORDS CONT.		☐ ☐ 15.5(18)c: Each section of a multi-section pool is
	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6)I: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool.
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	☐ 15.4(4)j(3): Depth markers not more than 25ft apart
16	☐ ☐ 15.51(2)e(3):Spa temperature recorded when water		around the deep end of swimming pool.
1.01	quality testing is done (104° or less-closures noted when out of temp		☐ 15.4(4)j(6): "No Diving" marked in areas where diving
	range).		is not permitted (not more than 25ft apart).
17	15.51(2)e(1)-(8): Spa: ORP and pH at opening and		☐ 15.4(4)j(7): Letters, numbers & graphics marked on
1/.			decks and slip resistant.
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl		15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	and cyanuric acid daily; total alkalinity weekly and at each fill;		resistant, have durable and cleanable surface, are free of litter,
	calcium hardness at each fill & bacteria testing monthly		obstructions & tripping hazards.
18.			
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000		☐ ☐ 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	gal 1x every three weeks.		projections or obstructions.
		29.	
PO	OL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
	S U N/A		I 15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1.	15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall, building enclosure or combination not less than 4ft high.
	adjusting weirs and removable baskets.	31.	15.4(4)I(2) & 15.51(4)k(2): The distance between the
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		ground & the top of the lowest horizontal support is at least 45
	openings visible in water less than 8ft deep.		inches.
3.	15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	15.4(4)I(3) & 15.51(4)k(3): A gate at least 36 inches
٥,	cleaning.		wide provided for emergency purposes.
4.	15.4(4)b(1): Ladders or recessed steps provided in the	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
4.	deep portion of pool. Stairs, ladders, recessed steps, or ramps		15.4(4)I(5) & 15.51(4)k(4): Gates/doors are self-
	proyided in the shallow portion if more than 2ft deep.		closing and self-latching (where lifeguards are not provided).
-		35.	
5.	☐ 15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs		3ft high if there are sleeping rooms, hallways, apartments,
-	are securely anchored.		condominiums or permanent recreation areas used by children that
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		open directly into the swimming pool area.
	from the pool wall. The bottom end of ladder is within one inch of	36.	
_	the pool wall and covered with a smooth non-metallic cap.		least 42 inches high along the full length of each side of the wave
7.	15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		pool.
	are slip resistant.		
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,		15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
	ladders, ramps, or stairs installed on each side.		pool deck equipped with (GFCI) at the outlet or at the breaker
9,	15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have		serving the outlet.
	segurely anchored grab rails or handrails.		15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10.	☑ 15.4(4)b(8): Stairs have slip resistant color contrasting		for indoor or outdoor pools/spas used after sunset (overhead and/or
	stripe at least 1 inch wide marked at the leading edge of each tread.		underwater lights) are functional.
11.	15.4(4)e: Elevated lifeguard chairs (where required)		15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
	are provided.		signs posted at two locations (No Diving, No Rough Play, No
12.	15.4(4)f(1): Required lifesaving equipment provided.		Running)
13,	15.4(4)f(4): First-aid kit containing bandages, 4x4	40.	15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
	bandage compress, self-adhering gauze bandage, disposable gloves		accompanied by an adult) sign posted at each swimming pool entry
	& chemical cold compress. Signage if required.		where lifeguards are not provided.
14.	15.4(4)f(5):Spine board provided (facilities with	41.	15.5(4)h & 15.51(4)h(3): At least one hose bib
- 11	lifeguards)		provided for flushing the deck(built or reconstructed since March 14,
15	15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
10.	telephone with instruction. Signage posted as required.	42.	☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
16			preventers provided on all hose bibs on the deck.
16.	maintained at the skimming level.	43.	
17			sign posted to prevent use by the public during general use periods.
1/.	15.4(4)h & 15.51(4)f: Fully submerged outlets not		15.5(4)d & 15.52(4)b: The decks drain away from the
40	missing or broken.		swimming pool/spa (built or reconstructed since March 10, 1993).
18.	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer		15.5(13)f(3): Where pool depth changes from shallow
4 ~	openings VGB compliant or the equalizers plugged.		to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
19.	15.4(4)i(1): The bottom and sides of pool are white or		depth (built or reconstructed since March 14, 1990).
	light color.	AC	15.4 & 15.51: A swimming pool/spa is operated in a
20.			
	in slope is marked by a float line with floats spaced no more than 5ft		safe, sanitary manner.

apart.

SP/		ME	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S U N/A 15.4(1)a & 15.51(1)a: Filtration system is in good
2.	104°F. 15.51(4)I: Agitation system control out of reach of	2.	working condition. 15.4(1)b(1) & 15.51(1)c: The recirculation system is
	persons and timer is 10 minutes or less.	2	operating continuously (except for backwashing or servicing). 15.4(1)b(1) & 15.51(1)c: The circulation system flow
3.	15.51(5)b: Spa rules sign (8 required stipulations) posted.	3.	meţer(s) are functional.
4.	15.51(5)c: Maximum spa depth posted (letters or	4.	15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and after) filter pump
5.	numbers 3in high). 15.52(12)a: A spa has at least one stairway, ramp,	5.	15.4(1)c & 15.51(1)f: Wastewater and backwash is
	ladder or set of recessed steps designating a point of entry (built or reconstructed since March 14, 1990).	6.	discharged through an air break or air gap. 15.4(1)d(1) & 15.51(1)g(1): Water supplied to a
6.	15.52(12)a(1)2: Spa stair steps have two hand/grab	0.	pool/spa is discharged to the system through an air gap or a reduced
	rails, one on each side of the steps (built or reconstructed since March 10, 1993).	7.	principle backflow device. 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	15.52(12)c: An emergency shutoff switch near the spa		preventers provided on hose bibs in mechanical room.
	(built or reconstructed since 1999).	8.	☐ ☐ ☐ 15.4(1)e(1) & 15.51(1)h(1): Electric water heaters have UL seal.
WA	ADING Pools	9.	In 15.4(1)e(2) & 15.51(1)h(2): Gas-fired heaters have AGA seal and equipped with a pressure relief valve.
1.	S U N/A 15.4(4)h: Fully submerged outlets not missing or	10.	15.4(1)e(3) & 15.51(1)h(3): Fuel-burning water
2.	broken. 15.4(4)h(1)2: Fully submerged outlet covers/grates	11.	heaters are vented to the outside. 15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning
۷.,	not removable without the use of tools.		equipment has opening(s) to the outside for providing combustion
3.	☐ ☐ 15.4(4)I(4): Wading pool within 50 ft of a pool has a barrier at least 36 inches high separating it from the pool or has	12.	air. 15.4(2)g: Knowledgeable person in testing
	written alternate management plan on-site.		water/operating water treatment equipment available when pool is open for use.
4.	☐ ☐ ☑ 15.4(4)I(5): Gates/doors are self-closing and self-latching (where lifeguards are not provided).	13.	15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming
5.	☐ ☐ ☐ ☐ 15.4(6)d(1): 'No Lifeguard' (Children must be accompanied by an adult) sign posted at each wading pool entry		pool/spa facility has water testing equipment for free chlorine & combined chlorine, or total bromine; pH; total alkalinity; calcium
	where lifeguards are not provided.		hardness; & cyanuric acid.
6.	15.4(4)j(4):Maximum depth of wading pool at each entrance and one location inside enclosure (letters or numbers 3in	14.	☐ ☐ 15.4(2)f(4)-(5) & 15.51(2)f(4)-(5): ORP/pH controller with numerical analog or digital display
	high).	15.	15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection
DI/	/ING BOARDS	16.	feed equipment installed and operational. 15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
	S U N/A 15.4(4)c(6): Diving boards/platforms have slip-		feed equipment installed and operational (built or reconstructed since July 1, 1998).
1.	resistant surfaces.	17.	15.4(3)b(2): A vacuum cleaning system is provided.
2.	☐ ☐ 15.4(4)c(8)-(9): Diving board handrails and guard rails present and secure.	18.	15.4(6)j & 15.51(5)i: A schematic drawing of the recirculation system is posted or clear labeling of piping with flow
3.	☐ ☐ ☐ 15.4(4)c(10): Diving board supports, platforms &		direction and water status (unfiltered, treated, backwashed).
	steps have no obvious visual structural problems.	СН	EMICAL STORAGE
WA	ATER SLIDES	1.	S U N/A 15.4(4)a(2) & 15.51(4)a(2): Swimming pool/spa
1.	S U N/A 15.4(4)d(5): Water slide has a lifeguard (or shallow		chemicals properly stored & handled.
2.	water guard where applicable) at the top and bottom of slide. 15.4(4)o(1): Water slide support structures are free of	2.	☐ ☐ 15.4(4)a(4) & 15.51(4)a(4): Chemical storage conţainers clearly labeled.
	obvious structural defects.	3.	☐ 15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	☐ ☐ ☑ 15.4(4)o(2): The walkable surface of flume is smooth and continuous.		warning placed at the entrances to rooms where chemical are used or stored.
4.	15.4(4)o(3): The walkable surface of flume has no	4.	☐ ☐ ✓ 15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single submerged outlet that is not unblockable is equipped with a SVRS.
	sharp edges within reach of a user while in the proper sliding position.	5.	15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more
5.	☐ ☐ ☐ 15.4(6)e (1)-(6): Water slide rules are posted near the slide.	6.	than 15 V equipped with a GFCI. 15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	☐ ☐ 15.5(17)b(1): Plunge pool depth is at least 3ft and no		gallons have secondary containment (built or reconstructed since
7.	more than 4ft. 15.5(17)b(4): Landing area for a water slide is		May 4, 2005).
	designated by a float line or a painted area.		

CHLOR	INE GAS	8.	☐ ☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S	U N/A		preventers provided on all hose bibs in the bathhouse.
1.	15.4(4)n(1)1: Chlorine gas room has an exhaust		
SVS	stem.	SPI	RAY PADS
2.	15.4(4)n(1)2: An air intake provided near the ceiling.		S U N/A,
3.	15.4(4)n(1)3: The exhaust fan shall be operated from	1.	15.5(19)a: The surface of a spray pad shall be
	witch labeled "Chlorine Exhaust Fan" in a nearby location outside		impervious and durable. Padding specifically designed for spray pads
	e chlorine room or building.	_	may be used with play features.
4.	☐ 15.4(4)n(1)4: Discharge from exhaust system outside	2.	☐ ☑ 15.5(19)b: The spray pad surface shall slope to drain.
of	pool enclosyre		Deck or other areas outside the spray pad shall not drain into the
5.	15.4(4)n(1)5: Artificial lighting provided in chlorine		spray pad.
roc		3.	15.5(19)c: Unless the spray pad is supervised by
6.	15.4(4)n(1)7: A plastic bottle of commercial strength		facility staff, a sign shall be posted near the spray pad that
_			
-	monia solution for leak detection.		addresses: No running on or around the spray pad, No rough play,
7.	☐ 15.4(4)n(2)1: Chlorine gas cylinders are individually		No facility supervision. Parents are responsible for supervising their
an	chored with safety chains or straps		children.
		4.	15.5(19)d: Spray pads drains shall be gravity outlets.
ВАТНН	OUSE		At least two drains or a single drain that is unblockable shall be
			provided,
. S	U N/A	p=	
1.	15.4(5): Showers, dressing rooms & sanitary facilities	5.	15.5(19)e(2): On independent treatment systems the
are	e clean & free of debris.		tank shall be accessible for cleaning and inspection.
2.	15.4(5)a-b: Floors slip-resistant and maintained	6.	☐ ☐ 15.5(19)e(3): On independent treatment systems the
wit	thout standing water.		recirculation treatment system and play feature pump and piping
3.	15.4(5)c: Carpet not in wet areas of the		system shall be separate.
		7.	
_	thhouse/dressing area.	1.	15.5(19)e(5): On independent treatment systems the
4.	Light 15.4(5)d: Lavatories, showers & sanitary facilities		play feature pump system shall be designed so that it will not
fur	nctional.		operate if the recirculation system in not operating.
5. W	15.4(5)e: Soap at each lavatory and indoor shower		
	tures.	low	VA SMOKEFREE AIR ACT
	☐ 15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the		S \U
	blic dressing, lavatory, and shower areas are protected by GFCI	1.	Iowa Code §142D: No violations observed (No evidence of
	ceptacles at the outlet or breaker serving the outlet.		smoking in prohibited areas, no ashtrays present, signs posted at
7.	15.5(21)e: Hose bib(s) provided within the bathhouse		entrances)
(bu	uilt or reconstructed since March 14, 1990) .		ŗ
Comm	ents/Recommendations:		
Commi	ents/ Neconninentations.		
1		(1
	lo violations observed on	1	Ms day.
^			
	Lecond Keeping was complete	- 1	and Organized very well.
	'		
	Y Y		
	ne pool deck paint is becomer discussed pokutally p	CHIV	ining to show wear
		. ·	. , . ,
C	owner olicrossed potentially p	ceiv	thro it or resurfacing this summer
) , , , , , , , , , , , , , , , , , , ,
Comme	outs/Danamandations		
Comm	ents/Recommendations:		
		_	
		_	

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc.) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

	11-20-24
Pool/Spa Representative	Date
CPH Representative	11 20 24 Date
By checking this box, I understand and acknowledge that if the C a special inspection may be conducted and a fee of \$200 will be a	orrective Action Plan is not returned by <u>N (A</u> , applied. *IAC 641 Chapter 15.12 (3)c
Pool/Spa Representative Initials	

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

5

Rev. 2/22/2023 JP

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION

Enforcement 641 15.6(135I)

Facility Name: Comfort Suites Date of Inspection: 11/20 /24
Inspector: Fames Lacina The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within _____ days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to Iowa Code 135I and 641 IAC 15.6. **Deficiency 1:** (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) No violations observed on this day. Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected) Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected) Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected) Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected) **Deficiency 5:** (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

6 Rev. 2/22/2023 JP