

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 lowa City, IA 52240

Date of Inspection	on: 12/5/	24		egistration# Pool Spa Other	SP52-0	164
Facility Name:	ountry 1.	no + Sin		egistration# Pool Spa Other		
Facility Physical	Address:	ert land		ity:	Zipcode:	
Person Contacte	d:	en i maro	E-	Mail:	8 11 6	
Managar on Dub	A los			countrying	and ville	2 gmail.com
Manager on Duty	Drew H	ellina		Mailrellingds	eu 8900	Imail con
Name of CPO(s):	Bhavita	Bhatt	E-	Mail: bhavita.	bhattec	ountry on co
CHEMICAL FEED	SYSTEMS AND SECOND	DARY DISINFECTANT				
Disinfection mak	e and model #:	~ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	111	1 A C 10	1 .	64
Type:	p 411-120	ne (al-P	14 bo (M/100	del) Colo	in contro	Wer
☐ Bromine ☐ 1	Frichlor 🔲 Calcium Hyp	ochlorite M.Sodium H	ypochlorite 🔲 L	ithium Hypochlorite 🔲 CI (g	as) 🗌 Other:	
WATER CHEMIST	RY					
Type (Pool, Spa, Plunge Pool, etc.)	Free Chlorine Pool 1.0-8.0	Bromine	pH	Cyanuric Acid	Controller	Spa Temperature
	Spa 2.0-8.0	Pool 2.0-18.0 Spa 4.0-18.0	Pool 7.2-7.8 Spa 7.2-7.8	Pool 0-40 Spa 0- 40	ORP 700-880 pH 7.2-7.8	<= 104°
Pool	FUI-1.09		7.5		113/7.42	
Spa	TUI-	34	7.5		715/747	
1					, , , , ,	*
ey: S = Satisf	factory U = Unsat	isfactory N/A =	Not Applicable			
CILITY RECORDS	S			6. 🔀 🗆 🗆 15.4(6))	Certified operator life	eguard, first-aid, & CPR
S U N/A	-			certificates.		
registered.	5.9(1) The swimming po	iol or spa is currently		7. 15.4(6)f analyses results.	(2) & 15.51(5)e(2): Mor	nthly microbiological
⊠ □ 15	5.4(2)a(1)-(6) & 15.51(2			8. 🔀 🗌 🗎 15.4(6)f		lity maintains reports of
readings record out of range).	led are in the correct ra	nge (or closures noted	when		, injuries, & illness. Rep	orts submitted as
	5.4(2)e(1)-(6): Swimmin	g pool: ORP and pH at		required. 9. 1 15.4(6)f	(4) & 15.51(5)e(5): Date	es & quantities of
opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total			chemical additions, in	chemical additions, including resupply of chemical feed systems.		
testing monthly		gium nardness & bacte	ria		(5) & 15.51(5)e(6): Date . or a filter cartridge wa:	
	i.4(4)h(1)3 & 15.51(4)f(11. 🔼 🥇 🔲 15.4(6)f	(6) & 15.51(5)e(8): GFC	receptacles & breakers
certification of c etc.) is on-site.	compliance (main drain	, equalizer, feature out	lets,	are tested at least 1x/	month and dates of tes	t dates recorded.
	i.4(4)h(3)1-3 & 15.51(4))f(4)1-3: SVRS product			(7) & 15.51(5)e(9): MSD d date(s) of review reco	S for chemicals on-site, orded.
information tha	t demonstrates complia	ance is on-site. SVRS te	sted	13. 🔀 🔲 🔲 15.4(6)i(1)-(6) & 15.51(5)g(1)-(6	i): Operations manual
monthly and the	e test date(s) recorded.			on-site (water testing	procedures, backwash,	vacuuming, etc.).

FAC	ILITY RECORDS CONT.		15.5(18)c: Each section of a multi-section pool
	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6): A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool.
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	15.4(4)j(3): Depth markers not more than 25ft apart
16	☐ ☐ 15.51(2)e(3):Spa temperature recorded when water		around the deep end of swimming pool.
10.	quality testing is done (104° or less-closures noted when out of temp	25.	15.4(4)j(6): "No Diving" marked in areas where diving
			is not permitted (not more than 25ft apart).
47	range).	26.	15.4(4)j(7): Letters, numbers & graphics marked on
17.	15.51(2)e(1)-(8): Spa: ORP and pH at opening and		decks and slip resistant.
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl	27	15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	resistant, have durable and cleanable surface, are free of litter,
	calcium hardness at each fill & bacteria testing monthly		obstructions & tripping hazards.
18.	15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal	20	15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28.	
	gal 1x every three weeks.		projections or obstructions.
		29.	15.4(4)1(2) & 15.51(4)k(2): Fence, wall, or other
POC	DL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
-	S U N/A	30.	☐ 15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1.	☐ 15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall, building enclosure or combination not less than 4ft high.
1.	adjusting weirs and removable baskets.	31.	15.4(4)I(2) & 15.51(4)k(2): The distance between the
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		ground & the top of the lowest horizontal support is at least 45
2.	openings visible in water less than 8ft deep.		inches.
2		32.	15.4(4)I(3) & 15.51(4)k(3): A gate at least 36 inches
3.	/".V		wide provided for emergency purposes.
	cleaning. 15.4(4)b(1): Ladders or recessed steps provided in the	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
4.	deep portion of pool. Stairs, ladders, recessed steps, or ramps	34.	15.4(4)!(5) & 15.51(4)k(4): Gates/doors are self-
	geep portion of pool. Stalls, lauders, recessed steps, or ramps		closing and self-latching (where lifeguards are not provided).
_	provided in the shallow portion if more than 2ft deep. 15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	35.	15.4(4)I(5): Indoor pool enclosed by barrier at least
5.			3ft high if there are sleeping rooms, hallways, apartments,
-	are securely anchored.		condominiums or permanent recreation areas used by children that
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		open directly into the swimming pool area.
	from the pool wall. The bottom end of ladder is within one inch of	36.	☐ ☐ ☐ 15.4(4)I(6): Wave pool has a continuous barrier at
	the pool wall and covered with a smooth non-metallic cap.		least 42 inches high along the full length of each side of the wave
7.	15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		pool.
	are slip resistant.	37.	(1) 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,	01.	pool deck equipped with (GFCI) at the outlet or at the breaker
	ladders, ramps, or stairs installed on each side.		serving the outlet.
9.	15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have	38	15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
	securely anchored grab rails or handrails.	50.	for indoor or outdoor pools/spas used after sunset (overhead and/or
10.	15.4(4)b(8): Stairs have slip resistant color contrasting		underwater lights) are functional.
	stripe at least 1 inch wide marked at the leading edge of each tread.	20	15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legibie pool rules
11.	☐ ☐ 15.4(4)e: Elevated lifeguard chairs (where required)	33.	signs posted at two locations (No Diving, No Rough Play, No
	are provided.		Running)
12.	15.4(4)f(1): Required lifesaving equipment provided.	40	
13.	15.4(4)f(4): First-aid kit containing bandages, 4x4	40.	accompanied by an adult) sign posted at each swimming pool entry
	bandage compress, self-adhering gauze bandage, disposable gloves		where lifeguards are not provided.
	& chemical cold compress. Signage if required.	4.4	
14.	\[\begin{align*} \begin{align*}	41.	15.5(4)h & 15.51(4)h(3): At least one hose bib
	lifeguards)		provided for flushing the deck(built or reconstructed since March 14
15.	15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
	telephone with instruction. Signage posted as required.	42.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
16.	15.4(4)g & 15.51(4)e: Pool/spa water levels		preventers provided on all hose bibs on the deck.
	maintained at the skimming level.	43.	15.4(4)c(2): Starting blocks removed, covered, or a
17.	15.4(4)h & 15.51(4)f: Fully submerged outlets not		sign posted to prevent use by the public during general use periods
	missing or broken.	44.	15.5(4)d & 15.52(4)b: The decks drain away from the
18,	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer		swimming pool/spa (built or reconstructed since March 10, 1993).
	openings VGB compliant or the equalizers plugged.	45.	15.5(13)f(3): Where pool depth changes from shallow
19.	15.4(4)i(1): The bottom and sides of pool are white or		to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
	light color.		depth (built or reconstructed since March 14, 1990).
20	. 🔲 🔲 🎁 15.4(4)i(3): The shallow & deep water (5ft) or change	46.	15.4 & 15.51: A swimming pool/spa is operated in a
	in slope is marked by a float line with floats spaced no more than 5ft		safe, sanitary manner.
	apart.		
	-		

SP		<u>IVI</u>	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S U N/A 15.4(1)a & 15.51(1)a: Filtration system is in good
2.		2.	working condition. 15.4(1)b(1) & 15.51(1)c: The recirculation system is
3.	persons and timer is 10 minutes or less. Direction 15.51(5)b: Spa rules sign (8 required stipulations)	3.	operating continuously (except for backwashing or servicing). 15.4(1)b(1) & 15.51(1)c: The circulation system flow
4.	posted. Discrete in the posted in the poste	4.	meter(s) are functional. 1. 15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and
	numbers 3in high).		after) filter pump
5.	15.52(12)a: A spa has at least one stairway, ramp, ladder or set of recessed steps designating a point of entry (built or	5.	☐ ☐ 15.4(1)c & 15.51(1)f: Wastewater and backwash is discharged through an air break or air gap.
	reconstructed since March 14, 1990).	6.	☐ ☐ 15.4(1)d(1) & 15.51(1)g(1): Water supplied to a
6.	15.52(12)a(1)2: Spa stair steps have two hand/grab rails, one on each side of the steps (built or reconstructed since		pool/spa is discharged to the system through an air gap or a reduced principle backflow device.
	March 10, 1993).	7.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	15.52(12)c: An emergency shutoff switch near the spa	• •	preventers provided on hose bibs in mechanical room.
	(built or reconstructed since 1999).	8.	15.4(1)e(1) & 15.51(1)h(1): Electric water heaters
		_	have UL séal.
WA	ADING Pools S U N/A	9.	AGA seal and equipped with a pressure relief valve.
1.	S U N/A 15.4(4)h: Fully submerged outlets not missing or	10.	
	broken.	201	heaters are vented to the outside.
2.	☐ ☐ 15.4(4)h(1)2: Fully submerged outlet covers/grates	11.	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	not removable without the use of tools.		equipment has opening(s) to the outside for providing combustion
3.	☐ ☐ ☐ ☐ 15.4(4)!(4): Wading pool within 50 ft of a pool has a barrier at least 36 inches high separating it from the pool or has	12.	air. 15.4(2)g: Knowledgeable person in testing
	written alternate management plan on-site.	12.	water/operating water treatment equipment available when pool is
4.	☐ ☐ ☑ 15.4(4)I(5): Gates/doors are self-closing and self-		open for use.
	latching (where lifeguards are not provided).	13.	15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming
5.	☐ ☐ ☑ 15.4(6)d(1): 'No Lifeguard' (Children must be		pool/spa facility has water testing equipment for free chlorine &
	accompanied by an adult) sign posted at each wading pool entry where lifeguards are not provided.		combined chlorine, or total bromine; pH; total alkalinity; calcium hardness; & cyanuric acid.
6.	15.4(4)j(4):Maximum depth of wading pool at each	14.	15.4(2)f(4)-(5) & 15.51(2)f(4)-(5): ORP/pH controller
	entrance and one location inside enclosure (letters or numbers 3in		with numerical analog or digital display
	high).	15.	15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection
DD	ING BOARDS	16	feed equipment installed and operational. 15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
DIV	S U N/A	20.	feed equipment installed and operational (built or reconstructed
1.	☐ ☐ 15.4(4)c(6): Diving boards/platforms have slip-		since July 1, 1998).
	resistant surfaces.		15.4(3)b(2): A vacuum cleaning system is provided.
2.	☐ ☐ ☑ 15.4(4)c(8)-(9): Diving board handrails and guard rails present and secure.	18.	☐ 15.4(6)] & 15.51(5)i: A schematic drawing of the recirculation system is posted or clear labeling of piping with flow
3.	☐ ☐ IS 15.4(4)c(10): Diving board supports, platforms &		direction and water status (unfiltered, treated, backwashed).
	steps have no obvious visual structural problems.		
14/4	TER CLUDES	CH:	EMICAL STORAGE
VVA	NTER SLIDES S U N/A	1.	S U N/A
1.	☐ ☐ 15.4(4)d(5): Water slide has a lifeguard (or shallow		chemicals properly stored & handled.
	water guard where applicable) at the top and bottom of slide.	2.	15.4(4)a(4) & 15.51(4)a(4): Chemical storage
2.	☐ ☐ 15.4(4)o(1): Water slide support structures are free of obvious structural defects.	2	containers clearly labeled. 15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	15.4(4)o(2): The walkable surface of flume is smooth	3.	In the state of th
	and continuous.		or stored.
4.	☐ ☐ ☐ ☐ 15.4(4)o(3): The walkable surface of flume has no	4.	15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single
	sharp edges within reach of a user while in the proper sliding	e	submerged outlet that is not unblockable is equipped with a SVRS.
5.	position. 15.4(6)e (1)-(6): Water slide rules are posted near the	5.	15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more than 15 V equipped with a GFCI.
	slide.	6.	☐ ☐ 15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	☐ ☐ 15.5(17)b(1): Plunge pool depth is at least 3ft and no		gallons have secondary containment (built or reconstructed since
7	more than 4ft.		May 4, 2005).
7.	☐ ☐ ☐ ☐ 15.5(17)b(4): Landing area for a water slide is designated by a float line or a painted area.		

CHLO:	RINE GAS	8.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S			preventers provided on all hose bibs in the bathhouse.
1.	15.4(4)n(1)1: Chlorine gas room has an exhaust		
5)	ystem.	SPR	AY PADS
2.	15.4(4)n(1)2: An air intake provided near the ceiling.		S U N/A
3.	15.4(4)n(1)3: The exhaust fan shall be operated from	1.	15.5(19)a: The surface of a spray pad shall be
а	switch labeled "Chlorine Exhaust Fan" in a nearby location outside		impervious and durable. Padding specifically designed for spray pads
tŀ	ne chlorine room or building.		may be used with play features.
4.	☐ ☐ 15.4(4)n(1)4: Discharge from exhaust system outside	2.	☐ ☐ 15.5(19)b: The spray pad surface shall slope to drain.
	f pool enclosure		Deck or other areas outside the spray pad shall not drain into the
	15.4(4)n(1)5: Artificial lighting provided in chlorine		spray pad.
5.	,	3.	15.5(19)c: Unless the spray pad is supervised by
	oom	۵,	
6.	15.4(4)n(1)7: A plastic bottle of commercial strength		facility staff, a sign shall be posted near the spray pad that
	mmonia solution for leak detection.		addresses: No running on or around the spray pad, No rough play,
7.	15.4(4)n(2)1: Chlorine gas cylinders are individually		No facility supervision. Parents are responsible for supervising their
a	nchored with safety chains or straps		children.
		4.	☐ ☐ 15.5(19)d: Spray pads drains shall be gravity outlets.
DATH	HOUSE		At least two drains or a single drain that is unblockable shall be
			provided.
. S		5.	15.5(19)e(2): On independent treatment systems the
	15.4(5): Showers, dressing rooms & sanitary facilities	5.	
100	re clean & free of debris.	-	tank shall be accessible for cleaning and inspection.
2.		6.	15.5(19)e(3): On independent treatment systems the
W	rithout standing water.		recirculation treatment system and play feature pump and piping
3.	15.4(5)c: Carpet not in wet areas of the		system shall be separate.
	athhouse/dressing area.	7.	15.5(19)e(5): On independent treatment systems the
	15.4(5)d: Lavatories, showers & sanitary facilities		play feature pump system shall be designed so that it will not
7	unctional.		operate if the recirculation system in not operating.
_			operate it and to an extent of parents in the control of the contr
5.	15.4(5)e: Soap at each lavatory and indoor shower	low	CAROUPPOER AID ACT
	xtures.	IOW	A SMOKEFREE AIR ACT
	15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the		S U
	ublic dressing, lavatory, and shower areas are protected by GFCI	1.	I lowa Code §142D: No violations observed (No evidence of
re	eceptacles at the outlet or breaker serving the outlet.		smoking in prohibited areas, no ashtrays present, signs posted at
7.	15.5(21)e: Hose bib(s) provided within the bathhouse		entrances)
78	built or reconstructed since March 14, 1990) .		,
,			
Come	nents/Recommendations:		
Comi	hency recommendations.		
	· · · · · · · · · · · · · · · · · · ·		
_			
Comr	nents/Recommendations:		
	_	-	

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Coliform bacteria are detected and the above listed requirements are met.

| 12-5-24 |
| Date |
| Date

By checking this box, I understand and acknowledge that if the Corrective Action Plan is not returned by 1/5/24, a special inspection may be conducted and a fee of \$200 will be applied. *IAC 641 Chapter 15.12 (3)c

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION

Facility Name: Country Inn & Suites
Date of Inspection: 12/5/24
Inspector: Emmer Nelson

The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within 36 days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan

section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe material with enforcement action against your facility pursuant to Iowa Code 135I and 641 IAC 15.6.
Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) IS. 4(2)e(1)-(6): Testing Should be recorded every four hours Ensure dates are included on record sheet Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.4(4)h(1) 8 + 15.51(4)f(2)3: VGB certificate for pool and spa drain should be available on site Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.4 (6/6 (7) + 15.81(5)e(9): Safety data sheets should be available for chemicals on site, reviewed annually with review dates recorde Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15. SI(2)e(3): Spa temperature should be recorded when testing is completed Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 5: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.51(2) c(1)-(8): ORP and PH recorded every 2 hours. Manually tested at least twice a day Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

<u>Deficiency 6</u> : (Cite 641 IAC Chapter 15 violation and man 15.51 (3) b(2): Doubes of W	ner in which the facility failed to comply) hen spen is dramed + refilled should ed
be recordi	ed
Corrective Action Plan: (this section to be completed by	y the facility to indicate how the deficiencies will be corrected)
	ner in which the facility failed to comply) n Pool is Missing cup on He end ty the facility to indicate how the deficiencies will be corrected)
Deficiency 8: (Cite 641 IAC Chapter 15 violation and man 15, 4(5) e: Soap should	
Corrective Action Plan: (this section to be completed by	by the facility to indicate how the deficiencies will be corrected)
Deficiency 9: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	by the facility to indicate how the deficiencies will be corrected)
Deficiency 10: (Cite 641 IAC Chapter 15 violation and ma	nner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
*** Additional identified deficiencies may be listed on The deficiencies noted during the inspection shall be a original signed copy of this document to:	attached pages. ddressed by completing this Corrective Action Plan within days and submitting an
	Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240
Pool Representative:	Date:

Deficiency 11: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 12: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 13: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 14:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 15:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)