

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 Iowa City, IA 52240

Date of Inspection:			F	Registration # 3PS2~0 84				
Facility Name: Drury Inn + Suites				Registration #				
Facility Physical Address: 815 15+ Ave, Coval ville				City: Covalville Zipcode: 52241				
Person Contacted			E	-iviaii:		acketine	11. (em	
Manager on Duty: Chad Pitlik				E-Mail: Jafletcher @ (ocketmail. com				
Name of CPO(s):	Josh Fleto		E	E-Mail:				
•								
1000,000,000,000,000	SYSTEMS AND SECOND	ARY DISINFECTANT						
1,460.	in bow (Made	(300-29x) Po					mine	
Bromine Ti	richlor 🔲 Calcium Hyp	ochlorite	ypochlorite 🔲	Lithium Hypochlorite	CI (gas)	Other:		
WATER CHEMISTI	RY		7			Dr. Ve		
Type (Pool, Spa, Plunge Pool, etc.)	Free Chlorine Pool 1.0-8.0 Spa 2.0-8.0	Bromine Pool 2.0-18.0 Spa 4.0-18.0	pH Pool 7.2-7.8 Spa 7.2-7.8	Cyanuric 4 Pool 0-4 Spa 0- 4	0	Controller ORP 700-880 pH 7.2-7.8	Spa Temperature <= 104°	
Pool	fel - 229 Tcl - 2.29	•	7.6	CH- 15	3	820		
Spa		7.6	7.5	A1K-19		791		
•								
(ey: S = Satisf	actory U = Unsat	isfactory N/A =	Not Applicabl	e				
ACILITY RECORDS	6			6. 🗹 🗆 🗆	15.4(6) h: Ce	rtified operator, li	feguard, first-aid, & CPR	
S U N/A 15.9(1) The swimming pool or spa is currently				certificates. 7.				
registered. . I 15.4(2)a(1)-(6) & 15.51(2)a(1)-(6):Water quality readings recorded are in the correct range (or closures noted when				analyses res	ults. 15.4(6)f(3) 8	& 15.51(5)e(4): Fac	cility maintains reports of ports submitted as	
out of range). i. I 15.4(2)e(1)-(6): Swimming pool: ORP and pH at				required.	15.4(6)f(4) 8	& 15.51(5)e(5) : Dat	tes & quantities of	
opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total alkalinity and cyanuric acid weekly; calcium hardness & bacteria				chemical additions, including resupply of chemical feed systems. 10.				
testing monthly.				backwashed, cleaned, or a filter cartridge was changed. 11.				
certification of compliance (main drain, equalizer, feature outlets, etc.) is on-site.				are tested at least 1x/month and dates of test dates recorded. 12. 15.4(6)f(7) & 15.51(5)e(9): MSDS for chemicals on-site,				
information that demonstrates compliance is on-site. SVRS tested monthly and the test date(s) recorded.				13. 🗹 🗌 🗀	15.4(6)i(1)-(corded. (6): Operations manual n, vacuuming, etc.).	

FAC	CILITY RECORDS CONT.	21.	☐ ☐ 15.5(18)c: Each section of a multi-section pool is
	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6)!: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool.
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	☐ ☐ 15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	15.4(4)j(3): Depth markers not more than 25ft apart
16.	15.51(2)e(3):Spa temperature recorded when water		around the deep end of swimming pool.
	quality testing is done (104° or less-closures noted when out of temp	25.	15.4(4)j(6): "No Diving" marked in areas where diving
	range).		is not permitted (not more than 25ft apart).
17.	☐ 15.51(2)e(1)-(8): Spa: ORP and pH at opening and	26.	15.4(4)j(7): Letters, numbers & graphics marked on
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl		decks and slip resistant.
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	calcium hardness at each fill & bacteria testing monthly		resistant, have durable and cleanable surface, are free of litter,
18.			obstructions & tripping hazards.
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28.	15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	gal 1x every three weeks.		projections or obstructions.
		29.	15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
PO	OL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
	S U N/A	30.	15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1.	☐ ☐ 15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-	50.	wall, building enclosure or combination not less than 4ft high.
	adjusting weirs and removable baskets.	31.	15.4(4)I(2) & 15.51(4)k(2): The distance between the
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		ground & the top of the lowest horizontal support is at least 45
	openings visible in water less than 8ft deep.		inches.
3.	☐ 15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	15.4(4)I(3) & 15.51(4)k(3): A gate at least 36 inches
	cleaning.		wide provided for emergency purposes.
4.	15.4(4)b(1): Ladders or recessed steps provided in the	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
	deep portion of pool. Stairs, ladders, recessed steps, or ramps	34.	15.4(4)I(5) & 15.51(4)k(4): Gates/doors are self-
	provided in the shallow portion if more than 2ft deep.		closing and self-latching (where lifeguards are not provided).
5.	15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	35.	15.4(4)I(5): Indoor pool enclosed by barrier at least
	are securely anchored.		3ft high if there are sleeping rooms, hallways, apartments,
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		condominiums or permanent recreation areas used by children that
	from the pool wall. The bottom end of ladder is within one inch of	2.0	open directly into the swimming pool area.
	the pool wall and covered with a smooth non-metallic cap.	36.	
7.	15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		least 42 inches high along the full length of each side of the wave
	are slip resistant.	27	pool. 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,	37.	
	ladders, ramps, or stairs installed on each side.		pool deck equipped with (GFCI) at the outlet or at the breaker
9.	15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have	20	serying the outlet.
	securely anchored grab rails or handrails.	38.	15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10.	15.4(4)b(8): Stairs have slip resistant color contrasting		for indoor or outdoor pools/spas used after sunset (overhead and/or
	stripe at least 1 inch wide marked at the leading edge of each tread.	20	underwater lights) are functional. 15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
11.		39.	
	are provided.		signs posted at two locations (No Diving, No Rough Play, No
12.	15.4(4)f(1): Required lifesaving equipment provided.	40	Running) 15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
13.		40.	accompanied by an adult) sign posted at each swimming pool entry
	bandage compress, self-adhering gauze bandage, disposable gloves		where lifeguards are not provided.
	& chemical cold compress. Signage if required.	41.	
14.	,,,,,	41.	provided for flushing the deck(built or reconstructed since March 14,
45	lifeguards)		1990).
15.	15.4(4)f(6) & 15.51(4)d: A designated emergency	12	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
10	telephone with instruction. Signage posted as required.	72,	preventers provided on all hose bibs on the deck.
16.	15.4(4)g & 15.51(4)e: Pool/spa water levels	43.	
17	maintained at the skimming level.	73.	sign posted to prevent use by the public during general use periods.
1/.	15.4(4)h & 15.51(4)f: Fully submerged outlets not	44	2 15.5(4)d & 15.52(4)b: The decks drain away from the
10	missing or broken.	771	swimming pool/spa (built or reconstructed since March 10, 1993).
TQ.	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer	45.	
10	openings VGB compliant or the equalizers plugged. 15.4(4)i(1): The bottom and sides of pool are white or	.5.	to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
TJ.	light color.		depth (built or reconstructed since March 14, 1990).
20.		46.	15.4 & 15.51: A swimming pool/spa is operated in a
ZU.	in slope is marked by a float line with floats spaced no more than 5ft	.51	safe, sanitary manner.
	in slope is marked by a noat line with hoats spaced no more triall sit		

apart.

SPA		ME	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S U N/A 15.4(1)a & 15.51(1)a: Filtration system is in good working condition.
2.	104°F. 15.51(4)I: Agitation system control out of reach of persons and timer is 10 minutes or less.	2.	operating continuously (except for backwashing or servicing).
3.	persons and timer is 10 minutes of less. 15.51(5)b: Spa rules sign (8 required stipulations) posted.	3.	meter(s) are functional.
4.	15.51(5)c: Maximum spa depth posted (letters or numbers 3in high).	4.	after) filter pump
5.	15.52(12)a: A spa has at least one stairway, ramp, ladder or set of recessed steps designating a point of entry (built or	5.	15.4(1)c & 15.51(1)f: Wastewater and backwash is discharged through an air break or air gap.
6.	reconstructed since March 14, 1990). 15.52(12)a(1)2: Spa stair steps have two hand/grab	6.	15.4(1)d(1) & 15.51(1)g(1): Water supplied to a pool/spa is discharged to the system through an air gap or a reduced
	rails, one on each side of the steps (built or reconstructed since March 10, 1993).	7.	principle backflow device. 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	(built or reconstructed since 1999).	8.	preventers provided on hose bibs in mechanical room. 15.4(1)e(1) & 15.51(1)h(1): Electric water heaters have UL seal.
WA	DING Pools	9.	AGA seal and equipped with a pressure relief valve.
1.	S U N/A 15.4(4)h: Fully submerged outlets not missing or broken.	10.	☐ ☐ 15.4(1)e(3) & 15.51(1)h(3): Fuel-burning water heaters are vented to the outside.
2.	15.4(4)h(1)2: Fully submerged outlet covers/grates not removable without the use of tools.	11.	☐ ☐ 15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning equipment has opening(s) to the outside for providing combustion
3.	15.4(4)I(4): Wading pool within 50 ft of a pool has a barrier at least 36 inches high separating it from the pool or has	12.	air. 15.4(2)g: Knowledgeable person in testing
4.	written alternate management plan on-site. [] [] 15.4(4)I(5): Gates/doors are self-closing and self-latching (where lifeguards are not provided).	12	water/operating water treatment equipment available when pool is open for use. 15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming
5.	Tatching (where inlegial us are not provided). To it is a serior provided). To it is a serior provided). To it is a serior provided in the	13.	pool/spa facility has water testing equipment for free chlorine & combined chlorine, or total bromine; pH; total alkalinity; calcium
6.	where lifeguards are not provided. 15.4(4)j(4):Maximum depth of wading pool at each	14.	
	entrance and one location inside enclosure (letters or numbers 3in high).	15.	with numerical analog or digital display 15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection
DIV	ING BOARDS	16.	feed equipment installed and operational. 15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
1.	S U N/A 15.4(4)c(6): Diving boards/platforms have slip-		feed equipment installed and operational (built or reconstructed singe July 1, 1998).
2.	resistant surfaces.		15.4(3)b(2): A vacuum cleaning system is provided. 15.4(6)j & 15.51(5)i: A schematic drawing of the
3.	present and secure. 15.4(4)c(10): Diving board supports, platforms &		recirculation system is posted or clear labeling of piping with flow direction and water status (unfiltered, treated, backwashed).
	steps have no obvious visual structural problems.	СНЕ	MICAL STORAGE
WA	ATER SLIDES		S U N/A
1.	S U N/A 15.4(4)d(5): Water slide has a lifeguard (or shallow	1.	☐ ☐ 15.4(4)a(2) & 15.51(4)a(2): Swimming pool/spa chemicals properly stored & handled.
2.	water guard where applicable) at the top and bottom of slide. 15.4(4)o(1): Water slide support structures are free of	2.	☐ ☐ 15.4(4)a(4) & 15.51(4)a(4): Chemical storage containers clearly labeled.
3.	obvious structural defects. 15.4(4)o(2): The walkable surface of flume is smooth	3.	warming placed at the entrances to rooms where chemical are used
٥.	and continuous.		or stored.
4.	15.4(4)o(3): The walkable surface of flume has no sharp edges within reach of a user while in the proper sliding	4. 5.	□ □ 15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single submerged outlet that is not unblockable is equipped with a SVRS. □ □ 15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more
5.	position. 15.4(6)e (1)-(6): Water slide rules are posted near the slide.	5. 6.	than 15 V equipped with a GFCI. 15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	15.5(17)b(1): Plunge pool depth is at least 3ft and no more than 4ft.		gallons have secondary containment (built or reconstructed since May 4, 2005).
7.	15.5(17)b(4): Landing area for a water slide is designated by a float line or a painted area.		

CHLORINE GAS	8. 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S U N/A	preventers provided on all hose bibs in the bathhouse.
1.	
system.	SPRAY PADS
2. 15.4(4)n(1)2: An air intake provided near the ceiling.	S U N/A
3.	1.
a switch labeled "Chlorine Exhaust Fan" in a nearby location outside	impervious and durable. Padding specifically designed for spray pad
the chlorine room or building.	may be used with play features.
4. 15.4(4)n(1)4: Discharge from exhaust system outside	2. 🔲 🔲 15.5(19)b: The spray pad surface shall slope to drain.
of pool enclosure	Deck or other areas outside the spray pad shall not drain into the
5. 15.4(4)n(1)5: Artificial lighting provided in chlorine	spray pad.
room	3. 15.5(19)c: Unless the spray pad is supervised by
6. 15.4(4)n(1)7: A plastic bottle of commercial strength	facility staff, a sign shall be posted near the spray pad that
ammonia solytion for leak detection.	addresses: No running on or around the spray pad, No rough play,
7.	No facility supervision. Parents are responsible for supervising their
anchored with safety chains or straps	children.
	4. 15.5(19)d: Spray pads drains shall be gravity outlets.
BATHHOUSE	At least two drains or a single drain that is unblockable shall be
S U N/A	provided.
	The state of the s
1. I 15.4(5): Showers, dressing rooms & sanitary facilities	5. 15.5(19)e(2): On independent treatment systems the
are clean & free of debris.	tank shall be accessible for cleaning and inspection.
2. If 15.4(5)a-b: Floors slip-resistant and maintained	6.
without standing water.	recirculation treatment system and play feature pump and piping
	system shall be separate.
3.	
bathhouse/dressing area.	7.
4. 15.4(5)d: Lavatories, showers & sanitary facilities	play feature pump system shall be designed so that it will not
functional.	operate if the recirculation system in not operating.
	operate it the roth dutation by seem in the operating.
fixtures.	IOWA SMOKEFREE AIR ACT
6. 15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the	S LJ
public dressing, lavatory, and shower areas are protected by GFCI	1. Iowa Code §142D: No violations observed (No evidence of
receptacles at the outlet or breaker serving the outlet.	
	smoking in prohibited areas, no ashtrays present, signs posted at
7. 15.5(21)e: Hose bib(s) provided within the bathhouse	entrances)
(built or reconstructed since March 14, 1990).	
Comments/Recommendations:	
Comments/ Recommendations.	
5 5 4 1 1	
- Facility continues to use an	and to electronically record
pool & spa chemical testing, h	sackwashing, Clemical additions
and more. Data is reviewed by	by Regional management. Inspector
was able to review the ele	chance do to through the
	Zinder Carlotte
arp dalabase,	
\	
Comments/Recommendations:	

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Pool/Spa Representative	11/,5/24 Date
JCPH Representative	11/15/24 Date

By checking this box, I understand and acknowledge that if the Corrective Action Plan is not returned by 12/15/24, a special inspection may be conducted and a fee of \$200 will be applied. *IAC 641 Chapter 15.12 (3)c

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION

Enforcement 641 15.6(135I)

Facility Name: Orung Inn + Suites Date of Inspection: 1115/24 Inspector: James Lacina
The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within 30 days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to lowa Code 135I and 641 IAC 15.6.
Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) A chemical hazard warming (abel must be placed at entrenes to rooms where clemicals are used corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected).
<u>Deficiency 2</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 5: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (Cita this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deticiency 6: (Cite 641 IAC Chapter 15 violation and manner in which the facility falled to comply)	
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)	
Deficiency 7: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)	
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)	
Deficiency 8: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)	
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)	
Deficiency 9: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)	
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)	
<u>Deficiency 10:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)	
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)	
*** Additional identified deficiencies may be listed on attached pages. The deficiencies noted during the inspection shall be addressed by completing this Corrective Action Plan within 30 days and submitting	, an
original signed copy of this document to:	
Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240	
Pool Representative: Date:	

Deficiency 11 : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 12</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 13:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 14:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 15: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)