

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 lowa City, IA 52240

Date of Inspection: \\\/27/24				Registration # SP52-076 (00			
Facility Name: Grand Living at Bridgewater							
Facility Physical Address: 3 Russel Slade Blud, (oralville					Coralville	Zipcode: 5	2241
Person Contacted	ier starte r	sind i Coran		E-Mail:			
M	egen Ai	ueabeni					
Manager on Duty:	J		E	E-Mail:			
Name of CPO(s):	supra KI	îen	E	E-Mail: Sklien @ grandliving. com			
	alville 14					- grano n	md . Oir
CHEMICAL FEED	SYSTEMS AND SECONE	DARY DISINFECTANT				_	
Disinfection make	and model #:	48.					
BEC	SysS						
Type:	V						
Bromine DT	richlor	ochlorite Sodlum H	vpochlorite	Lithiur	n Hypochlorite 🔲 Cl (gas	s)	
	Tremer 🖂 Garanant 1777	Joseph C. M. J. G. Carlotte	7,000		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
WATER CHEMIST	RY						
Type (Pool, Spa,	Free Chlorine	Bromine	рН		Cyanuric Acid	Controller	Spa Temperature
Plunge Pool, etc.)	Pool 1.0-8.0	Pool 2.0-18.0	Pool 7.2-7.8	Δ	NK Pool 0-40 Spa 0-40	ORP 700-880	<= 104°
	Spa 2.0-8.0 FC(~ 1.3	Spa 4.0-18.0	Spa 7.2-7.8	-	77 Spa 0- 40	pH 7.2-7.8	
Pool	761 - 3.71		7.3		91		
				-			-
						_	
(ey: S = Satisf	factory U = Unsat	tisfactory N/A =	Not Applicabl	e			
ACILITY RECORDS	3			6.	🔀 🗌 🗎 15.4(6)h	: Certified operator, li	feguard, first-aid, & CPR
S U N/A				certificates.			
. 🔀 🔲 15.9(1) The swimming pool or spa is currently registered.				7.			
registered. 15.4(2)a(1)-(6) & 15.51(2)a(1)-(6):Water quality			/	8. I 15.4(6)f(3) & 15.51(5)e(4): Facility maintains reports of			
readings recorded are in the correct range (or closures noted when				complaints, accidents,	injuries, & illness. Re	ports submitted as	
out of range).				required.			
. – 🔣 🔲 15.4(2)e(1)-(6): Swimming pool: ORP and pH at opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total				 Image: 15.4(6)f(4) & 15.51(5)e(5): Dates & quantities of chemical additions, including resupply of chemical feed systems. 			
alkalinity and cyanuric acid weekly; calcium hardness & bacteria				10. 2 15.4(6)f(5) & 15.51(5)e(6): Dates when filters were			
testing monthly.			h (cp)	backwashed, cleaned, or a filter cartridge was changed.			
. X				 11.			
etc.) is on-site.			en-a-to-j	12. 15.4(6)f(7) & 15.51(5)e(9): MSDS for chemicals on-site,			
. 🔲 🔼 15.4(4)h(3)1-3 & 15.51(4)f(4)1-3: SVRS product				reviewed annually, and date(s) of review recorded.			
information that demonstrates compliance is on-site. SVRS tested			ested	13.	on-site (water testing)		(6): Operations manual
monthly and the test date(s) recorded.				ouraite (water fezillig)	Ji ocedures, Dackwasi	i, vacuuming, etc.).	

FAC	CILITY RECORDS CONT.	21.	
	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6)I: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	☑ 15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool.
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	☐ ☐ 15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	15.4(4)j(3): Depth markers not more than 25ft apart
16.			around the deep end of swimming pool.
	quality testing is done (104° or less-closures noted when out of temp	25.	
	range).		is not permitted (not more than 25ft apart).
17.	☐ ☐ X 15.51(2)e(1)-(8): Spa: ORP and pH at opening and	26.	15.4(4)j(7): Letters, numbers & graphics marked on
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl		decks and slip resistant.
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	☐ 15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	calcium hardness at each fill & bacteria testing monthly		resistant, have durable and cleanable surface, are free of litter,
18.	☐ ☑ 15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal		obstructions & tripping hazards.
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28.	☐ 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	gal 1x every three weeks.		projections or obstructions.
		29.	15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
PO	OL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
10	S U N/A	30.	☐ 15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1	15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall, building enclosure or combination not less than 4ft high.
Δ.	adjusting weirs and removable baskets.	31.	☐ 15.4(4)I(2) & 15.51(4)k(2): The distance between the
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		ground & the top of the lowest horizontal support is at least 45
4-1	openings visible in water less than 8ft deep.		inches.
3.	15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	15.4(4)I(3) & 15.51(4)k(3): A gate at least 36 inches
٥.	cleaning.		wide provided for emergency purposes.
4.	15.4(4)b(1): Ladders or recessed steps provided in the	33.	☐ ☐ 15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
	deep portion of pool. Stairs, ladders, recessed steps, or ramps	34.	☐ 15.4(4)I(5) & 15.51(4)k(4): Gates/doors are self-
	provided in the shallow portion if more than 2ft deep.		closing and self-latching (where lifeguards are not provided).
5.	15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	35.	
J.	are securely anchored.		3ft high if there are sleeping rooms, hallways, apartments,
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		condominiums or permanent recreation areas used by children that
0.	from the pool wall. The bottom end of ladder is within one inch of		open directly into the swimming pool area.
	the pool wall and covered with a smooth non-metallic cap.	36.	
7.	15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		least 42 inches high along the full length of each side of the wave
	are slip resistant.		pool.
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,	37.	☐ 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
O.	ladders, ramps, or stairs installed on each side.		pool deck equipped with (GFCI) at the outlet or at the breaker
9.	☐ ☐ 15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have		serving the outlet.
٥,	securely anchored grab rails or handrails.	38,	☑ ☐ 15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10	15.4(4)b(8): Stairs have slip resistant color contrasting		for indoor or outdoor pools/spas used after sunset (overhead and/or
201	stripe at least 1 inch wide marked at the leading edge of each tread.		underwater lights) are functional.
11	☐ ☐ 15.4(4)e: Elevated lifeguard chairs (where required)	39.	☐ 15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
	are provided.		signs posted at two locations (No Diving, No Rough Play, No
12.			Running)
	15.4(4)f(4): First-aid kit containing bandages, 4x4	40.	☑ 15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
	bandage compress, self-adhering gauze bandage, disposable gloves		accompanied by an adult) sign posted at each swimming pool entry
	& chemical cold compress. Signage if required.		where lifeguards are not provided.
14	☐ ☐ ☐ 15.4(4)f(5):Spine board provided (facilities with	41.	15.5(4)h & 15.51(4)h(3): At least one hose bib
	lifeguards)		provided for flushing the deck(built or reconstructed since March 14
15	15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
201	telephone with instruction. Signage posted as required.	42.	☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
16.			preventers provided on all hose bibs on the deck.
10.	maintained at the skimming level.	43.	☐ ☐ 15.4(4)c(2): Starting blocks removed, covered, or a
17	☐ ☐ 15.4(4)h & 15.51(4)f: Fully submerged outlets not		sign posted to prevent use by the public during general use periods
3.71	missing or broken.	44.	☐ 15.5(4)d & 15.52(4)b: The decks drain away from the
12	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer		swimming pool/spa (built or reconstructed since March 10, 1993).
20.	openings VGB compliant or the equalizers plugged.	45.	
19	15.4(4)i(1): The bottom and sides of pool are white or		to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
200	light color.		depth (built or reconstructed since March 14, 1990).
วก	15.4(4)i(3): The shallow & deep water (5ft) or change	46.	15.4 & 15.51: A swimming pool/spa is operated in a
Z.U.	in slope is marked by a float line with floats spaced no more than 5ft		safe, sanitary manner.

apart.

S U N/A	
1.	n good
2.	
3.	
4.	before and
5. 🔲 🖂 15.52(12)a: A spa has at least one stairway, ramp, 5. 🔀 🔲 15.4(1)c & 15.51(1)f: Wastewater and back	kwash is
reconstructed since March 14, 1990). 6. D [15.4(1)d(1) & 15.51(1)g(1): Water supplie	
6.	
March 10, 1993). 7.	er backflow
(built or reconstructed since 1999). 8. 15.4(1)e(1) & 15.51(1)h(1): Electric water have UL seal.	heaters
WADING Pools 9. ☑ ☐ 15.4(1)e(2) & 15.51(1)h(2): Gas-fired heat	ers have
1. 🔲 🔀 15.4(4)h: Fully submerged outlets not missing or 10. 🙀 🔲 15.4(1)e(3) & 15.51(1)h(3): Fuel-burning v	/ater
2. 15.4(4)h(1)2: Fully submerged outlet covers/grates 11. 15.4(1)e(4) & 15.51(1)h(4): Rooms with fu	
not removable without the use of tools. approximately equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the outside for providing contains a equipment has opening(s) to the equipment has	
barrier at least 36 inches high separating it from the pool or has	
4. open for use. latching (where lifeguards are not provided). 13. 15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimn	ning
5. D 15.4(6)d(1): 'No Lifeguard' (Children must be accompanied by an adult) sign posted at each wading pool entry combined chlorine, or total bromine; pH; total alkalinity;	orine &
where lifeguards are not provided. hardness; & cyanuric acid.	
entrance and one location inside enclosure (letters or numbers 3in with numerical analog or digital display	
high). 15. 🔼 🔲 15.4(3)a(1) & 15.51(3)a(1): Continuous dis	
DIVING BOARDS S U N/A 16.	
1. Since July 1, 1998). resistant surfaces. 17. 1998). 18. 15.4(4)c(6): Diving boards/platforms have slip- since July 1, 1998). 19. 15.4(3)b(2): A vacuum cleaning system is p	rovided.
2. 15.4(4)c(8)-(9): Diving board handralls and guard rails present and secure. 18. 18. 19. 15.4(6)j & 15.51(5)i: A schematic drawing recirculation system is posted or clear labeling of piping versions.	of the
3. 15.4(4)c(10): Diving board supports, platforms & direction and water status (unfiltered, treated, backwash steps have no obvious visual structural problems.	
CHEMICAL STORAGE	
WATER SLIDES S U N/A S U N/A 1. □ □ 15.4(4)a(2) & 15.51(4)a(2): Swimming pool	/spa
1. D 15.4(4)d(5): Water slide has a lifeguard (or shallow chemicals properly stored & handled.	
water guard where applicable) at the top and bottom of slide. 2. \(\sqrt{15.4(4)a(4) \& 15.51(4)a(4)}: \) Chemical stora	ge
2. \[\bigcup \frac{\text{total 15.4(4)o(1): Water slide support structures are free of obvious structural defects.} \] containers clearly labeled. 3. \[\bigcup \bigcup \frac{15.4(4)a(5) & 15.51(4)a(5): A chemical hazer containers clearly labeled.} \]	ard
3. 15.4(4)o(2): The walkable surface of flume is smooth warning placed at the entrances to rooms where chemical warning placed at the entrances to rooms where chemical surface of flume is smooth.	
4.	
sharp edges within reach of a user while in the proper sliding submerged outlet that is not unblockable is equipped wit position. 5. In 15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater I	
5. \[\bigcap \infty \] 15.4(6)e (1)-(6): Water slide rules are posted near the slide. \[\text{than 15 V equipped with a GFCI.} \] 6. \[\bigcap \infty \] 15.5(11)g: Sodium hypochlorite tanks large	er than 55
6. Sallons have secondary containment (built or reconstruct more than 4ft. May 4, 2005).	
7.	

CHI	ORINE GAS	8.	☐ ☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
	S U N/A		preventers provided on all hose bibs in the bathhouse.
1.	☐ ☐ 315.4(4)n(1)1: Chlorine gas room has an exhaust		
	system.	SPI	RAY PADS
2.	15.4(4)n(1)2: An air intake provided near the ceiling.		S U N/A
3.	15.4(4)n(1)3: The exhaust fan shall be operated from	1.	☐ ☐ 🔀 15.5(19)a: The surface of a spray pad shall be
	a switch labeled "Chlorine Exhaust Fan" in a nearby location outside		impervious and durable. Padding specifically designed for spray pads
	the chlorine room or building.		may be used with play features.
4.	☐ ☐ X 15.4(4)n(1)4: Discharge from exhaust system outside	2.	15.5(19)b: The spray pad surface shall slope to drain.
	of pool enclosure		Deck or other areas outside the spray pad shall not drain into the
5.	☐ ☐ ☑ 15.4(4)n(1)5: Artificial lighting provided in chlorine		spray pad.
	room	3.	15.5(19)c: Unless the spray pad is supervised by
6.	☐ ☐ ☑ 15.4(4)n(1)7: A plastic bottle of commercial strength		facility staff, a sign shall be posted near the spray pad that
٥.	ammonia solution for leak detection.		addresses: No running on or around the spray pad, No rough play,
7.	☐ ☐ ☎ 15.4(4)n(2)1: Chlorine gas cylinders are individually		No facility supervision. Parents are responsible for supervising their
<i>,</i> .	anchored with safety chains or straps		children.
	andiored with safety chains of straps	4.	15.5(19)d: Spray pads drains shall be gravity outlets.
DAT	THIOLICE	7.	At least two drains or a single drain that is unblockable shall be
BAI	THHOUSE THE THE THE THE THE THE THE THE THE TH		provided.
	S U N/A	5.	<u></u>
1.	15.4(5): Showers, dressing rooms & sanitary facilities	Э,	
	are clean & free of debris.	_	tank shall be accessible for cleaning and inspection.
2.	15.4(5)a-b: Floors slip-resistant and maintained	6.	15.5(19)e(3): On independent treatment systems the
	without standing water.		recirculation treatment system and play feature pump and piping
3.	15.4(5)c: Carpet not in wet areas of the		system shall be separate.
	bathhouse/dressing area.	7.	15.5(19)e(5): On independent treatment systems the
4.	15.4(5)d: Lavatories, showers & sanitary facilities		play feature pump system shall be designed so that it will not
	functional.		operate if the recirculation system in not operating.
5.	15.4(5)e: Soap at each lavatory and indoor shower		
	fixtures.	low	VA SMOKEFREE AIR ACT
6.	☐ 15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the		S_U
	public dressing, lavatory, and shower areas are protected by GFCI	1.	lowa Code §142D: No violations observed (No evidence of
	receptacles at the outlet or breaker serving the outlet.		smoking in prohibited areas, no ashtrays present, signs posted at
7.	15.5(21)e: Hose bib(s) provided within the bathhouse		entrances)
-	(built or reconstructed since March 14, 1990) .		chit ances)
	(bant of reconstructed billion trigion 14, 1550)		
Con	nments/Recommendations:		
			, k
~ "	Pressure acuse by aims is	tra	Il of water toopies for
_	The state of the s	10	11 DA WONCH S TO
	Still be functioning but ma	AL I	want to replace
_		~	
_	Clank annul review	01	E WOULD TESTING PROCEDUT
	01.00 2021 2010 1200		
	malades M202 review	<u> </u>	
-		_	
Cor	nments/Recommendations:		
			
	-		

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Megan Ayezbeni Pool/Spa Representative	11/27/24 Date
ICBU Penrecentative	Date
JCPH Representative	Date

By checking this box, I understand and acknowledge that if the Corrective Action Plan is not returned by a special inspection may be conducted and a fee of \$200 will be applied. *IAC 641 Chapter 15.12 (3)c

Pool/Spa Representative Initials 4

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION Enforcement 641 15.6(1351)

Facility Name: Date of Inspection: Inspector:
The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to lowa Code 135I and 641 IAC 15.6.
Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
· ·
Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
benciative 4. (Cite 641 IAC Chapter 15 violation and marrier in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 5: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 6: (Cite 641 IAC Chapter 15 violation and manual	ner in which the facility failed to comply)		
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficienci	es will be corrected)	
<u>Deficiency 7</u> : (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)		
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficienc	ies will be corrected)	
Deficiency 8: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)		
Corrective Action Plan: (this section to be completed by	y the facility to Indicate how the deficienc	ies will be corrected)	
Deficiency 9: (Cite 641 IAC Chapter 15 violation and mani	ner in which the facility failed to comply)		
Corrective Action Plan: (this section to be completed by	y the facility to indicate how the deficienc	ies will be corrected)	
Deficiency 10: (Cite 641 IAC Chapter 15 violation and ma	nner in which the facility failed to comply)		
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficienc	ies will be corrected)	
*** Additional identified deficiencies may be listed on The deficiencies noted during the inspection shall be a original signed copy of this document to:		e Action Plan within days and su	Ibmitting a
	Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240		
Pool Representative:		Date:	

7

Deficiency 11: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 12</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 13: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 14: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 15: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)