

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 Iowa City, IA 52240

Date of Inspection	10/18/	24		tegistration # N Pool Spa Other	SP52 - 0	073	
Facility Name: \ \			Registration # SP52-073				
			ity: Coralvi	Zipcode: 5	2241		
Person Contacted	Manies	Adaic		-Mail:	adair@hil	ton com	
Manager on Duty:	1 101 City	/ CAUCIT	E	E-Mail:			
Name of CPO(s):			E	-Mail:			
CHEMICAL FEED S	YSTEMS AND SECOND	ARY DISINFECTANT					
Disinfection make	and model #:	ECSUS	5				
Type:	<u>_</u>	V S			7	1.1	
☐ 8romine ☐ Tr	richlor Calcium Hyp	ochlorite 🔲 Sadium H	ypochlorite 🔲	Lithium Hypochlorite 🔲 Cl (gas) 🗌 Other:	14	
WATER CHEMISTI	RY						
Type (Pool, Spa, Plunge Pool, etc.)	Free Chlorine Pool 1.0-8.0 Spa 2.0-8.0	Bromine Pool 2.0-18.0 Spa 4.0-18.0	pH Pool 7.2-7.8 Spa 7.2-7.8	Cyanuric Acid Pool 0-40 Spa 0- 40	Controller ORP 700-880 pH 7.2-7.8	Spa Temperature <= 104°	
Pool	2.52		7.6	Alk-156	7.4712		
Sna	1.47		7.3	A(h-74	697	102.2	
1							
Key: S = Satisfactory U = Unsatisfactory N/A = Not Applicable							
ACILITY RECORDS	1			6. 15.4(6	i)h: Certified operator, lif	eguard, first-aid, & CPR	
S U N/A L. 15.9(1) The swimming pool or spa is currently			7. X				
registered. 1. In Indiana Ind				i)f(3) & 15.51(5)e(4): Fac ts, injuries, & illness. Re			
out of range). 3. 15.4(2)e(1)-(6): Swimming pool: ORP and pH at)f(4) & 15.51(5)e(5): Dat			
opening and every 4 hours; free Cl (Br) 2x daily; combined Cl, total alkalinity and cyanuric acid weekly; calcium hardness & bacteria			10. 🎇 🔲 🔲 15.4(6		es when filters were		
testing monthly. 4.			11. 🔁 🗌 🔲 15.4(6	ed, or a filter cartridge was o)f(6) & 15.51(5)e(8): GFC	I receptacles & breaker		
etc.) is on-site.		n, equalizer, feature ou		12. 🔣 🔲 🔲 15.4(6	.x/month and dates of te 5)f(7) & 15.51(5)e(9): MS	DS for chemicals on-site	
. 15.4(4)h(3)1-3 & 15.51(4)f(4)1-3: SVRS product information that demonstrates compliance is on-site. SVRS tested			13. 🔀 🔲 🔲 15.4(6	and date(s) of review rec 5)i(1)-(6) & 15.51(5)g(1)-(6): Operations manual		
monthly and the test date(s) recorded.				ng procedures, backwash			

FACILITY RECORDS CONT.	21. [] 15.5(18)c: Each section of a multi-section pool is
S U N/A	separated from the other sections by a float line (built or
14. 15.4(6): A written emergency plan onsite (drowning,	reconstructed since March 10, 1993).
serious illness or injury, chemical-handling accidents, weather	22. 🔀 🔲 15.4(4)j(1): Depth markers within 3ft from edge of
emergencies, and other serious incidents) reviewed annually by	pool.
staff, and date(s) of review recorded.	23. 🔽 🔲 15.4(4)j(2): Depth markers in 1ft depth intervals and
15. [15.4(6)m: Lifeguard staffing plan, including diagram(s)	not more than 25ft apart in shallow water.
	24. D 15.4(4)j(3): Depth markers not more than 25ft apart
of zones of surveillance responsibility.	around the deep end of swimming pool.
16. 15.51(2)e(3):Spa temperature recorded when water	
quality testing is done (104° or less-closures noted when out of temp	25. 15.4(4))(6): "No Diving" marked in areas where diving
range).	is not permitted (not more than 25ft apart).
17. 🔲 🔀 🔲 15.51(2)e(1)-(8): Spa: ORP and pH at opening and	26. 🔯 🔲 15.4(4)j(7): Letters, numbers & graphics marked on
every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl	decks and slip resistant.
and cyanuric acid daily; total alkalinity weekly and at each fill;	27. 🔀 🔲 15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
calcium,hardness at each fill & bacteria testing monthly	resistant, have durable and cleanable surface, are free of litter,
18. [15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal	obstructions & tripping hazards.
or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28. 🔀 🔲 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	projections or obstructions.
gal 1x every three weeks.	
	29. 15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
POOL/DECK/SURROUNDING AREA	means of enclosure has no openings greater than 4 inches.
S U N/A	30. 15.4(4)(1) & 15.51(4)k(1): Pool enclosed by a fence,
1. 15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-	wall, building enclosure or combination not less than 4ft high.
adjusting weirs and removable baskets.	31. 🔀 🔲 15.4(4)l(2) & 15.51(4)k(2): The distance between the
2.	ground & the top of the lowest horizontal support is at least 45
openings visible in water less than 8ft deep.	inches.
	32. 15.4(4)(3) & 15.51(4)k(3): A gate at least 36 inches
3. 15.4(3)b(1) & 15.51(3)b(1); Pool/spa does not require	wide provided for emergency purposes.
cleaning.	
4.	33. 15.4(4)(4) & 15.51(4)k(3): Gates lockable.
deep portion of pool. Stairs, ladders, recessed steps, or ramps	34. 15.4(4)(5) & 15.51(4)k(4): Gates/doors are self-
provided in the shallow portion if more than 2ft deep.	closing and self-latching (where lifeguards are not provided).
5. 🔼 🗌 15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	35. 🔼 🔲 15.4(4)I(5): Indoor pool enclosed by barrier at least
are securely anchored.	3ft high if there are sleeping rooms, hallways, apartments,
6. 15.4(4)b(3): The vertical rails of a ladder are 3" to 6"	condominiums or permanent recreation areas used by children that
from the pool wall. The bottom end of ladder is within one inch of	open directly into the swimming pool area.
the pool wall and covered with a smooth non-metallic cap.	36. 15.4(4)I(6): Wave pool has a continuous barrier at
	least 42 inches high along the full length of each side of the wave
7. 15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps	pool.
are slip resistant.	27 7 7 45 4(4) (2) 9 45 54(4)-(2) 5 5
8. 🔼 🗌 15.4(4)b(5): Pool over 30ft wide have recessed steps,	37. 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
ladders, ramps, or stairs installed on each side.	pool deck equipped with (GFCI) at the outlet or at the breaker
9. The stairs, or ramps have	serving the outlet.
securely anchored grab rails or handrails.	38. 15.4(4)m(2) & 15.51(4))(4): Artificial lighting provided
10. \(\bigcap \) \(\bigcap \	for indoor or outdoor pools/spas used after sunset (overhead and/or
stripe at least 1 inch wide marked at the leading edge of each tread.	underwater lights) are functional.
11. 12. 13.4(4)e: Elevated lifeguard chairs (where required)	39. 📈 🔲 15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
are provided.	signs posted at two locations (No Diving, No Rough Play, No
March 1 to the same	Running)
	40. 15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
13.	
bandage compress, self-adhering gauze bandage, disposable gloves	accompanied by an adult) sign posted at each swimming pool entry
& chemical cold compress. Signage if required.	where lifeguards are not provided.
14. 15.4(4)f(5):Spine board provided (facilities with	41. X
lifeguards)	provided for flushing the deck(built or reconstructed since March 14,
15. 15.4(4)f(6) & 15.51(4)d: A designated emergency	1990).
telephone with instruction. Signage posted as required.	42. 2 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
16. 15.4(4)g & 15.51(4)e: Pool/spa water levels	preventers provided on all hose bibs on the deck.
maintained at the skimming level.	43. 🔲 🔲 【 15.4(4)c(2): Starting blocks removed, covered, or a
	sign posted to prevent use by the public during general use periods.
17. 15.4(4)h & 15.51(4)f: Fully submerged outlets not	44. The last of province as by the public daring general as a periods.
missing or broken.	
18. [] [15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer	swimming pool/spa (built or reconstructed since March 10, 1993).
openings VGB compliant or the equalizers plugged.	45. 15.5(13)f(3): Where pool depth changes from shallow
19. 🔀 🔲 15.4(4)i(1): The bottom and sides of pool are white or	to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
light color.	depth (built or reconstructed since March 14, 1990).
20. 🔲 🔲 🎁 15.4(4)i(3): The shallow & deep water (5ft) or change	46. 🔣 🔲 🔲 15.4 & 15.51: A swimming pool/spa is operated in a
in slope is marked by a float line with floats spaced no more than 5ft	safe, sanitary manner.

apart.

SP/	$ar{I}$	ME	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S U N/A D 15.4(1)a & 15.51(1)a: Filtration system is in good working condition.
2.	104°F. 15.51(4)I: Agitation system control out of reach of	2.	☐ 15.4(1)b(1) & 15.51(1)c: The recirculation system is
3.	persons and timer is 10 minutes or less. 15.51(5)b: Spa rules sign (8 required stipulations)	3.	operating continuously (except for backwashing or servicing). 15.4(1)b(1) & 15.51(1)c: The circulation system flow
4.	posted. 15.51(5)c: Maximum spa depth posted (letters or	4,	meter(s) are functional. 15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and
5.	numbers 3in high). 15.52(12)a: A spa has at least one stairway, ramp,	5.	after) filter pump 15.4(1)c & 15.51(1)f: Wastewater and backwash is
	ladder or set of recessed steps designating a point of entry (built or reconstructed since March 14, 1990).	6.	discharged through an air break or air gap. 15.4(1)d(1) & 15.5(1)g(1); Water supplied to a
6.	In 15.52(12)a(1)2: Spa stair steps have two hand/grab rails, one on each side of the steps (built or reconstructed since		pool/spa is discharged to the system through an air gap or a reduced principle backflow device.
	March 10, 1993).	7.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	[Section 2015] [Description of the space of	8.	preventer's provided on hose bibs in mechanical room. 15.4(1)e(1) & 15.51(1)h(1): Electric water heaters have UL seal.
WA	ADING Pools	9.	15.4(1)e(2) & 15.51(1)h(2): Gas-fired heaters have
1.	S U N/A 15.4(4)h: Fully submerged outlets not missing or	10.	AGA seal and equipped with a pressure relief valve. 15.4(1)e(3) & 15.5(1)h(3): Fuel-burning water
2.	broken.	11_	heaters are vented to the outside. 15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning
	not removable without the use of tools.	11.	equipment has opening(s) to the outside for providing combustion
3.	☐ ☐ ☒ 15.4(4)I(4): Wading pool within 50 ft of a pool has a barrier at least 36 inches high separating it from the pool or has	12.	
4.	written alternate management plan on-site. [] [] 15.4(4)((5): Gates/doors are self-closing and self-		water/operating water treatment equipment available when pool is open for use.
	latching (where lifeguards are not provided). 15.4(6)d(1): 'No Lifeguard' (Children must be	13.	<u> </u>
5.	accompanied by an adult) sign posted at each wading pool entry		combined chlorine, or total bromine; pH; total alkalinity; calcium
6.	where lifeguards are not provided.	14.	hardness; & cyanuric acid. 15.4(2)f(4)-(5) & 15.51(2)f(4)-(5): ORP/pH controller
	entrance and one location inside enclosure (letters or numbers 3in high).	15.	with numerical analog or digital display 15.4(3)a(1) & 15.5(3)a(1): Continuous disinfection
D.I.		16	feed equipment installed and operational. 15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
	/ING BOARDS S U N/A	10.	feed equipment installed and operational (built or reconstructed
1.	☐ ☐ 15.4(4)c(6): Diving boards/platforms have slipresistant surfaces.	17.	since July 1, 1998).
2.	☐ ☐ <a> 15.4(4)c(8)-(9): Diving board handrails and guard rails present and secure.	18.	☐ 15.4(6)j & 15.51(5)i: A schematic drawing of the recirculation system is posted or clear labeling of piping with flow
3.	15.4(4)c(10): Diving board supports, platforms & steps have no obvious visual structural problems.		direction and water status (unfiltered, treated, backwashed).
		<u>CHI</u>	EMICAL STORAGE
WA	ATER SLIDES S U N/A	1.	S U N/A 1 15.4(4)a(2) & 15.51(4)a(2): Swimming pool/spa
1.	☐ ☐ IX 15.4(4)d(5): Water slide has a lifeguard (or shallow water guard where applicable) at the top and bottom of slide.	2.	chemicals properly stored & handled. 15.4(4)a(4) & 15.51(4)a(4): Chemical storage
2.	☐ ☑ ☎ 15.4(4)o(1): Water slide support structures are free of obvious structural defects.	3.	containers clearly labeled. 15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	15.4(4)o(2): The walkable surface of flume is smooth and continuous.	٠.	warning placed at the entrances to rooms where chemical are used or stored.
4.	☐ 🔲 🐹 15.4(4)o(3): The walkable surface of flume has no	4.	15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single
	sharp edges within reach of a user while in the proper sliding position.	5.	submerged outlet that is not unblockable is equipped with a SVRS. I 15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more
5.	15.4(6)e (1)-(6): Water slide rules are posted near the slide.	6.	than 15 V equipped with a GFCI. 15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	☐ ☐ [X] 15.5(17)b(1): Plunge pool depth is at least 3ft and no more than 4ft.		gallons have secondary containment (built or reconstructed since May 4, 2005).
7.	☐ ☐ ☒ 15.5(17)b(4): Landing area for a water slide is designated by a float line or a painted area.		

CHLOR	INE GAS	8.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S	U N/A		preventers provided on all hose bibs in the bathhouse.
1.	☐ 🄀 15.4(4)n(1)1: Chlorine gas room has an exhaust		
sys	stem.	SPI	RAY PADS
2. 🔲	15.4(4)n(1)2: An air intake provided near the ceiling. 15.4(4)n(1)3: The exhaust fan shall be operated from		S U N/A
3. 🔲	15.4(4)n(1)3: The exhaust fan shall be operated from	1.	15.5(19)a: The surface of a spray pad shall be
	witch labeled "Chlorine Exhaust Fan" in a nearby location outside		impervious and durable. Padding specifically designed for spray pad-
	e chlorine room or building.		may be used with play features.
_		2.	15.5(19)b: The spray pad surface shall slope to drain.
4.	15.4(4)n(1)4: Discharge from exhaust system outside	۷.	
	pool enclosure		Deck or other areas outside the spray pad shall not drain into the
5.	☐ ☒ 15.4(4)n(1)5: Artificial lighting provided in chlorine		spray pad.
roc	om	3.	☐ ☐ 15.5(19)c: Unless the spray pad is supervised by
6.	15.4(4)n(1)7: A plastic bottle of commercial strength		facility staff, a sign shall be posted near the spray pad that
	nmonia solution for leak detection.		addresses: No running on or around the spray pad, No rough play,
7.	15.4(4)n(2)1: Chlorine gas cylinders are individually		No facility supervision. Parents are responsible for supervising their
an	chored with safety chains or straps		children.
		4.	15.5(19)d: Spray pads drains shall be gravity outlets.
BATHH	OUSE		At least two drains or a single drain that is unblockable shall be
S	U N/A		provided.
1. 🔽		5.	15.5(19)e(2): On independent treatment systems the
	e clean & free of debris.		tank shall be accessible for cleaning and inspection.
		_	
2.		6.	15.5(19)e(3): On independent treatment systems the
wit	thout standing water.		recirculation treatment system and play feature pump and piping
3. 📉	15.4(5)c: Carpet not in wet areas of the		system shall be separate.
	thhouse/dressing area.	7.	15.5(19)e(5): On independent treatment systems the
4.			play feature pump system shall be designed so that it will not
-			operate if the recirculation system in not operating.
	nctional.		operate if the recirculation system in not operating.
5. 🞾			
fix	tures.	low	/A SMOKEFREE AIR ACT
6.	15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the		S U
ู่ ขึ้น	blic dressing, lavatory, and shower areas are protected by GFCI	1.	lowa Code §142D: No violations observed (No evidence of
	ceptacles at the outlet or breaker serving the outlet.	Δ.	smoking in prohibited areas, no ashtrays present, signs posted at
7. 📙	15.5(21)e: Hose bib(s) provided within the bathhouse		entrances)
)d)	uilt or reconstructed since March 14, 1990).		
Comm	ents/Recommendations:		
	•		
-			
-			
	· -		
Comm	ents/Recommendations:		
			· · ·

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Pool/Spa Representative

Date 10/18/24

4CPH Representative

Date

By checking this box, I understand and acknowledge that if the Corrective Action Plan is not returned by VY 18/ a special inspection may be conducted and a fee of \$200 will be applied. *IAC 641 Chapter 15.12 (3)c

Pool/Spa Representative Initials

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

	4	

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION

Enforcement 641 15.6(135I)

Facility Name: Date of Inspection: Inspector:
The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within 30 days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to lowa Code 135I and 641 IAC 15.6.
Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.4(2)e(1)-(6): Physical water quality tests taken at least twice a day. Dates recorded for water tests Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) (S, U(Y)h(I)3: Submerged VGB certificate available On site Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15, 4(6) f(4) 1 Dates and quantifies of chemical additions, including chemical feed system recorde Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 4: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.51(2)e(1)-(8): Warter quality tests completed with Clarks, Should include temperature readings Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 5: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
15.51(3)6(2): Spa cleaned and dramed regularly Corrective Action Plan: (Cite this section to be completed by the facility to Indicate how the deficiencies will be corrected)

Deficiency 6: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15.4(1)6(4)1: Pool is missing self-adjusting weirs
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 7: (Cite 641 IAC Chapter 15 violation, and manner in which the facility failed to comply) 15. 4(4) 9 + 15.5(4) 6: Pool and Spa Should be Manhamed at Proper Stamming Level Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 8: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) 15. $U(Y)m(2) + 15.51(U)(Y)$ Lighting in Spa is Out
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 9: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 10: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
*** Additional identified deficiencies may be listed on attached pages. The deficiencies noted during the inspection shall be addressed by completing this Corrective Action Plan within days and submitting a original signed copy of this document to: Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240
Pool Representative: Date:
Ray 2/22/2023 .IP

Deficiency 11: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 12: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 13:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 14: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 15:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)