

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 Iowa City, IA 52240

Date of Inspection: 12/16/24				Registration # ∑b Pool ☐ Spa ☐ Other			
Facility Name: Hught (Rise)			Re	gistration# Pool Spa Other			
Facility Physical Address:			Cit		Zipcode:	40	
Person Contacted:			E-N	E-Mail:			
Manager on Duty: Brithney Hagen				E-Mail: brittney. hagen@hyatt.com			
Name of CPO(s): Matt Parizek				E-Mail: brittney. hagen@hyatt.com E-Mail: matt. paricek@hyatt.com			
CHEMICAL FEED S	SYSTEMS AND SECOND	ARY DISINFECTANT					
Disinfection make	e and model #: \PS	contro	llers				
Туре:							
☐ Bromine ☐ T	richlor 🔲 Calcium Hyp	ochlorite Sodium H	ypochlorite 🔲 Li	thium Hypochlorite CI (gas	s) Other:		
WATER CHEMIST	RY						
Type (Pool, Spa, Plunge Pool, etc.)	Free Chlorine Pool 1.0-8.0 Spa 2.0-8.0	Bromine Pool 2.0-18.0 Spa 4.0-18.0	pH Pool 7.2-7.8 Spa 7.2-7.8	Cyanuric Acid Pool 0-40 Spa 0- 40	Controller ORP 700-880 pH 7.2-7.8	Spa Temperature <= 104°	
Pool		,25	7.5	Alk- 72	825	CH -39	
ey; S = Satis	factory U = Unsat	isfactory N/A =	Not Applicable				
ACILITY RECORDS	<u>s</u>			6. A 15.4(6)h certificates.	: Certified operator,	lifeguard, first-aid, & CPR	
S U N/A . 15.9(1) The swimming pool or spa is currently				7. 🛣 🔲 15.4(6)f(2) & 15.51(5)e(2): Monthly microbiological			
registered. 15.4(2)a(1)-(6) & 15.51(2)a(1)-(6):Water quality readings recorded are in the correct range (or closures noted when				analyses results. 8. D 15.4(6)f(3) & 15.51(5)e(4): Facility maintains reports of complaints, accidents, injuries, & illness. Reports submitted as			
out of range). 15.4(2)e(1)-(6): Swimming pool: ORP and pH at opening and every 4 hours; free CI (Br) 2x daily; combined CI, total				required. 9.		ates & quantities of chemical feed systems.	
alkalinity and cyanuric acid weekly; calcium hardness & bacteria testing monthly.				10. D 15.4(6)f	(5) & 15.51(5)e(6): D	ates when filters were	
testing monthly. 1.			t (VGB)	11. 2 15.4(6)f	(6) & 15.51(5)e(8): G	FCI receptacles & breaker	
etc.) is on-site	l.			12. D 15.4(6)fr	(7) & 15.51(5)e(9): M	ISDS for chemicals on-site	
15.4(4)h(3)1-3 & 15.51(4)f(4)1-3: SVRS product information that demonstrates compliance is on-site. SVRS tested monthly and the test date(s) recorded.				13. 🔼 🗌 🗎 15.4(6)i()-(6): Operations manual	

FAC	CILITY RECORDS CONT.	21.	☐ ☐ 15.5(18)c: Each section of a multi-section pool is
	S U N/A		separated from the other sections by a float line (built or
14.	☑ 15.4(6)I: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	☐ ☐ ☐ 15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	15.4(4)j(3): Depth markers not more than 25ft apart
16.	☐ ☐ 15.51(2)e(3):Spa temperature recorded when water		around the deep end of swimming pool.
	quality testing is done (104° or less-closures noted when out of temp	25.	☐ 15.4(4)j(6): "No Diving" marked in areas where diving
	range).		is not permitted (not more than 25ft apart).
17.		26.	15.4(4)j(7): Letters, numbers & graphics marked on
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl		decks and slip resistant.
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	calcium hardness at each fill & bacteria testing monthly		resistant, have durable and cleanable surface, are free of litter,
18.	☐ ☐ ☐ 15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal		obstructions & tripping hazards.
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28.	☐ 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	gal 1x every three weeks.		projections or obstructions.
	Bet my and a fill are asserted	29.	☐ 15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
DO.	OF ADDRESS ADD		means of enclosure has no openings greater than 4 inches.
PUI	DL/DECK/SURROUNDING AREA S U N/A	30.	☐ ☐ 15.4(4)(1) & 15.51(4)k(1): Pool enclosed by a fence,
1	15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall, building enclosure or combination not less than 4ft high.
1,	adjusting weirs and removable baskets.	31	☐ 15.4(4)I(2) & 15.51(4)k(2): The distance between the
2		02.	ground & the top of the lowest horizontal support is at least 45
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		inches.
2	openings visible in water less than 8ft deep.	32.	☐ ☐ ☐ 15.4(4)I(3) & 15.51(4)k(3): A gate at least 36 inches
3.	☐ 15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	wide provided for emergency purposes.
Α.	cleaning.	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
4.	15.4(4)b(1): Ladders or recessed steps provided in the		15.4(4)I(5) & 15.51(4)k(4): Gates lockable.
	deep portion of pool. Stairs, ladders, recessed steps, or ramps	J.T.	closing and self-latching (where lifeguards are not provided).
	provided in the shallow portion if more than 2ft deep.	25	15.4(4)I(5): Indoor pool enclosed by barrier at least
5.	(A) 15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	33,	3ft high if there are sleeping rooms, hallways, apartments,
_	are securely anchored.		condominiums or permanent recreation areas used by children that
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		open directly into the swimming pool area.
	from the pool wall. The bottom end of ladder is within one inch of	36	15.4(4)I(6): Wave pool has a continuous barrier at
7	the pool wall and covered with a smooth non-metallic cap.	50.	least 42 inches high along the full length of each side of the wave
7.	☐ ☐ 15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps are slip resistant.		pool.
O		37	☐ ☐ 15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
8.	Is 15.4(4)b(5): Pool over 30ft wide have recessed steps, ladders, ramps, or stairs installed on each side.	57.	pool deck equipped with (GFCI) at the outlet or at the breaker
0	15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have		serving the outlet.
9.	securely anchored grab rails or handrails.	38.	☐ 15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10.		00.	for indoor or outdoor pools/spas used after sunset (overhead and/or
10.	stripe at least 1 inch wide marked at the leading edge of each tread.		underwater lights) are functional.
11	Surpe at reast 1 incl wide marked at the leading edge of each fread. 1. 15.4(4)e: Elevated lifeguard chairs (where required)	39.	☐ ☐ 15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
11.	are provided.		signs posted at two locations (No Diving, No Rough Play, No
12	2) 15.4(4)f(1): Required lifesaving equipment provided.		Running)
12. 13.		40.	15.4(6)d(1): 'No Lifeguard' (Children under 12 must be
LJ.		101	accompanied by an adult) sign posted at each swimming pool entry
	bandage compress, self-adhering gauze bandage, disposable gloves		where lifeguards are not provided.
1.4	& chemical cold compress. Signage if required.	41	15.5(4)h & 15.51(4)h(3): At least one hose bib
14.	☐ 15.4(4)f(5):Spine board provided (facilities with lifeguards)	121	provided for flushing the deck(built or reconstructed since March 14,
4 E	☐ ☐ 15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
£J.	telephone with instruction. Signage posted as required.	42.	
16	15.4(4)g & 15.51(4)e: Pool/spa water levels		preventers provided on all hose bibs on the deck.
10,	maintained at the skimming level.	43.	
17	☐ 15.4(4)h & 15.51(4)f: Fully submerged outlets not		sign posted to prevent use by the public during general use periods.
11.	missing or broken.	44.	15.5(4)d & 15.52(4)b: The decks drain away from the
19	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer		swimming pool/spa (built or reconstructed since March 10, 1993).
TO'	openings VGB compliant or the equalizers plugged.	45.	
10	15.4(4)i(1): The bottom and sides of pool are white or		to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
10.	light color.		depth (built or reconstructed since March 14, 1990).
20	15.4(4)i(3): The shallow & deep water (5ft) or change	46.	
20.	in slone is marked by a float line with floats spaced no more than 5ft	-	safe, sanitary manner.

apart.

SPA		ME	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S U N/A
	104°F.		working condition.
2.	☐ ☐ 15.51(4)I: Agitation system control out of reach of	2.	☐ 15.4(1)b(1) & 15.51(1)c: The recirculation system is
_	persons and timer is 10 minutes or less.	2	operating continuously (except for backwashing or servicing).
3.	☐ ☐ ☑ 15.51(5)b: Spa rules sign (8 required stipulations)	3.	15.4(1)b(1) & 15.51(1)c: The circulation system flow
	posted.	4	meter(s) are functional.
4.	15.51(5)c: Maximum spa depth posted (letters or	4.	15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and
*	numbers 3in high). 15.52(12)a: A spa has at least one stairway, ramp,	5.	after) filter pump 15.4(1)c & 15.51(1)f: Wastewater and backwash is
5.		Э,	discharged through an air break or air gap.
	ladder or set of recessed steps designating a point of entry (built or reconstructed since March 14, 1990).	6.	15.4(1)d(1) & 15.51(1)g(1): Water supplied to a
6.	15.52(12)a(1)2: Spa stair steps have two hand/grab	o.	pool/spa is discharged to the system through an air gap or a reduced
o.	rails, one on each side of the steps (built or reconstructed since		principle backflow device.
	March 10, 1993).	7.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
7.	15,52(12)c: An emergency shutoff switch near the spa	,,	preventers provided on hose bibs in mechanical room.
1.	(built or reconstructed since 1999).	8.	☐ ☐ ☑ 15.4(1)e(1) & 15.51(1)h(1): Electric water heaters
	Application (Constructed street 1999).	0,	have UL seal.
18/0	ADING Pools	9.	15.4(1)e(2) & 15.51(1)h(2): Gas-fired heaters have
447	S U N/A		AGA seal and equipped with a pressure relief valve.
1.	15.4(4)h: Fully submerged outlets not missing or	10.	
	broken.		heaters are vented to the outside.
2.	☐ ☐ 15.4(4)h(1)2: Fully submerged outlet covers/grates	11.	☐ 15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning
	not removable without the use of tools.		equipment has opening(s) to the outside for providing combustion
3.	☐ ☐ 15.4(4)I(4): Wading pool within 50 ft of a pool has a		air.
	barrier at least 36 inches high separating it from the pool or has	12.	15.4(2)g: Knowledgeable person in testing
	written alternate management plan on-site.		water/operating water treatment equipment available when pool is
4.	☐ ☐ 15.4(4)I(5): Gates/doors are self-closing and self-		open for use.
	latching (where lifeguards are not provided).	13.	15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming
5.	☐ ☐ 15.4(6)d(1): 'No Lifeguard' (Children must be		pool/spa facility has water testing equipment for free chlorine &
	accompanied by an adult) sign posted at each wading pool entry		combined chlorine, or total bromine; pH; total alkalinity; calcium
	where lifeguards are not provided.		hardness; & cyanuric acid.
6.	☐ ☐ I5.4(4)j(4):Maximum depth of wading pool at each	14.	15.4(2)f(4)-(5) & 15.51(2)f(4)-(5): ORP/pH controller
	entrance and one location inside enclosure (letters or numbers 3in	4.0	with numerical analog or digital display
	high).	15.	☐ 15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection
		15	feed equipment installed and operational.
DIV	ING BOARDS	10'	[15.4(3)a(2) & 15.52(11)h: Continuous pH chemical feed equipment installed and operational (built or reconstructed
1	S U N/A 15.4(4)c(6): Diving boards/platforms have slip-		since July 1, 1998).
1.	resistant surfaces.	17.	
2.	15.4(4)c(8)-(9): Diving board handralls and guard rails	18.	
۷.	present and secure.	.1.0.	recirculation system is posted or clear labeling of piping with flow
3.	15.4(4)c(10): Diving board supports, platforms &		direction and water status (unfiltered, treated, backwashed).
J.	steps have no obvious visual structural problems.		Will control with the states fall into the first state of the state of
	Steps flate fle objects flower of weeter problems.	CH	EMICAL STORAGE
WA	ATER SLIDES		S U N/A
	S U N/A	1.	☐ 15.4(4)a(2) & 15.51(4)a(2): Swimming pool/spa
1.	☐ ☐ 15.4(4)d(5): Water slide has a lifeguard (or shallow		chemicals properly stored & handled.
	water guard where applicable) at the top and bottom of slide.	2.	☐ 15.4(4)a(4) & 15.51(4)a(4): Chemical storage
2.	☐ ☐ X 15.4(4)o(1): Water slide support structures are free of		containers clearly labeled.
	obvious structural defects.	3.	☐ 15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	☐ ☐ 15.4(4)o(2): The walkable surface of flume is smooth		warning placed at the entrances to rooms where chemical are used
	and continuous.		or stored.
4.	☐ ☐ 15.4(4)o(3) : The walkable surface of flume has no	4.	☐ ☐ 15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single
	sharp edges within reach of a user while in the proper sliding		submerged outlet that is not unblockable is equipped with a SVRS.
	position.	5.	15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights more
5.	☐ ☐ ☑ 15.4(6)e (1)-(6): Water slide rules are posted near the	_	than 15 V equipped with a GFCI.
	slide.	6.	15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	☐ ☐ ☑ 15.5(17)b(1): Plunge pool depth is at least 3ft and no		gallons have secondary containment (built or reconstructed since
-	more than 4ft.		May 4, 2005).
7.	15.5(17)b(4): Landing area for a water slide is		
	designated by a float line or a painted area.		

	RINE GAS	8.	☐ ☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S	U N/A		preventers provided on all hose bibs in the bathhouse.
1.	15.4(4)n(1)1: Chlorine gas room has an exhaust		
	stem.	SPI	RAY PADS
2.	15.4(4)n(1)2: An air intake provided near the ceiling.		S U N/A
3.	15.4(4)n(1)3: The exhaust fan shall be operated from	1.	☐ ☐ 15.5(19)a: The surface of a spray pad shall be
a s	switch labeled "Chlorine Exhaust Fan" in a nearby location outside		impervious and durable. Padding specifically designed for spray pads
th	e chlorine room or building.		may be used with play features.
4.	15.4(4)n(1)4: Discharge from exhaust system outside	2.	☐ ☐ 15.5(19)b: The spray pad surface shall slope to drain.
of	pool enclosure		Deck or other areas outside the spray pad shall not drain into the
5.	15.4(4)n(1)5: Artificial lighting provided in chlorine		spray pad.
	om	3.	15.5(19)c: Unless the spray pad is supervised by
6.	15.4(4)n(1)7: A plastic bottle of commercial strength		facility staff, a sign shall be posted near the spray pad that
	nmonia solution for leak detection.		addresses: No running on or around the spray pad, No rough play,
7.	15.4(4)n(2)1: Chlorine gas cylinders are individually		No facility supervision. Parents are responsible for supervising their
	chored with safety chains or straps		children.
an	chored with safety chains of straps	4.	15.5(19)d: Spray pads drains shall be gravity outlets.
	101105	4.	At least two drains or a single drain that is unblockable shall be
BATH			
S	U N/A	_	provided.
1.		5.	☐ ☐ 15.5(19)e(2): On independent treatment systems the
_	e clean & free of debris.		tank shall be accessible for cleaning and inspection.
2.	15.4(5)a-b: Floors slip-resistant and maintained	6.	15.5(19)e(3): On independent treatment systems the
_	thout standing water.		recirculation treatment system and play feature pump and piping
3. X	☐ 15.4(5)c: Carpet not in wet areas of the		system shall be separate.
	thhouse/dressing area.	7.	15.5(19)e(5): On independent treatment systems the
4.	15.4(5)d: Lavatories, showers & sanitary facilities		play feature pump system shall be designed so that it will not
fu	nctional.		operate if the recirculation system in not operating.
5.	15.4(5)e: Soap at each lavatory and indoor shower		
fix	tures.	low	/A SMOKEFREE AIR ACT
6. X	☐ 15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the		S U
-	blic dressing, lavatory, and shower areas are protected by GFCI	1.	[] Iowa Code §142D: No violations observed (No evidence of
	ceptacles at the outlet or breaker serving the outlet.	1.	smoking in prohibited areas, no ashtrays present, signs posted at
7. X	15.5(21)e: Hose bib(s) provided within the bathhouse		entrances)
-	uilt or reconstructed since March 14, 1990) .		entrances
10	ant of reconstructed since water 14, 1550;		
Comm	ents/Recommendations:		Λ
	chist land land		Λ (
1-0	with had very oran	17	red records and
10	sorting items and order	711	to technos dato
D.C	GOO IN Charde Of	VIC	101 Maintenance in his
1		1	
V	ery renowned a subject		
- 0	o deficiencies at tim	(0)	of secondations
10	o arachericas on the	K	of inspection
Comm	ents/Recommendations:		
•			
		_	

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.

1

- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

Mary on	12/16/24
Pool/Spa Representative	Date
JCPH Representative	Date 12/6/24
By checking this box, I understand and acknowledge that if the Corre a special inspection may be conducted and a fee of \$200 will be app	
Pool/Sna Penresentative Initials	

*The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION Enforcement 641 15.6(1351)

Facility Name: Date of Inspection: Inspector:
The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to lowa Code 135I and 641 IAC 15.6.
Deficiency 1 : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 2</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 3: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 4</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 5</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

Deficiency 6: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
Deficiency 7: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	by the facility to indicate how the deficiencies will be corrected)
Deficiency 8 : (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	by the facility to indicate how the deficiencles will be corrected)
Deficiency 9: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	by the facility to indicate how the deficiencies will be corrected)
Deficiency 10: (Cite 641 IAC Chapter 15 violation and ma	nner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	by the facility to indicate how the deficiencies will be corrected)
*** Additional identified deficiencies may be listed on The deficiencies noted during the inspection shall be a original signed copy of this document to:	attached pages. ddressed by completing this Corrective Action Plan within days and submitting ar
	Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240
Pool Representative:	

Deficiency 11: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 12: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 13: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 14:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 15: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

8

Rev. 2/22/2023 JP