

SWIMMING POOL/SPA INSPECTION REPORT

LOCAL INSPECTION AGENCY:

Johnson County Public Health 855 S. Dubuque St; Suite 217 Iowa City, IA 52240

Date of Inspection	7/17/2	4		Pool	ntion # Spa Other	39-52-03	52
Facility Name:	, Liberty A	nuate Ce			Spa 🔲 Other		
Facility Physical A		U	C	ty:	the Liberty	Zipcode:	317
Person Contacted	17% 4	7			bjorkenor	thlibery iow	a org
Manager on Duty:	shly Bion	rle	E-	Mail:		1	J
Name of CPO(s):	12 8	rk	E-	Mail:			
CHEMICAL FEED S	SYSTEMS AND SECOND	ARY DISINFECTANT		٠.,			
Disinfection make		Precision					
Type:						-	-
☐ Bromine ☐ To	richlor 🛮 Calcium Hypo	ochlorite 🔲 Sodium H	ypochlorite 🔲 l	ithium.	Hypochlorite)	
WATER CHEMIST	RY	The second	7.	T	The state of the state of	Hot Take	
Type (Pool, Spa, Plunge Pool, etc.)	Free Chlorine Pool 1.0-8.0 Spa 2.0-8.0	*Bromine- Pool 2.0-18.0 Spa 4.0-18.0	pH Pool 7.2-7.8 Spa 7.2-7.8		Cyanuric Acid Pool 0-40 Spa 0- 40	Controller ORP 700-880 pH 7.2-7.8	Spa Temperature <= 104°
Appl Pool	FOI - 7C 1-	-	7.3			823	84°
100 Pool	Fel- 2.71 Tel- 2.75		7.4		(0		
Key: S = Satisf	actory U = Unsat	sfactory N/A =	Not Applicable	•			
FACILITY RECORDS	<u> </u>			6.	☐ ☐ 15.4(6)h: certificates.	Certified operator, l	ifeguard, first-aid, & CPR
1. W N/A	5.9(1) The swimming po	ool or spa is currently			15.4(6)f(2) & 15.51(5)e(2): M	onthly microbiological
	5.4(2)a(1)-(6) & 15.51(2						cility maintains reports o
out of range).	led are in the correct ra				complaints, accidents, required.	•	
	5.4(2)e(1)-(6): Swimmin ery 4 hours; free Cl (Br)				chemical additions, in		
	yanuric acid weekly; cal				□ 15.4(6)f(5) & 15.51(5)e(6): Da	ates when filters were
testing monthly	/. 5.4(4)h(1)3 & 15.51(4)f	(2)3: Submerged outle	t (VGB)	11.	backwashed, cleaned,		vas changed. FCI receptacles & breaker
certification of	compliance (main drain				are tested at least 1x/r	month and dates of t	est dates recorded.
etc.) is on-site.	5.4(4)h(3)1-3 & 15.51(4	\f(4)1-3: SVRS product		12.	reviewed annually, and		SDS for chemicals on-site corded.
	nt demonstrates compli			13.	☐ ☐ 15.4(6)i(1)-(6) & 15.51(5)g(1)	-(6): Operations manual
ملح المستحدد والملحد والمستحدد	a tast date(s) recorded				on-site (water testing)	aracaduras hackwas	h vacuuming atc \

FAC	ILITY RECORDS CONT.	21.	15.5(18)c: Each section of a multi-section pool is
	S U N/A		separated from the other sections by a float line (built or
14.	15.4(6)I: A written emergency plan onsite (drowning,		reconstructed since March 10, 1993).
	serious illness or injury, chemical-handling accidents, weather	22.	15.4(4)j(1): Depth markers within 3ft from edge of
	emergencies, and other serious incidents) reviewed annually by		pool
	staff, and date(s) of review recorded.	23.	15.4(4)j(2): Depth markers in 1ft depth intervals and
15.	15.4(6)m: Lifeguard staffing plan, including diagram(s)		not more than 25ft apart in shallow water.
	of zones of surveillance responsibility.	24.	15.4(4)j(3): Depth markers not more than 25ft apart
16.			argund the deep end of swimming pool.
10.	quality testing is done (104° or less-closures noted when out of temp	25	15.4(4)j(6): "No Diving" marked in areas where diving
		25.	is not permitted (not more than 25ft apart).
47	range).	26	15.4(4)j(7): Letters, numbers & graphics marked on
17.		20.	
	every 2 hours; free Cl (Br) and temperature 2x daily+; combined Cl		deaks and slip resistant.
	and cyanuric acid daily; total alkalinity weekly and at each fill;	27.	15.4(4)k(1)-(3) & 15.51(4)h(1)-(4): Decks are slip
	calcium hardness at each fill & bacteria testing monthly		resistant, have durable and cleanable surface, are free of litter,
18.	15.51(3)b(2): Spa drained, cleaned & refilled: 500 gal		obstructions & tripping hazards.
	or less 1x week, 500 -2000 gal 1x every two weeks, more than 2000	28.	☐ 15.4(4)k(3) & 15.51(4)i: No underwater or overhead
	gal 1x every three weeks.		projections or obstructions.
	<i>y</i> .	29,	☐ 15.4(4)I(2) & 15.51(4)k(2): Fence, wall, or other
DO(DL/DECK/SURROUNDING AREA		means of enclosure has no openings greater than 4 inches.
FUC	S U N/A	30.	15.4(4)I(1) & 15.51(4)k(1): Pool enclosed by a fence,
1.	15.4(1)b(4)1 & 15.51(1)e(1)-(2): Skimmers have self-		wall building enclosure or combination not less than 4ft high.
1.		31.	15.4(4)I(2) & 15.51(4)k(2): The distance between the
_	adjusting weirs and removable baskets.	511	ground & the top of the lowest horizontal support is at least 45
2.	15.4(2)c & 15.51(2)c: Grate clearly visible. Grate		inches.
	openings visible in water less than 8ft deep.	22	
3.	15.4(3)b(1) & 15.51(3)b(1): Pool/spa does not require	32.	`````
	cleaning		wide provided for emergency purposes.
4.	15.4(4)b(1): Ladders or recessed steps provided in the	33.	15.4(4)I(4) & 15.51(4)k(3): Gates lockable.
	deep portion of pool. Stairs, ladders, recessed steps, or ramps	34.	15.4(4)I(5) & 15.51(4)k(4): Gates/doors are self-
	proyided in the shallow portion if more than 2ft deep.		closing and self-latching (where lifeguards are not provided).
5.	15.4(4)b(2) & 15.51(4)b(5): Ladders and ladder rungs	35.	
	are securely anchored.		3ft high if there are sleeping rooms, hallways, apartments,
6.	15.4(4)b(3): The vertical rails of a ladder are 3" to 6"		condominiums or permanent recreation areas used by children that
- (from the pool wall. The bottom end of ladder is within one inch of		open directly into the swimming pool area.
	the pool wall and covered with a smooth non-metallic cap.	36.	15.4(4)I(6): Wave pool has a continuous barrier at
7.	☐ ☐ 15.4(4)b(4) & 15.51(4)b(2): Steps, rungs, and ramps		least 42 inches high along the full length of each side of the wave
,.	are slip resistant.		pool.
8.	15.4(4)b(5): Pool over 30ft wide have recessed steps,	37.	15.4(4)m (1) & 15.51(4)j(1): Electrical outlets serving
О.	ladders, ramps, or stairs installed on each side.		pool deck equipped with (GFCI) at the outlet or at the breaker
9.	15.4(4)b(6)-(7): Recessed steps, stairs, or ramps have		serying the outlet.
5.	securely anchored grab rails or handrails.	38.	☐ ☐ 15.4(4)m(2) & 15.51(4)j(4): Artificial lighting provided
10			for indoor or outdoor pools/spas used after sunset (overhead and/or
10.	15.4(4)b(8): Stairs have slip resistant color contrasting		underwater lights) are functional.
	stripe at least 1 inch wide marked at the leading edge of each tread.	39.	15.4(6)b(1)-(3) & 15.51(5)b(1)-(8): Legible pool rules
11.	15.4(4)e: Elevated lifeguard chairs (where required)	33.	signs posted at two locations (No Diving, No Rough Play, No
	are provided.		Running)
12.	15.4(4)f(1): Required lifesaving equipment provided.	40	
13.		40.	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `
	bandage compress, self-adhering gauze bandage, disposable gloves		accompanied by an adult) sign posted at each swimming pool entry
	& chemical cold compress. Signage if required.		where lifeguards are not provided.
14.	15.4(4)f(5):Spine board provided (facilities with	41.	15.5(4)h & 15.51(4)h(3): At least one hose bib
	lifeguards)		provided for flushing the deck(built or reconstructed since March 14
15.	15.4(4)f(6) & 15.51(4)d: A designated emergency		1990).
	telephone with instruction. Signage posted as required.	42.	☐ 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
16	☐ ☐ 15.4(4)g & 15.51(4)e: Pool/spa water levels		preventers provided on all hose bibs on the deck.
	maintained at the skimming level.	43.	
17	15.4(4)h & 15.51(4)f: Fully submerged outlets not		sign posted to prevent use by the public during general use periods
Ψ/,	missing or broken.	44.	☐ 15.5(4)d & 15.52(4)b: The decks drain away from the
10			swipfiming pool/spa (built or reconstructed since March 10, 1993).
TQ'	15.4(4)h(4) & 15.51(4)f (5): Skimmer equalizer	45.	☐ 15.5(13)f(3): Where pool depth changes from shallow
4.0	openings VGB compliant or the equalizers plugged.	·	to deep, a 4 inch wide stripe is marked (floor and wall) at 5 feet
19.	15.4(4)i(1): The bottom and sides of pool are white or		depth (built or reconstructed since March 14, 1990).
20	light color.	46.	15.4 & 15.51: A swimming pool/spa is operated in a
20.	15.4(4)i(3): The shallow & deep water (5ft) or change	40.	safe, sanitary manner.
	in slope is marked by a float line with floats spaced no more than 5ft		sare, sameary manner.
	apart.		

2

SP		ME	CHANICAL ROOM
1.	S U N/A 15.51(4)c: Spa water temperature does not exceed	1.	S N/A I 15.4(1)a & 15.51(1)a: Filtration system is in good
2.	104°F. 104°F. 15.51(4)I: Agitation system control out of reach of	2.	working condition. 15.4(1)b(1) & 15.51(1)c: The recirculation system is
3.	persons and timer is 10 minutes or less.	3.	operating continuously (except for backwashing or servicing). 15.4(1)b(1) & 15.51(1)c: The circulation system flow
	posted.		meter(s) are functional.
4.	☐ ☐ ☑ 15.51(5)c: Maximum spa depth posted (letters or numbers 3in high).	4.	15.4(1)b(2) & 15.51(1)b: Pressure gauges (before and after) filter pump
5.	15.52(12)a: A spa has at least one stairway, ramp,	5.	15.4(1)c & 15.51(1)f: Wastewater and backwash is
	ladder or set of recessed steps designating a point of entry (built or	6.	discharged through an air break or air gap. 15.4(1)d(1) & 15.51(1)g(1): Water supplied to a
6.	reconstructed since March 14, 1990). The property of the prop	0,	pool/spa is discharged to the system through an air gap or a reduced
	rails, one on each side of the steps (built or reconstructed since		principle backflow device.
7.	March 10, 1993). The state of	7.	15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow preventers provided on hose bibs in mechanical room.
,.	(built or reconstructed since 1999).	8.	15.4(1)e(1) & 15.51(1)h(1): Electric water heaters
111	ADIMC Passa	9.	have UL seal. 15.4(1)e(2) & 15.51(1)h(2): Gas-fired heaters have
VV A	ADING Pools S U N/A	Э.	AGA seal and equipped with a pressure relief valve.
1.	☐ ☐ 15.4(4)h: Fully submerged outlets not missing or	10.	15.4(1)e(3) & 15.51(1)h(3): Fuel-burning water
2.	broken. 15.4(4)h(1)2: Fully submerged outlet covers/grates	11.	heaters are vented to the outside. 15.4(1)e(4) & 15.51(1)h(4): Rooms with fuel-burning
۷.	not removable without the use of tools.		equipment has opening(s) to the outside for providing combustion
3.	15.4(4)!(4): Wading pool within 50 ft of a pool has a	12	air. 15.4(2)g: Knowledgeable person in testing
	barrier at least 36 inches high separating it from the pool or has written alternate management plan on-site.	12.	☐ 15.4(2)g: Knowledgeable person in testing water/operating water treatment equipment available when pool is
4.	☐ ☑ 15.4(4)I(5): Gates/doors are self-closing and self-		open for use.
5.	latching (where lifeguards are not provided). [] [] 15.4(6)d(1): 'No Lifeguard' (Children must be	13.	Discrete 15.4(2)f(1)-(3) & 15.51(2)f(1)-(3): A swimming pool/spa facility has water testing equipment for free chlorine &
J.	accompanied by an adult) sign posted at each wading pool entry		combined chlorine, or total bromine; pH; total alkalinity; calcium
_	where lifeguards are not provided.	1.4	hardness; & cyanuric acid.
6.	☐ ☑ 15.4(4)j(4):Maximum depth of wading pool at each entrance and one location inside enclosure (letters or numbers 3in	14.	☐ ☐ 15.4(2)f(4)-(5) & 15.51(2)f(4)-(5): ORP/pH controller with numerical analog or digital display
	high).	15.	15.4(3)a(1) & 15.51(3)a(1): Continuous disinfection
אום	/ING BOARDS	16.	feed equipment installed and operational. 15.4(3)a(2) & 15.52(11)h: Continuous pH chemical
יום	S U N/A	101	feed equipment installed and operational (built or reconstructed
1.	15.4(4)c(6): Diving boards/platforms have slipresistant surfaces.	17	since July 1, 1998). 15.4(3)b(2): A vacuum cleaning system is provided.
2.	15.4(4)c(8)-(9): Diving board handrails and guard rails		15.4(6)j & 15.51(5)i: A schematic drawing of the
	present and secure.		recirculation system is posted or clear labeling of piping with flow
3.	☐ 15.4(4)c(10): Diving board supports, platforms & steps have no obvious visual structural problems.		direction and water status (unfiltered, treated, backwashed).
		<u>CHE</u>	EMICAL STORAGE
WA	ATER SLIDES S U N/A	1.	S U N/A
1.	15.4(4)d(5): Water slide has a lifeguard (or shallow		chemicals properly stored & handled.
2.	water guard where applicable) at the top and bottom of slide. 15.4(4)o(1): Water slide support structures are free of	2.	☐ ☐ 15.4(4)a(4) & 15.51(4)a(4): Chemical storage containers clearly labeled.
۷.	obyious structural defects.	3.	15.4(4)a(5) & 15.51(4)a(5): A chemical hazard
3.	15.4(4)o(2): The walkable surface of flume is smooth		warning placed at the entrances to rooms where chemical are used
4.	and continuous. 1. 15.4(4)o(3): The walkable surface of flume has no	4.	or stored. 15.4(4)h(3)& 15.51(4)f(4):A pool/spa with a single
	sharp edges within reach of a user while in the proper sliding		submerged outlet that is not unblockable is equipped with a SVRS.
5.	position. 15.4(6)e (1)-(6): Water slide rules are posted near the	5.	15.4(4)m(2)2 & 15.51(4)j(4)2: Underwater lights' more than 15 V equipped with a GFCI.
J.	slide.	6.	15.5(11)g: Sodium hypochlorite tanks larger than 55
6.	☐ ☐ 15.5(17)b(1): Plunge pool depth is at least 3ft and no more than 4ft .		gallons have secondary containment (built or reconstructed since May 4, 2005).
7.	more than 4ft. 15.5(17)b(4): Landing area for a water slide is		Iviay +, 2003).
	designated by a float line or a painted area.		

CHLORINE GAS	8. 🗹 🗌 15.4(1)d(2) & 15.51(1)g(2): Vacuum breaker backflow
S U N/4 1.	preventers provided on all hose bibs in the bathhouse.
system.	SPRAY PADS
 15.4(4)n(1)2: An air intake provided near the ceiling. 15.4(4)n(1)3: The exhaust fan shall be operated from 	S U N/A 1.
a switch labeled "Chlorine Exhaust Fan" in a nearby location outside the chlorine room or building.	impervious and durable. Padding specifically designed for spray pads may be used with play features.
 ☐ ☐ ✓ 15.4(4)n(1)4: Discharge from exhaust system outside of pool enclogure 	2. Deck or other areas outside the spray pad surface shall slope to drain. Deck or other areas outside the spray pad shall not drain into the
 5.	spray pad. 3.
ammonia solytion for leak detection.	addresses: No running on or around the spray pad, No rough play,
7.	No facility supervision. Parents are responsible for supervising their children.
andiforca with survey diams of straps	4.
BATHHOUSE S / U N/A	At least two drains or a single drain that is unblockable shall be provided.
1. 15.4(5): Showers, dressing rooms & sanitary facilities	5. 15.5(19)e(2): On independent treatment systems the
are clean & free of debris. 2.	tank shall be accessible for cleaning and inspection. 6.
without standing water.	recirculation treatment system and play feature pump and piping
3. V 15.4(5)c: Carpet not in wet areas of the bathhouse/dressing area.	system shall be separate. 7.
4. 15.4(5)d: Lavatories, showers & sanitary facilities	play feature pump system shall be designed so that it will not
functional. 5. 15.4(5)e: Soap at each lavatory and indoor shower	operate if the recirculation system in not operating.
fixtures.	IOWA SMOKEFREE AIR ACT
6. 15.4(4)m(1) & 15.51(4)j(1): Electrical outlets in the public dressing, lavatory, and shower areas are protected by GFCI	S U 1. Lowa Code §142D: No violations observed (No evidence of
receptacles at the outlet or breaker serving the outlet.	smoking in prohibited areas, no ashtrays present, signs posted at
7. 15.5(21)e: Hose bib(s) provided within the bathhouse (built or reconstructed since March 14, 1990).	entrances)
(built of reconstructed since March 14, 1330).	
Comments/Recommendations:	
Pool appeared very well	organized and
dean on This day	0
Comment of the commen	
Comments/Recommendations:	
Comments/ Recommendations.	

FACILITY ACKNOWLEDGEMENT

If any of the conditions identified below occur during operation of the swimming pool or spa, the owner or their representative (i.e. CPO, Lifeguard, Manager, etc) must immediately close the pool/spa and document the closure in the daily logs in accordance to 641 IAC Chapter 15. The pool or spa must remain closed until proper operating conditions are achieved and recorded in the daily logs.

- The swimming pool shall be closed if the free chlorine measurement is less than 0.6 ppm or the total bromine measurement is less than 1.0 ppm.
- The spa shall be closed if the free chlorine measurement is less than 1 ppm or the total bromine measurement is less than 2.0 ppm.
- The spa shall be closed if the temperature is greater than 104°.
- The swimming pool or spa shall be closed if the free chlorine measurement is greater than 8.0 ppm or the total bromine measurement is greater than 18.0 ppm.
- The swimming pool or spa shall be closed if the ORP is less than 650 mV or greater than 880 mV.
- The swimming pool or spa shall be closed if the pH measurement is less than 6.8 or is greater than 8.2.
- The swimming pool or spa shall be closed if the cyanuric acid measurement is greater than 80 ppm.
- The swimming pool or spa (when the spa agitation system is off) shall be closed if the main drain is not clearly visible. (This can be caused by problems such as poor water clarity, surface reflection, and/or inadequate lighting.)
- The swimming pool or spa shall be closed if submerged suction outlets (drain cover, equalizer cover, feature outlets, etc.) are missing or broken.
- The swimming pool or spa shall be closed when chemical additions are made from the deck for at least one-half hour or until the disinfectant residual returns to acceptable levels
- Two consecutive positive test results for coliform bacteria. (After the first positive result, the local inspection agency office should be contacted, and the pool shall be super-chlorinated (the addition of chlorine disinfectant compound to a concentration of at least 10 ppm free chlorine) at the facility's earliest convenience but not to exceed 24 hours. A recheck sample shall be taken once the disinfectant residual returns to acceptable levels. The pool shall be closed if the second sample is positive and may reopen once no coliform bacteria are detected and the above listed requirements are met.

ashly Brone	7/17/24
Pool/Spa Representative	Date
JCPH Representative	7/17/24 Date

By checking this box, I understand and acknowledge that if the Corrective Action Plan is not returned by 8/17/24, a special inspection may be conducted and a fee of \$200 will be applied. *IAC 641 Chapter 15.12 (3)c

5

Rev. 2/22/2023 JP

^{*}The inspectior reviewed the facility in relation to the particular requirements of 641 IAC Chapter 15 identified above. The inspection is limited in scope and time noting observed deficiencies. Deficiencies may have occurred before the inspection, may occur after the inspection, or may not have been directly observable by the inspector at the time of inspection. The inspection in no way waives any of the requirements of 641 IAC Chapter 15 and the facility will be required to correct any deficiencies identified through future inspections. The inspection does not review any other local, state, or federal laws, ordinances, regulations, or requirements that may apply to this facility.

NOTIFICATION OF DEFICIENCIES AND REQUEST FOR CORRECTIVE ACTION Enforcement 641 15.6(1351)

Facility Name: North Ciberty Aquatre Center Date of Inspection: 7/17/24 Inspector: James Laans
The following is a list of the deficiencies that were identified in the inspection report that need a Corrective Action Plan. Please respond within 30 days of receipt of this notice to the identified deficiencies by completing the Corrective Action Plan section(s) below with an explanation of how the deficiencies will be corrected and the timeframe. If a deficiency cannot be completed before you respond, you must set a fixed time for correction. Failure to respond within the required timeframe may result with enforcement action against your facility pursuant to Iowa Code 135I and 641 IAC 15.6.
Deficiency 1: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) Missing ladder cap on west end of deep end.
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 2: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply) Removable steps for The radoor pool must have a step resistant color contrasty stripe at Least 1" wide on The leading adapt of each tep. Corrective Action Plane (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 3</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 4</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 5:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

Corrective Action Plan: (Cite this section to be completed by the facility to indicate how the deficiencies will be corrected)

Rev. 2/22/2023 JP 6

Corrective Action Plan: (this section to be completed by	y the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 7</u> : (Cite 641 IAC Chapter 15 violation and mann	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
Deficiency 8: (Cite 641 IAC Chapter 15 violation and man	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
Deficiency 9: (Cite 641 IAC Chapter 15 violation and mann	ner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed b	y the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 10:</u> (Cite 641 IAC Chapter 15 violation and man	nner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by	y the facility to indicate how the deficiencies will be corrected)
*** Additional identified deficiencies may be listed on	attached pages.
	ddressed by completing this Corrective Action Plan within days and submitting a
	Johnson County Public Health Attn: 855 S. Dubuque St.; Suite 217 Iowa City, IA 52240
Pool Representative:	Date:

<u>Deficiency</u> 6: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)

<u>Deficiency 11</u> : (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 12: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 13: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 14:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
<u>Deficiency 15:</u> (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)
Deficiency 16: (Cite 641 IAC Chapter 15 violation and manner in which the facility failed to comply)
Corrective Action Plan: (this section to be completed by the facility to indicate how the deficiencies will be corrected)

8