

N  
IOWA LOCATION MAP  
NOT TO SCALE

# SHOWER HOUSE F.W. KENT PARK

JOHNSON COUNTY CONSERVATION  
F.W. KENT PARK, 2048 US-6 NW, OXFORD, IA 52322

## SHEET INDEX

SHEET LIST	
NUMBER	NAME
GENERAL	
G000	COVER SHEET
CIVIL	
C001	GENERAL NOTES
CD01	EXIST. CONDITIONS & DEMO. PLAN
C100	OVERALL SITE PLAN
C101	SHOWERHOUSE SITE PLAN
C102	PAVING PLAN
C103	SANITARY PLAN
C104	STORMWATER PLAN & PROFILE
C105	STORMWATER PLAN & PROFILE
C106	STORMWATER UTILITY PLAN
C201	OVERALL GRADING PLAN
C202	SHOWERHOUSE GRADING PLAN
C251	SWPPP PRE-CONSTRUCTION PLAN
C252	SWPPP POST CONSTRUCTION PLAN
C501	CONSTRUCTION DETAILS
C502	CONSTRUCTION DETAILS
LANDSCAPE ARCHITECTURE	
L101	LANDSCAPE PLAN
L501	LANDSCAPE DETAILS
STRUCTURAL	
S000	STRUCTURAL GENERAL INFORMATION
S001	SPECIAL INSPECTIONS
S100	FOUNDATION PLAN - SHOWERHOUSE
S500	DETAILS
S501	DETAILS

SHEET LIST	
NUMBER	NAME
PLUMBING	
P000	PLUMBING GENERAL INFORMATION
P101	PLUMBING PLANS
P400	PLUMBING SECTIONS
P500	PLUMBING DETAILS
P600	PLUMBING SCHEDULES
P700	PLUMBING ISOMETRICS - SV
P710	PLUMBING ISOMETRIC - DOMESTIC
MECHANICAL	
M000	MECHANICAL GENERAL INFORMATION
M101	MECHANICAL PLANS
M500	MECHANICAL DETAILS & SECTIONS
M600	MECHANICAL SCHEDULES
M700	MECHANICAL ISOMETRICS
ELECTRICAL	
E000	ELECTRICAL GENERAL INFORMATION
E010	ELECTRICAL SITE PLAN
E100	ENLARGED LIGHTING, POWER & SYSTEMS PLANS
E500	ELECTRICAL SCHEDULES

JOHNSON COUNTY CONSERVATION BOARD (JCCB)	
AUTHORIZED FOR LETTING	
CHAIR, JOHNSON COUNTY CONSERVATION BOARD	DATE

TOTAL SHEETS 39
PROJECT NUMBER
225000910

## CERTIFICATIONS

### CIVIL ENGINEER

I HEREBY CERTIFY THAT THIS ENGINEERING DOCUMENT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF IOWA.	
01/21/2026	
SIGNATURE _____ DATE _____	
PRINTED OR TYPED NAME <u>Daniel J. Jensen</u>	
LICENSE NUMBER <u>P25063</u>	
MY LICENSE RENEWAL DATE IS DECEMBER 31, 2027	
PAGES, SHEETS OR DIVISIONS COVERED BY THIS SEAL	
<u>ALL C SHEETS</u>	

### LANDSCAPE ARCHITECT

I HEREBY CERTIFY THAT THE PORTION OF THIS TECHNICAL SUBMISSION DESCRIBED BELOW WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL LANDSCAPE ARCHITECT UNDER THE LAWS OF THE STATE OF IOWA.	
Garret Munch	
PRINTED OR TYPED NAME OR SECURE ELECTRONIC SIGNATURE	
01/21/2026	
SIGNATURE _____ DATE _____	
PAGES OR SHEETS COVERED BY THIS SEAL	
<u>ALL L SHEETS</u>	

### STRUCTURAL ENGINEER

I HEREBY CERTIFY THAT THIS ENGINEERING DOCUMENT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF IOWA.	
01/21/2026	
SIGNATURE _____ DATE _____	
PRINTED OR TYPED NAME <u>Joseph W. Page</u>	
LICENSE NUMBER <u>P28577</u>	
MY LICENSE RENEWAL DATE IS DECEMBER 31, 2026	
PAGES, SHEETS OR DIVISIONS COVERED BY THIS SEAL	
<u>ALL S SHEETS</u>	

### MECHANICAL ENGINEER

I HEREBY CERTIFY THAT THIS ENGINEERING DOCUMENT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF IOWA.	
01/21/2026	
SIGNATURE _____ DATE _____	
PRINTED OR TYPED NAME <u>Jessica L Dooley</u>	
LICENSE NUMBER <u>P27051</u>	
MY LICENSE RENEWAL DATE IS DECEMBER 31, 2026	
PAGES, SHEETS OR DIVISIONS COVERED BY THIS SEAL	
<u>ALL P AND M SHEETS</u>	

### ELECTRICAL ENGINEER

I HEREBY CERTIFY THAT THIS ENGINEERING DOCUMENT WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF IOWA.	
01/21/2026	
SIGNATURE _____ DATE _____	
PRINTED OR TYPED NAME <u>Matthew K. Gordon</u>	
LICENSE NUMBER <u>19216</u>	
MY LICENSE RENEWAL DATE IS DECEMBER 31, 2026	
PAGES, SHEETS OR DIVISIONS COVERED BY THIS SEAL	
<u>ALL E SHEETS</u>	

## GENERAL NOTES

1. **UTILITY NOTE:**
  - A. THE LOCATIONS OF UTILITY MAINS, STRUCTURES AND SERVICE CONNECTIONS PLOTTED ON THIS DRAWING ARE APPROXIMATE ONLY AND WERE OBTAINED FROM RECORDS MADE AVAILABLE TO SHIVE-HATTERY, INC. THERE MAY BE OTHER EXISTING UTILITY MAINS, STRUCTURES AND SERVICE CONNECTIONS NOT KNOWN TO SHIVE-HATTERY, INC. AND NOT SHOWN ON THIS DRAWING. THE VERIFICATION OF EXISTENCE OF, AND THE DETERMINATION OF THE EXACT LOCATION OF, UTILITY MAINS, STRUCTURES AND SERVICE CONNECTIONS SHALL BE THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR(S).
  - B. SOME UTILITIES HAVE BEEN DISCONNECTED BY OWNER AND ABANDONED IN PLACE. IF ABANDONED UTILITIES ARE ENCOUNTERED DURING CONSTRUCTION ACTIVITIES, NOTIFY THE OWNER AND ENGINEER PRIOR TO RESUMING CONSTRUCTION.
2. NOTIFY UTILITY COMPANIES WHOSE FACILITIES ARE SHOWN ON THE PLANS OR KNOWN TO BE WITHIN CONSTRUCTION LIMITS OF THE SCHEDULE PRIOR TO EACH STAGE OF CONSTRUCTION.
3. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL UNCOVER EXISTING UTILITIES AT CRITICAL LOCATIONS TO VERIFY EXACT HORIZONTAL AND VERTICAL LOCATION.
4. IOWA CODE 480, UNDERGROUND FACILITIES INFORMATION, REQUIRES VERBAL NOTICE TO IOWA ONE-CALL 1-800-292-8989, NOT LESS THAN 48 HOURS BEFORE EXCAVATING, EXCLUDING WEEKENDS AND HOLIDAYS.
5. NOTIFY THE APPROPRIATE GOVERNING AUTHORITY 48 - 72 HOURS PRIOR TO BEGINNING CONSTRUCTION WITHIN PUBLIC RIGHT-OF-WAY. JOHNSON COUNTY CONSERVATION SHALL BE THE PUBLIC AGENCY RESPONSIBLE FOR INSPECTION DURING CONSTRUCTION OF THE PUBLIC PORTIONS OF THE PROJECT.
6. THE MEANS OF THE WORK AND THE SAFETY OF THE CONTRACTOR'S EMPLOYEES ARE SOLELY THE RESPONSIBILITY OF THE CONTRACTOR.
7. NO WORK SHALL BE PERFORMED BEYOND THE PROJECT LIMITS WITHOUT PRIOR AUTHORIZATION FROM THE OWNER'S REPRESENTATIVE.
8. A PRE-CONSTRUCTION MEETING SHALL BE HELD FOLLOWING ISSUANCE OF THE NOTICE TO PROCEED BUT PRIOR TO COMMENCING WORK.
9. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH IOWA SUDAS, UNLESS OTHERWISE NOTED ON THE DRAWINGS.
10. ALL CONCRETE SHALL BE CONSTRUCTED AT A MINIMUM COMPRESSIVE STRENGTH OF 5,000 PSI.
11. PROVIDE TRAFFIC AND PEDESTRIAN CONTROL MEASURES (SIGNS, BARRICADES, FLAGGERS, ETC.) IN COMPLIANCE WITH PART VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) LATEST EDITION.
12. PROTECT EXISTING UTILITIES DURING CONSTRUCTION.
13. MAINTAIN POSITIVE DRAINAGE ON THE SITE THROUGHOUT THE PROJECT DURATION.
14. ADJUST ALL VALVES, MANHOLES, CASTINGS, GAS VENTS, ETC. TO MATCH THE NEW SURFACE. ADJUSTMENT SHALL BE COORDINATED WITH THE UTILITY COMPANIES AND THE COST FOR ALL ADJUSTMENTS SHALL BE INCIDENTAL TO THE CONSTRUCTION. AT NO ADDITIONAL COST TO THE OWNER, REPAIR ANY DAMAGE TO SAID STRUCTURES AND APPURTENANCES THAT OCCUR DURING CONSTRUCTION.
15. SITE CLEAN-UP SHALL BE PERFORMED ON A DAILY BASIS. SIDEWALKS, PARKING LOTS, ROADWAYS, ETC. SHALL BE KEPT CLEAN AT ALL TIMES.
16. ALL OPEN EXCAVATIONS SHALL BE PROTECTED.
17. REPLACE ANY PROPERTY MONUMENTS REMOVED OR DESTROYED BY CONSTRUCTION. MONUMENTS SHALL BE SET BY A LAND SURVEYOR REGISTERED TO PRACTICE IN THE STATE OF IOWA.
18. CONTROL DUST SPREADING FROM ALL WORK AND STAGING AREAS.
19. ANY WORK REQUIRED TO COMPLETE THE SCOPE OF THIS PROJECT BUT NOT SET FORTH AS A SPECIFIC BID ITEM, SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED FOR THE COMPLETION OF THIS WORK.
20. REPAIR OR REPLACE EXISTING FACILITIES (CURBS, PAVEMENT, UTILITIES, ETC.) TO REMAIN, AT NO ADDITIONAL EXPENSE TO THE OWNER.
21. IT IS INTENDED THAT ALL COSTS OF MATERIALS, EQUIPMENT, TOOLS, LABOR AND INCIDENTALS BE PAID FOR UNDER THE ITEMS LISTED ON THE BIDDER'S PROPOSAL. BEFORE SUBMITTING A BID ON THIS PROJECT, THE CONTRACTOR SHALL EXAMINE ALL DRAWINGS, SPECIFICATIONS, SPECIAL PROVISIONS AND THE JOB SITE. IF ANY DISCREPANCIES OR DELETIONS OCCUR IN THE CONTRACT DOCUMENTS, THE CONTRACTOR SHALL REPORT SAME TO SHIVE-HATTERY, INC. IN WRITING AND OBTAIN WRITTEN CLARIFICATION AND/OR INSTRUCTIONS ON HOW TO PROCEED.
22. WORK WHICH DOES NOT CONFORM TO THE REQUIREMENTS OF THE CONTRACT WILL BE CONSIDERED UNACCEPTABLE. UNACCEPTABLE WORK, WHETHER THE RESULT OF POOR WORKMANSHIP, USE OF DEFECTIVE MATERIALS, DAMAGE THROUGH CARELESSNESS OR ANY OTHER CAUSE, FOUND TO EXIST PRIOR TO THE FINAL ACCEPTANCE OF THE WORK, SHALL BE REMOVED AND REPLACED IN AN ACCEPTABLE MANNER, AS REQUIRED BY SHIVE-HATTERY, INC. AT THE CONTRACTOR'S EXPENSE. WORK DONE CONTRARY TO THE INSTRUCTIONS OF SHIVE-HATTERY, INC., WORK DONE BEYOND THE LINES SHOWN ON THE PLANS OR ANY EXTRA WORK DONE WITHOUT AUTHORITY WILL NOT BE PAID FOR.
23. THE CONTRACTOR SHALL PROTECT ALL TREES SHOWN TO BE SAVED ON THE PLANS. CONTRACTOR SHALL ERECT FENCING AROUND TREE AT THE DRIP LINE, UNDER NO CIRCUMSTANCES SHALL THE CONTRACTOR PARK OR TRAVEL WITH ANY VEHICLE UNDER THE TREE DRIP LINE.

CIVIL QUANTITIES LIST				
#	ITEM DESCRIPTION	QUANTITY	UNITS	SPEC SECTION
1	GRADING, ON SITE CUT TO FILL	267	CY	SUDAS 2010
2	TOPSOIL STRIP AND RESPREAD	359	CY	SUDAS 2010
3	PCC, 5"	582	SY	SUDAS 7010
4	12" SUBGRADE PREP	582	SY	SUDAS 2010
5	6" MODIFIED SUBBASE	582	SY	SUDAS 2010
6	SANITARY PVC, 6"	193	LF	SUDAS 4010
7	SANITARY MANHOLE, SW-301	2	EA	SUDAS 6010
8	STORMSEWER, 8" DUAL WALL	228	LF	SUDAS 4020
9	BIOCELL INTAKE, 24" NYLOPLAST	5	EA	SUDAS 6020
10	WATER MAIN, 4" C900	46	LF	SUDAS 5010
11	2" HDPE GEOTHERMAL HEADER	43	LF	ASTM D3035, SDR 11
12	TRENCH DRAIN	237	LF	SEE DETAILS
13	6" HDPE TRENCH DRAIN OUTLETS	60	LF	SUDAS 4020
14	SEEDING AND RESTORATION	1	LS	SEE LANDSCAPE PLANS AND SPECS
15	CONSTRUCTION SURVEY	1	LS	SUDAS DIVISION 1

LEGEND	
EXISTING GENERAL SITE	
PLAN MARK	DESCRIPTION
	EXISTING STRUCTURE
	BOLLARD
	SHRUB
	DECIDUOUS TREE
	CONIFEROUS TREE
	SINGLE POLE SIGN
	DOUBLE POLE SIGN
	TREE LINE
	MINOR CONTOUR
	MAJOR CONTOUR

LEGEND		
UTILITY LINES		
EXISTING LINE TYPE	DESCRIPTION	PROPOSED LINE TYPE
	ELECTRIC - OVERHEAD	
	ELECTRIC - UNDERGROUND	
	GAS MAIN	
	WATER MAIN	
	SANITARY SEWER	
	STORM SEWER	
	TELEPHONE - UNDERGROUND	
	FIBER OPTICS	
	HIGH VOLTAGE ELECTRICAL	
	LOW VOLTAGE ELECTRICAL	


LEGEND	
UTILITIES	
PLAN MARK	DESCRIPTION
	WATER IRRIGATION VALVE
	UTILITY POLE W/TRANSFORMER
	SIREN POLE
	WATER SHUTOFF VALVE
	GUY ANCHOR
	FIRE HYDRANT
	FLARED END SECTION
	VALVE
	STOP BOX
	CABLE TV PEDESTAL
	CLEANOUT
	JUNCTION BOX


LEGEND	
RIGHT-OF-WAY	
PLAN MARK	DESCRIPTION
	PROPOSED RIGHT-OF-WAY
	EXISTING RIGHT-OF-WAY
	EXISTING PROPERTY LINE
	EXISTING EASEMENT
	TEMPORARY EASEMENT
	PROPOSED EASEMENT


LEGEND	
GENERAL SITE GRADING / EROSION CONTROL	
PLAN MARK	DESCRIPTION
	SLOPE ARROW
	FLOW ARROW
	SILT FENCE
	INLET PROTECTION
	COMPOST SOCK
	GRADING LIMITS


LEGEND	
SURVEY	
PLAN MARK	DESCRIPTION
	BENCH MARK
	BOUND
	IRON ROD - FOUND
	IRON ROD - SET
	MONUMENT FOUND
	MONUMENT SET
	X CUT FOUND
	X CUT SET
	RIGHT OF WAY MARKER
	DRILL HOLE
	STATION MARKER
	SOIL BORING
	PROPERTY CORNER
	SURVEY POINT ELEVATION




LEGEND	
GAS METER	
PLAN MARK	DESCRIPTION
	WATER METER
	CURB INLET
	INTAKE - CIRCLE
	INTAKE - RECTANGLE
	INTAKE - SQUARE
















## 1 SANITARY SEWER 1 PROFILE




VERTICAL SCALE 1" = 5'  
HORIZONTAL SCALE 1" = 10'




## 3 SANITARY SEWER 2 PROFILE

2 VERTICAL SCALE 1" = 5'  
HORIZONTAL SCALE 1" = 10'








1 STORM SEWER 3 PROFILE  
VERTICAL SCALE 1" = 5'  
HORIZONTAL SCALE 1" = 10'





2 STORM SEWER 4 PROFILE  
VERTICAL SCALE 1" = 5'  
HORIZONTAL SCALE 1" = 10'











## SEQUENCING AND PHASING NOTES

1. THIS PROJECT MAY BE CONSTRUCTED OVER SEVERAL PHASES. EROSION/SEDIMENT CONTROL DEVICES IDENTIFIED ON THE PLAN WILL BE IMPLEMENTED ON A PER PHASE BASIS.
2. INSTALL INTAKE PROTECTION AND DOWN SLOPE AND SIDE SLOPE PERIMETER CONTROLS BEFORE LAND DISTURBING ACTIVITY OCCURS.
3. STRIP EXISTING TOPSOIL WITHIN DISTURBANCE LIMITS AND STOCKPILE. DO NOT MIX TOPSOIL WITH SUBSOIL.
4. GRADE SUBSOIL TO CONFORM WITH THE GRADES, CONTOURS AND LEVELS IDENTIFIED ON THE DRAWINGS.
5. ROUGH GRADE FOR ROADWAY, WALKS, CURBS, GUTTERS, AND LANDSCAPED AREAS.
6. COVER OR STABILIZE DISTURBED AREAS AS SOON AS POSSIBLE.
7. SCARIFY AREAS TO RECEIVE TOPSOIL TO A DEPTH OF 4". REMOVE ALL STONES, WOOD AND OTHER DEBRIS LARGER THAN 1" FROM AREAS TO RECEIVE TOPSOIL. DO NOT COMPACT TOPSOIL.
8. ALL DISTURBED AREAS NOT PAVED, OR HARD SURFACED ON THE SITE SHALL RECEIVE A MINIMUM 6" OF TOPSOIL AND SEED AS IDENTIFIED IN THE DRAWINGS. REFER SUDAS SPECIFICATION SECTION 9010 - SEEDING FOR SITE RESTORATION INFORMATION.
9. UPON COMPLETION OF EACH PHASE AND APPROVAL BY THE OWNER'S REPRESENTATIVE, EROSION/SEDIMENT CONTROL DEVICES MAY BE REMOVED/RELOCATED.


## EROSION AND SEDIMENT CONTROL NOTES

1. EROSION/SEDIMENT CONTROL MEASURES SHOULD BE INSTALLED BEFORE EARTH DISTURBING ACTIVITIES BEGIN AND ARE REQUIRED REGARDLESS OF THE TIME OF YEAR. THIS PLAN AND ITS ASSOCIATED REQUIREMENTS FOR THE PERMIT MUST BE IMPLEMENTED DURING WINTER MONTHS AS WELL. ADDITIONAL INSTALLATION/REMOVAL OF STABILIZATION CONTROLS ASSOCIATED WITH SEEDING OUTSIDE THE SEEDING WINDOW ARE INCIDENTAL TO THE PROJECT.
2. REFER TO SUDAS 9040 FOR STORMWATER POLLUTION PREVENTION PLAN, NPDES GENERAL PERMIT NO.2 SUBMITTAL REQUIREMENTS AND EROSION/SEDIMENT CONTROL TECHNICAL SPECIFICATIONS.
3. IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTROL EROSION/SEDIMENT ON THE SITE AT ALL TIMES. THE CONTROL MEASURES SHOWN ON THE PLAN ARE A MINIMUM. THE CONTRACTOR SHALL PROVIDE ADDITIONAL EROSION/SEDIMENT CONTROL MEASURES AS NECESSARY TO FULFILL THIS REQUIREMENT. CONTRACTOR TO INCORPORATE ALL TEMPORARY STABILIZING AND PERMANENT EROSION/SEDIMENT CONTROL FEATURES AT THE EARLIEST TIME PRACTICABLE.
4. THE CONTRACTOR IS REQUIRED TO USE STABILIZATION CONTROLS ON ALL DISTURBED AREAS OF THE SITE REGARDLESS OF THE TIME PERIOD BEFORE THEY WILL BE DISTURBED AGAIN. IN THE EVENT THAT CONSTRUCTION ACTIVITY WITHIN A DISTURBED AREA WILL NOT OCCUR FOR A PERIOD OF 14 OR MORE CALENDAR DAYS, THE CONTRACTOR IS REQUIRED TO INSTALL STABILIZATION MEASURES IMMEDIATELY AFTER CONSTRUCTION ACTIVITY CEASED IN THAT AREA. REFER TO SUDAS 9040 FOR REQUIRED STABILIZATION CONTROLS NOT SHOWN ON THIS PLAN.
5. THE CONTRACTOR SHALL RESTORE DISTURBED AREAS AS SOON AS WORK IS COMPLETED AS INDICATED ON THE PLANS AND PROJECT MANUAL.
6. THE CONTRACTOR SHALL USE CONTROL MEASURES AS REQUIRED TO KEEP SOILS FROM LEAVING THE SITE.
7. CONTRACTOR SHALL IMPLEMENT SITE SPECIFIC BEST MANAGEMENT PRACTICES (BMPS) AS SHOWN AND REQUIRED BY THE SWPPP. ADDITIONAL BEST MANAGEMENT PRACTICES SHALL BE IMPLEMENTED BY THE CONTRACTOR AS DICTATED BY SITE CONDITIONS OR THE PROJECT GOVERNING AUTHORITIES AT NO ADDITIONAL COST TO THE OWNER THROUGHOUT ALL PHASES OF CONSTRUCTION.
8. IF AFTER REPEATED FAILURE ON THE PART OF THE CONTRACTOR TO PROPERLY CONTROL SOIL EROSION, SEDIMENT AND/OR POLLUTION FROM THE PROJECT SITE, THE GOVERNING AUTHORITIES RESERVE THE RIGHT TO EFFECT NECESSARY CORRECTIVE MEASURES AND CHARGE ANY COSTS TO THE CONTRACTOR.
9. ALL BMPS AND CONTROLS SHALL CONFORM TO THE APPLICABLE FEDERAL, STATE, OR LOCAL REQUIREMENTS, STANDARDS, AND SPECIFICATIONS OR MANUAL OF PRACTICE.
10. ALL BMPS AND CONTROLS INSTALLED ON GREEN INFRASTRUCTURE SHALL REMAIN UNTIL THE SITE HAS STABILIZATION AND BEEN APPROVED BUT THE OWNER'S REPRESENTATIVE.
11. IN THE EVENT THAT SOILS LEAVE THE SITE, CLEANUP OF ALL SURROUNDING ROADS, DRIVES, AND PARKING LOTS SHALL BE PERFORMED ON A DAILY BASIS AT A MINIMUM AND UPON REQUEST BY OWNER'S REPRESENTATIVE AT NO ADDITIONAL COST. PAVEMENT IS TO BE SCRAPED OF DEBRIS AND MUD AND BROOMED CLEAN. MUD TRACKS ARE TO BE REMOVED AS THEY ARE CREATED.
12. IF DURING CONSTRUCTION OPERATIONS ANY LOOSE MATERIALS ARE DEPOSITED IN THE FLOW LINE OF GUTTERS, DRAINAGE STRUCTURES, OR DITCHES SUCH THAT THE NATURAL FLOW LINE OF WATER IS OBSTRUCTED, THIS LOOSE MATERIAL SHALL BE REMOVED.
13. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING ANY EXISTING STORM DRAINAGE SYSTEMS BY THE USE OF INLET PROTECTION OR OTHER APPROVED FUNCTIONAL METHODS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING SEDIMENT RESULTING FROM CONSTRUCTION ACTIVITIES ASSOCIATED WITH THIS PROJECT.
14. CONSTRUCTION ACCESS POINTS TO THE SITE SHALL BE PROTECTED IN SUCH A WAY AS TO PREVENT TRACKING OF MUD OR SOIL ONTO PUBLIC THOROUGHFARES. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY BY THE CONTRACTOR.
15. CLEAN SILT FROM FILTER SOCKS/SILT FENCE ON A REGULAR BASIS AS PER THE STANDARD SPECIFICATIONS. FILTER SOCKS MUST BE CLEANED OUT WHEN THEY ARE 33% FULL.
16. CONTRACTOR TO LOCATE/ RELOCATE FILTER SOCKS/SILT FENCE AS NECESSARY THROUGHOUT THE PROJECT TO CONTROL EROSION/SEDIMENT. FILTER SOCK INSTALLATION IS TO FOLLOW SUDAS 9040.102.
17. REMOVE ALL TEMPORARY EROSION/SEDIMENT CONTROLS, NOT CALLED OUT TO REMAIN, AFTER SITE HAS BEEN STABILIZED AND APPROVED BY THE OWNER'S REPRESENTATIVE.
18. WHERE WATER IS PUMPED FROM EXCAVATIONS ON SITE, PROVISIONS SHALL BE MADE TO REMOVE SEDIMENT FROM THE WATER BEFORE IT IS RELEASED. REFER TO SUDAS 3010 SECT 3.04 FOR DEWATERING GUIDANCE.
19. WHERE WATER IS RELEASED FROM A DEWATERING SYSTEM, PRECAUTIONS SHALL BE TAKEN TO ENSURE THAT EROSION GULLIES DO NOT FORM. WATER MUST BE FILTERED THROUGH AN APPROPRIATE FILTER DEVICE BEFORE DISCHARGING.
20. ALL EXISTING AND PROPOSED STORM INTAKES, WITHIN AND ADJACENT TO THE PROJECT AREA, MUST BE PROTECTED THROUGHOUT THE DURATION OF THE PROJECT AS IDENTIFIED ON THE DRAWINGS. INTAKES SHALL BE FREE OF DIRT, DEBRIS AND ROCK AT COMPLETION OF WORK.
21. BIODEGRADABLE EROSION CONTROL BLANKETS SHALL BE USED AT ALL LOCATIONS IDENTIFIED ON THE DRAWINGS. POLYPROPYLENE (PLASTIC) NETTING IS NOT ALLOWED. BIODEGRADABLE STAKES SHALL BE USED IN LIEU OF 'U' STAPLES.
22. SANITARY WASTE DISPOSAL: ALL LOCATIONS OF PORTABLE RESTROOM FACILITIES MUST BE IDENTIFIED ON THE PLAN. IN THE EVENT THAT PORTABLE RESTROOM FACILITIES ARE USED ON-SITE, THE CONTRACTOR IS REQUIRED TO INSTALL AN 8" FILTER SOCK AROUND THE FACILITY TO MINIMIZE THE RADIUS OF THE Affected ZONE IN THE EVENT OF A SPILL. WASTES SHALL BE COLLECTED AND DISPOSED OF IN COMPLETE COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. PORTABLE RESTROOM FACILITIES MUST NOT BE LOCATED NEAR DRAINAGE WAYS. RELOCATE AS REQUIRED FOR CONSTRUCTION.
23. IDENTIFICATION OF ALLOWABLE NON-STORMWATER DISCHARGES: DURING CONSTRUCTION THE NON-STORMWATER DISCHARGES, WHICH INCLUDE WATER FLUSHED FROM WATER LINES, PAVEMENT WASHING (WHERE NO SPILLS OR LEAKS HAVE OCCURRED, UNLESS THE SPILLED MATERIAL HAS BEEN CLEANED UP), VEHICLE WASHING, AND GROUNDWATER (DEWATERING), SHOULD BE DIRECTED AS MUCH AS POSSIBLE TOWARDS VEGETATED AREAS AND AWAY FROM DRAINAGE WAYS. REFER TO THE IDNR NPDES GENERAL PERMIT NO. 2 FOR ALLOWABLE NON-STORMWATER DISCHARGES.
24. POLLUTION AND SPILL PREVENTION PLANNING: POTENTIALLY HAZARDOUS MATERIALS ON THE CONSTRUCTION SITE INCLUDE FUEL, LUBRICANTS, CURING COMPOUNDS, FERTILIZERS, GREASE AND CLEANING SOLVENTS. THE CONTRACTOR STAGING AREA FOR PORTABLE RESTROOM FACILITIES, TEMPORARY FUEL TANKS, WASTE CONTAINERS AND OTHER HAZARDOUS CHEMICALS MUST BE PROTECTED BY AN 8" FILTER SOCK AT ALL TIMES. ALL REASONABLE PRECAUTIONS WILL BE TAKEN TO PREVENT SPILLS. ANY SPILLED MATERIAL WILL IMMEDIATELY BE DIRECTED AWAY FROM STORMWATER INTAKES, DETENTION BASINS, OR DRAINAGE WAYS. SPILLED MATERIALS WILL BE CLEANED AND, IF NECESSARY, SOIL REMEDIATION PRACTICES WILL BE USED. A RECORD OF SPILLS WILL BE MAINTAINED BY THE PRIME CONTRACTOR. RELOCATE AS REQUIRED FOR CONSTRUCTION.
25. CONCRETE, PAINT AND GROUT WASHOUT AREA: THE WASHOUT AREA SHOULD BE AN APPROVED CONCRETE WASHOUT CONTAINER, COLLECTION BAG, OR WASHOUT BOX PER SUDAS 11,050. PROTECT WITH AN EROSION CONTROL DEVICE (IF USING FILTER SOCKS, STACK TWO (2) TALL). CONTRACTOR TO HAUL OFF ALL WASTE MATERIAL. ALL LOCATIONS OF CONCRETE, PAINT AND GROUT WASHOUT AREAS MUST BE PROVIDED BY THE CONTRACTOR AND IDENTIFIED ON THE PLAN (RELOCATE AS REQUIRED FOR CONSTRUCTION). THE CONTRACTOR IS REQUIRED TO INSTALL A SIGN THAT DESIGNATES THE WASHOUT AREA.
26. CONCRETE SLURRY AND DUST FROM SAWCUTTING ACTIVITIES IS PROHIBITED FROM ENTERING THE STORM SEWER SYSTEM. ALL STORM INTAKES LOCATED NEAR SAWCUTTING ACTIVITIES ARE REQUIRED TO BE PROTECTED. SAWCUT SLURRY AND DUST MUST BE CONTAINED, CLEANED UP, AND DISPOSED OF OFF-SITE.
27. SPILL KIT: THE LOCATION OF THE SPILL KIT MUST BE IDENTIFIED ON THE PLAN. THE SPILL KIT SHALL CONTAIN, BUT NOT BE LIMITED TO THE FOLLOWING ITEMS: A GARBAGE CAN, GLOVES, SAFETY GOGGLES, BROOM AND DUST PAN AND OIL ABSORBENT CLAY CHIPS OR PADS. THE SPILL KIT SHALL BE RESTOCKED AS SUPPLIES ARE USED. THE CONTRACTOR SHALL INSTALL A SIGN THAT DESIGNATES THE SPILL KIT. RELOCATE AS REQUIRED FOR CONSTRUCTION. THE SPILL KIT SHOULD BE DESIGNED TO DEAL WITH ANY HAZARDOUS MATERIALS ON-SITE.
28. DUST CONTROL: THE CONTRACTOR SHALL IMPLEMENT DUST CONTROL MEASURES WHERE DUST IS GENERATED. FREQUENT WATERING OF THE SITE, SPRINKLED, VEGETATIVE COVER, MULCH, WINDBREAKS, TILLAGE, STONE AND SPRAY-ON CHEMICAL SOIL TREATMENTS (PALLIATIVES) ARE POSSIBLE DUST CONTROL MEASURES. IF THE DUST CONTROL IS NOT ACCEPTABLE IT SHALL BE CHANGED AS DIRECTED BY THE OWNER'S REPRESENTATIVE.
29. STOCKPILED MATERIALS: CONTRACTOR TO IDENTIFY ALL LOCATIONS OF STOCKPILED MATERIALS ON THE STORMWATER POLLUTION PREVENTION PLAN. CONTRACTOR SHALL PROVIDE ALL EROSION/SEDIMENT CONTROLS AS REQUIRED TO CONTAIN MATERIALS ON-SITE. AT A MINIMUM, THE CONTRACTOR IS REQUIRED TO PROVIDE FILTER SOCKS AROUND STOCKPILED SOILS BEFORE STOCKPILE IS RE-SPREAD. IF STOCKPILE SOILS WILL REMAIN INACTIVE FOR 14 DAYS OR MORE, THEY SHALL BE STABILIZED IMMEDIATELY BY THE CONTRACTOR.







1 CONSTRUCTION FENCE DETAIL  
NOT TO SCALE




2 COMPOST FILTER SOCK DETAIL  
NOT TO SCALE



3 SILT FENCE DETAIL  
NOT TO SCALE




4 STABILIZED CONSTRUCTION  
ENTRANCE/ CONTRACTOR STAGING  
AND LAYDOWN AREA  
NOT TO SCALE




5 BIO-RETENTION CELL AND BIOSWALE OUTLET  
NOT TO SCALE

APPROVED ENGINEERING SOIL MEDIUM NOTES:


1. THE BIORETENTION FACILITY MAY NOT BE CONSTRUCTED UNTIL ALL CONTRIBUTING DRAINAGE AREA HAS BEEN STABILIZED.
2. COMPOST MEDIUM SHALL BE WELL MIXED ON SITE AT 50% COMPOST OF:
  - A. 30% CONSTRUCTION SAND
  - B. 30% ORGANIC COMPOST
  - C. 10% QUALITY TOPSOIL W/ LESS THAN 5% MAX CLAY CONTENT
3. ALL COSTS FOR MATERIALS, DELIVERY TO SITE, AND REQUIRED TEST ANALYSIS TO BE PAID FOR BY THE CONTRACTOR.
4. ENGINEERED COMPOST MEDIUM SHALL BE FINE DUST, STUMPS, ROOTS OR OTHER SIMILAR OBJECTS LARGER THAN TWO INCHES. NO OTHER MATERIALS OR SUBSTANCES SHALL BE MIXED OR DUMPED WITHIN THE BIORETENTION AREA THAT MAY BE HARMFUL TO PLANT GROWTH, OR PROVE A HINDRANCE TO THE PLANTING OR MAINTENANCE OPERATIONS. THE PLANTING SHALL BE FREE OF NOXIOUS WEEDS.
5. FINALLY ENGINEERED COMPOST MEDIUM SHALL MEET THE FOLLOWING CRITERIA:
  - A. pH RANGE : 5.2-7.0
  - B. ORGANIC MATTER 5-10%
  - C. SOLUBLE SALTS NOT TO EXCEED 500 PPM
6. CONTRACTOR SHALL PROVIDE TEST RESULTS FOR MATERIAL FOR APPROVAL.




6 TYPICAL GRAVITY STORM PIPE EMBEDMENT AND INSTALLATION DETAIL  
NOT TO SCALE




7 NYLOPLAST DRAIN BASIN  
NOT TO SCALE



8 PCC SIDEWALK SECTION  
NOT TO SCALE



9 DOUBLE SANITARY SEWER CLEANOUT  
NOT TO SCALE




## 1 TYPICAL GRAVITY SEWER PIPE EMBEDMENT AND INSTALLATION DETAIL

NOT TO SCALE




## 2 CLEANOUT DATA

2 NOT TO SCALE




## VALVE BO

3 N




## TYPICAL WATER PIPE EMBEDMENT AND INSTALLATION DETAIL

NOT TO SCALE




## 5 TRENCH DRAIN - TYPICAL SECTION


3 NOT TO SCALE




(A2) DECIDUOUS TREE PLANTING  
NOT TO SCALE




(D2) TREE STAKING DETAIL  
NOT TO SCALE




(A3) ROOT BALL INSTALLATION  
NOT TO SCALE



(E4) TURF ABUTTING PAVEMENT  
NOT TO SCALE



(A4) TYPICAL SPADE-CUT EDGE DETAIL  
NOT TO SCALE



## GENERAL NOTES

- THE GENERAL STRUCTURAL NOTES ARE INTENDED TO SUPPLEMENT THE DRAWINGS AND SPECIFICATIONS. SHOULD CONFLICTS EXIST BETWEEN THESE DRAWINGS AND THE SPECIFICATIONS NOTIFY THE ENGINEER OF ANY SUCH CONFLICTS.
- STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH ALL PROJECT DRAWINGS AND SPECIFICATIONS. REFER TO ALL DRAWINGS FOR THE COORDINATION OF THE WORK IN THIS PROJECT.
- THE INTENT OF THESE PLANS AND NOTES IS TO PRESENT THE PROJECT REQUIREMENTS. MAJOR DETAILS HAVE BEEN SHOWN ON THE DRAWINGS. HOWEVER, CERTAIN MINOR DETAILS MUST BE WORKED OUT IN THE FIELD OR SHOP DRAWING PROCESS BY THE CONTRACTOR.
- UNLESS NOTED OTHERWISE, DETAILS SHOWN ON DRAWINGS ARE TO BE CONSIDERED TYPICAL FOR ALL SIMILAR CONDITIONS.
- THE STRUCTURE IS DESIGNED TO BE STABLE AND SELF-SUPPORTING AFTER THE BUILDING IS FULLY ERECTED AND ALL CONNECTIONS ARE COMPLETED. UNLESS NOTED OTHERWISE, THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE ERECTION PROCEDURE AND SEQUENCING TO ENSURE THE SAFETY OF THE BUILDING AND ITS COMPONENT PARTS DURING ERECTION. THIS INCLUDES THE ADDITION OF TEMPORARY BRACING, GUYS AND TIE-DOWNS NECESSARY FOR THE ERECTION PROCESS.
- IT IS SOLELY THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW THE APPLICABLE SAFETY CODES AND REGULATIONS DURING ALL PHASES OF CONSTRUCTION.
- CONTRACTOR'S CONSTRUCTION AND ERECTION SEQUENCE SHALL CONSIDER THE EFFECTS OF THERMAL MOVEMENTS OF THE STRUCTURAL ELEMENTS DURING THE CONSTRUCTION PERIOD.
- EXISTING CONDITIONS:
  - THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL DIMENSIONS AND CONDITIONS RELATING TO EXISTING CONSTRUCTION AND EXISTING SERVICES ON SITE. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING COLUMNS, WALLS, OPENINGS, ETC, WITH THE ARCHITECTURAL DRAWINGS PRIOR TO PROCEEDING WITH THE WORK. ANY DISCREPANCIES WITH THE CONTRACT DOCUMENTS SHALL BE REPORTED TO THE ARCHITECT AND ENGINEER BEFORE PROCEEDING WITH THE Affected PART OF THE WORK.
  - DURING CONSTRUCTION THE CONTRACTOR MAY ENCOUNTER EXISTING CONDITIONS WHICH ARE NOT KNOWN OR ARE AT VARIANCE WITH PROJECT DOCUMENTATION (DISCOVERY). SUCH CONDITIONS MAY INTERFERE WITH THE NEW CONSTRUCTION OR REQUIRE PROTECTION AND/OR SUPPORT OF EXISTING WORK DURING CONSTRUCTION. IT MAY ALSO CONSIST OF DAMAGED OR DETERIORATION OF STRUCTURAL MATERIALS OR COMPONENTS WHICH COULD JEOPARDIZE THE STRUCTURAL INTEGRITY OF THE BUILDING(S). THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF ALL DISCOVERIES WHICH MAY INTERFERE WITH THE PROPER EXECUTION OF THE WORK OR JEOPARDIZE THE STRUCTURAL INTEGRITY OF THE BUILDING(S) PRIOR TO PROCEEDING WITH THE WORK RELATED TO SUCH DISCOVERIES.
  - DURING THE CONSTRUCTION PROCESS, IT SHALL BE SOLELY THE CONTRACTOR'S RESPONSIBILITY TO MAINTAIN THE INTEGRITY OF THE EXISTING STRUCTURE AND TO PROTECT IT FROM DAMAGE ANY PORTIONS THAT ARE TO REMAIN.
  - CONTRACTOR SHALL INVESTIGATE THE SITE DURING EARTHWORK OPERATIONS FOR FILL MATERIAL OR BURIED STRUCTURES. IMMEDIATELY, NOTIFY THE ENGINEER IF ANY SUCH MATERIALS OR STRUCTURES ARE DISCOVERED.
- STRUCTURAL COORDINATION
  - MECHANICAL, ELECTRICAL OR PLUMBING LOADS, OPENINGS AND SUPPORT FRAMING ARE SHOWN FOR BIDDING PURPOSES ONLY. CONTRACTOR SHALL OBTAIN APPROVAL OF THE MECHANICAL, ELECTRICAL OR PLUMBING CONTRACTOR BEFORE PROCEEDING WITH SUCH PORTION OF THE WORK.
  - THE CONTRACTOR SHALL VERIFY THE SIZE AND LOCATION OF ALL OPENINGS, HOLES AND SLEEVES THROUGH FOUNDATIONS AND OTHER STRUCTURAL ELEMENTS WITH THE MECHANICAL, ELECTRICAL AND PLUMBING CONTRACTORS. NO OPENINGS SHALL PASS THROUGH STRUCTURAL MEMBERS UNLESS SHOWN ON THE DRAWINGS OR APPROVED BY THE ENGINEER.
  - EXCESS COST DUE TO VARIATION IN THE STRUCTURE TO ACCOMMODATE A SUBSTITUTION OR ALTERNATE MANUFACTURER(S) FROM THE LISTED BASIS OF DESIGN SHALL BE BORNE BY THE CONTRACTOR.
- BEFORE SUBMITTING A BID, EACH BIDDER SHALL VISIT THE SITE AND BECOME FULLY ACQUAINTED WITH THE EXISTING CONDITIONS, CONSTRUCTION REQUIREMENTS, RESTRICTIONS, QUANTITIES AND EQUIPMENT NECESSARY TO COMPLETE THE WORK. THE BID SHALL INCLUDE ALL ITEMS REQUIRED TO COMPLETE THE WORK WITHIN THE EXISTING CONDITIONS. DISRUPTION OF THE OWNERS NORMAL ACTIVITIES AROUND THE CONSTRUCTION SITE SHALL BE KEPT TO A MINIMUM.
- THE COST OF ADDITIONAL DESIGN WORK DUE TO ERRORS AND OMISSIONS BY THE CONTRACTOR DURING CONSTRUCTION SHALL BE BORNE BY THE RESPONSIBLE CONTRACTOR.
- ANY ENGINEERING DESIGN PROVIDED BY OTHER AND SUBMITTED FOR REVIEW OR RECORD SHALL BEAR THE STAMP AND SIGNATURE OF A PROFESSIONAL STRUCTURAL ENGINEER REGISTERED IN THE STATE WHERE THE PROJECT EXISTS.
- CONTRACTOR SHALL COORDINATE WORK SCHEDULES WITH THE OWNER TO ESTABLISH CONSTRUCTION SEQUENCING AROUND ANY OCCUPIED AREAS. CONTRACTOR SHALL NOT PROCEED TO OCCUPIED AREAS UNTIL AUTHORIZED BY THE OWNER.
- ALL ELEMENTS AND SURFACES DAMAGED BY DEMOLITION, BUT NOT SCHEDULED FOR REMOVAL SHALL BE REPAIRED AND REFINISHED TO MATCH THE ADJACENT SURFACES AT NO ADDITIONAL COST TO THE OWNER.
- CONTRACTOR SHALL REMOVE ALL DEBRIS AND WASTE MATERIALS RESULTING FROM CONSTRUCTION FROM THE SITE, UNLESS NOTED OTHERWISE.
- CONTRACTOR SHALL MINIMIZE CREATION OF DUST, DIRT AND WINDBORNE DEBRIS FROM BLOWING ACROSS THE SITE AND ONTO ADJACENT SITES.
- CONTRACTOR SHALL COVER ANY EXTERIOR OPENING WITH TEMPORARY CLOSURES WHEN NOT WORKING ON SITE TO PROTECT THE INTERIOR SPACES FROM WEATHER, INSECTS, RODENTS AND INTRUDERS.

## DESIGN INFORMATION

- CODES:
  - INTERNATIONAL BUILDING CODE (IBC) 2024
  - AMERICAN CONCRETE INSTITUTE - BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE (ACI 318)
  - THE MASONRY SOCIETY - BUILDING CODE REQUIREMENTS AND SPECIFICATIONS FOR MASONRY STRUCTURES (402/602)
  - AMERICAN INSTITUTE OF STEEL CONSTRUCTION - SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS (AISC 360) ALLOWABLE STRENGTH DESIGN (ASD)
  - AMERICAN SOCIETY OF CIVIL ENGINEERS AND STRUCTURAL ENGINEERING INSTITUTE (ASCE/SEI 7) - MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES
  - AMERICAN WELDING SOCIETY D1.1
  - AMERICAN IRON AND STEEL INSTITUTE (AISI S100) SPECIFICATION FOR THE DESIGN OF COLD FORMED STEEL STRUCTURAL MEMBERS
  - AMERICAN FOREST & PAPER ASSOCIATION (AF&PA) NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION (NDS)
- DESIGN LOADS PER THE 2024 IBC (RISK CATEGORY II)
 

A. DEAD LOADS STRUCTURE SELF WEIGHT AS SHOWN CEILING, MEP & FP PRE-MANUFACTURED SHOWER BLDG	5 PSF
B. LIVE LOADS TYPICAL ROOF LIVE LOAD - 20 PSF LIGHT STORAGE (UNREDUCIBLE)	125 PSF
C. ROOF SNOW LOAD GROUND SNOW LOAD, $P_g$ FLAT ROOF SNOW LOAD, $P_f$ MINIMUM ROOF SNOW LOAD, $P_m$ SNOW EXPOSURE FACTOR, $C_e$ SNOW IMPORTANCE FACTOR, $I_s$ THERMAL FACTOR, $C_t$ UNBALANCED SNOW LOAD: REFER TO DIAGRAM	49 PSF 41 PSF 30 PSF 1.0 1.0 1.2
D. WIND PRESSURE (ASCE 7-22) WIND SPEED, $V_{ult}$ NOMINAL DESIGN WIND SPEED, $V_{asd}$ WIND EXPOSURE INTERNAL PRESSURE COEFFICIENT	109 MPH 84 MPH C +/-0.18
E. SEISMIC DESIGN DATA SEISMIC IMPORTANCE FACTOR MAPPED SPECTRAL RESPONSE ACCELERATIONS, $S_s$ MAPPED SPECTRAL RESPONSE ACCELERATIONS, $S_1$ SITE CLASS SPECTRAL RESPONSE COEFFICIENTS, $S_{ds}$ SPECTRAL RESPONSE COEFFICIENTS, $S_{d1}$ SEISMIC DESIGN CATEGORY	1.0 0.11 0.066 D 0.11 0.096 B
- SOILS INFORMATION BASED ON GEOTECHNICAL REPORT PREPARED BY TEAM SERVICES, REPORT NO. 1-3658, DATED JANUARY 27, 2015.
 

NET ALLOWABLE SOIL BEARING PRESSURES: SPREAD FOOTINGS CONTINUOUS WALL FOOTINGS	1500 PSF 1500 PSF
--	----------------------
- MINIMUM FROST PROTECTION DEPTH MEASURED FROM GRADE  
EXTERIOR FOOTING ADJACENT TO HEATED AREA  
EXTERIOR FOOTING AT UNHEATED AREA  
(-3'-6")  
(-3'-6")

## SUBMITTALS

- CONTRACTOR SHALL SUBMIT FOR REVIEW AND APPROVAL THE FOLLOWING SUBMITTALS FOR EACH MATERIAL INDICATED BELOW.
- CONCRETE REINFORCING
  - SUBMIT CONCRETE REINFORCEMENT SHOP DRAWINGS IN ACCORDANCE WITH ACI 315 FOR APPROVAL.
  - DETAIL BARS IN ACCORDANCE WITH "ACI DETAILING MANUAL", PUBLICATION SP-66 AND THE LATEST EDITION OF ACI 318 "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE".
- CONCRETE REINFORCING
  - SUBMIT CONCRETE MIX DESIGNS FOR EACH APPLICATION LOCATION INDICATED IN THE DRAWINGS
  - SUBMIT SHOP DRAWING OF EMBEDDED STEEL ELEMENTS AND CONNECTION
- PRECAST CONCRETE - SHOWER BUILDING
  - REFER TO SPECIFICATION SECTION 13 4345 "PREFABRICATED CONCRETE STRUCTURES" FOR REQUIRED SUBMITTALS

## CAST-IN-PLACE CONCRETE

- ALL CONCRETE SHALL CONFORM TO THE LATEST REQUIREMENTS OF THE AMERICAN CONCRETE INSTITUTES PUBLICATIONS: ACI 301, ACI 305.1, ACI 306.1, ACI 315, AND ACI 318 UNLESS NOTED OTHERWISE.
- CONCRETE COMPRESSIVE STRENGTH (28 DAY) ( $F'_c$ )
 

FOOTINGS	5000 PSI
FOUNDATION WALLS AND PIERS	5000 PSI
SLAB ON GRADE	5000 PSI
- CONCRETE REINFORCEMENT STANDARDS:
 

DEFORMED BARS	ASTM A615	Fy = 60 KSI
WELDED WIRE REINFORCEMENT (WWR)	ASTM A1084	Fy = 65 KSI
WELDABLE REINFORCING BARS	ASTM A706	Fy = 60 KSI
SYNTHETIC MACRO FIBER REINFORCING EPOXY COATED REINFORCING	ASTM C1116	Fy = 60 KSI
	ASTM A775	
- ALL CONCRETE SHALL BE STONE AGGREGATE UNLESS NOTED OTHERWISE. SUBMIT MIX DESIGN AND DOCUMENTATION FOR APPROVAL PER ACI 318.
- REINFORCEMENT PROTECTION
  - CONCRETE PLACED AGAINST EARTH - 3"
  - CONCRETE PLACED IN FORMS BUT EXPOSED TO WEATHER OR EARTH:
    - BARS #5 AND SMALLER - 1 1/2"
    - BARS LARGER THAN #5 - 2"
  - CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND:
    - SLABS, WALLS, AND JOISTS - 3/4"
    - BEAMS, COLUMNS - 1 1/2"
- WHERE REQUIRED, DOWELS SHALL MATCH THE SIZE, NUMBER AND SPACING OF THE MAIN REINFORCING UNLESS NOTED OTHERWISE.
- ALL SPLICES, STANDARD HOOKS, AND DEVELOPMENT LENGTHS TO BE PER THE REFERENCED EDITION OF ACI 318. MAKE BARS CONTINUOUS AROUND CORNERS. ALL SPLICES SHALL BE BY CONTACT LAP.
- ALL SPLICES SHALL BE A CLASS "B" TENSION SPLICE AS DEFINED IN ACI 318. PROVIDE LAP SPLICES LENGTHS AS FOLLOWS:

4000 PSI		
BAR SIZE	TYPICAL	TOP BARS
#3	19"	25"
#4	25"	33"
#5	31"	41"
#6	37"	49"
#7	54"	71"
#8	62"	81"
#9	70"	91"
#10	79"	102"
#11	87"	114"

LAP SPLICE LENGTHS GIVEN, ASSUME CLEAR SPACING BETWEEN BARS OF 2 BAR DIAMETERS, AND A MINIMUM CLEAR COVER OF 1 BAR DIAMETER. TOP BARS ARE DEFINED AS HORIZONTAL BARS WITH MORE THAN 12" ON FRESH CONCRETE BEHIND THE BARS.

- WALLS AND GRADE BEAMS SHALL NOT HAVE JOINTS IN A HORIZONTAL PLANE, UNLESS APPROVED BY THE ENGINEER.
- CONSTRUCTION JOINTS IN STRUCTURAL CONCRETE WORK MUST BE MADE AT CENTER OF SPAN OR AT CENTER OF SUPPORT WITH VERTICAL BULKHEADS AND HORIZONTAL KEYS, UNLESS OTHERWISE SHOWN.
- THERE SHALL BE NO ADDITIONAL OPENINGS LARGER THAN 10" IN CONCRETE WALLS AND SLABS NOT SHOWN. REFER TO CONCRETE OPENING DETAIL FOR ADDITIONAL REINFORCEMENT AROUND OPENINGS.
- REINFORCING STEEL SHALL BE SECURELY FASTENED INTO FORMS PRIOR TO POURING CONCRETE. WET SETTING OF REINFORCING STEEL WILL NOT BE ACCEPTED PER ACI.

- CONCRETE MIX - FOUNDATIONS
 

COARSE AGGREGATE	100% PASSING 1" SIEVE
FINE AGGREGATE	100% PASSING 3/8" SIEVE
WATER/CEMENT RATIO	0.45
SLUMP (NO WATER REDUCER)	4" +/- 1"
SLUMP (WITH WATER REDUCER)	4" TO 8"
AIR CONTENT	6% +/- 1.5%

- GRADE BEAM TOP BARS SHALL BE CONTINUOUS OVER THE SUPPORTS. REINFORCEMENT SHALL BE SPLICED WITH TOP BARS SPliced AT MIDSPAN AND BOTTOM BARS SPliced OVER THE SUPPORT POINTS.
- IF GRADE BEAM IS A SINGLE SIMPLE SPAN THEN TOP BARS SHALL BE CONTINUOUS FULL LENGTH OF BEAM WITH STANDARD HOOKS AT EACH END AND BOTTOM BARS SHALL BE CONTINUOUS BETWEEN SUPPORTS.


- CONTRACTOR SHALL NOTIFY THE ARCHITECT AND ENGINEER IMMEDIATELY IF THE EXISTING FOUNDATIONS VARY FROM THAT SHOWN ON THE DRAWINGS.
- CONTRACTOR SHALL VERIFY OPENINGS AND SLEEVES THROUGH FOUNDATION WALLS WITH THE ARCHITECTURAL, MECHANICAL AND ELECTRICAL REQUIREMENTS. CHANGES IN SIZE, LOCATION AND NUMBER SHALL NOT BE PERMITTED WITHOUT WRITTEN APPROVAL BY THE ENGINEER.
- CONTINUOUS WALL FOOTING REINFORCING SHALL EXTEND THROUGH COLUMN SPREAD FOOTINGS UNLESS NOTED OTHERWISE.

- GRADE BEAM TOP BARS SHALL BE CONTINUOUS OVER THE SUPPORTS. REINFORCEMENT SHALL BE SPLICED WITH TOP BARS SPliced AT MIDSPAN AND BOTTOM BARS SPliced OVER THE SUPPORT POINTS.

- IF GRADE BEAM IS A SINGLE SIMPLE SPAN THEN TOP BARS SHALL BE CONTINUOUS FULL LENGTH OF BEAM WITH STANDARD HOOKS AT EACH END AND BOTTOM BARS SHALL BE CONTINUOUS BETWEEN SUPPORTS.

12 PSF


58 PSF




## 1 UNBALANCE SNOW LOAD - SHOWERHOUSE


BUILDING ELEVATION TABLE		
BUILDING NAME	ACTUAL ELEVATION	REFERENCE ELEVATION
SHOWER HOUSE	840.00'	100'-0"









## 1 TYPICAL WALL CORNER DETAILS




## 2 TYPICAL FOOTING CORNER BAR




## 3 TYPICAL WALL OPENING REINFORCING DETAIL




## 4 STEP FOOTING DETAIL




## 5 TYPICAL FOUNDATION DETAIL AT SITE UTILITIES




**7 TYP INTERIOR FOUNDATION WALL DETAIL**




## 8 CONCRETE STOOP DETAIL



① CONCRETE APPROACH SLAB DETAIL



② TYPICAL WALL CONSTRUCTION JOINT



NOTES:

1. VERIFY SIZE AND LOCATION OF HOUSEKEEPING PADS WITH MECHANICAL AND ELECTRICAL CONTRACTORS.

③ TYPICAL HOUSEKEEPING PAD

## PLUMBING ABBREVIATIONS

SYMBOLS		F		Q	
&	AND	FCO	FLOOR CLEANOUT	QTY	QUANTITY
@	AT	FD	FLOOR DRAIN		
#	NUMBER or POUND	FLA	FULL LOAD AMPS		R
	A	FS	FLOOR SINK		
AC	AIR COMPRESSOR	FSEC	FOOD SERVICE EQUIPMENT CONTRACTOR\	RD	ROOF DRAIN
AD	AREA DRAIN	FT	FOOT/FEET	RECIRC	RECIRCULATE(ING)
ADJ	ADJUSTABLE/ADJACENT	FT HD	FOOT HEAD OR PRESSURE DROP	REQD	REQUIRED
AFF	ABOVE FINISHED FLOOR	FW	FEEDWATER	RHY	ROOF HYDRANT
ALT	ALTERNATE			RPM	REVOLUTIONS PER MINUTE
AMB	AMBIENT	G	GAS	RPZ	REDUCED PRESSURE ZONE
AP	ACCESS PANEL	GA	GAUGE		S
APD	AIR PRESSURE DROP	GAL	GALLON		
APPROX	APPROXIMATE(LY)	GC	GENERAL CONTRACTOR	SCH	SCHEDULE
AR	ACID-RESISTANT OR AIR RECIVER	GCO	GROUND CLEANOUT	SCHM	SCHEMATIC
AS	AIR SEPARATOR	GI	GREASE INTERCEPTOR	SEER	SEASONAL ENERGY EFFICIENCY RATIO
ASSY	ASSEMBLY	GPD	GALLONS PER DAY	SF	SQUARE FEET
ATM	ATMOSPHERE	GPH	GALLONS PER HOUR	SH	SHOWER
AUX	AUXILIARY	GPM	GALLONS PER MINUTE	SK	SINK (SERVICE, LAUNDRY, KITCHEN, SCRUB)
Avg	AVERAGE	GWH	GAS FIRED WATER HEATER	SOI	SAND OIL INTERCEPTOR
	B			SP	SUMP PUMP OR STATIC PRESSURE
BAS	BUILDING AUTOMATION SYSTEM	HB	HOSE BIBB	SPEC	SPECIFICATION(S)
BFF	BELOW FINISHED FLOOR	HD	HUB DRAIN	SQ IN	SQUARE INCH
BFP	BACKFLOW PREVENTER	HG	MERCURY	SRV	SAFETY RELIEF VALVE
BHP	BRAKE HORSEPOWER	HP	HORSEPOWER	STD	STANDARD
BLDG	BUILDING	HR	HOSE REEL	SV	SAFETY VALVE
BMS	BUILDING MANAGEMENT SYSTEM	HVAC	HEATING, VENTILATION, AIR CONDITIONING	SYS	SYSTEM
BOP	BOTTOM OF PIPE	HZ	HERTZ (FREQUENCY)		T
BP	BOOSTER PUMP			TCC	TEMPERATURE CONTROL CONTRACTOR
BT	BATHTUB			TD	TRENCH DRAIN
BTU	BRITISH THERMAL UNIT			TEFC	TOTALLY ENCLOSED FAN COOLED
BTUH	BRITISH THERMAL UNITS PER HOUR	ID	INSIDE DIAMETER	TEMP	TEMPERATURE OR TEMPORARY
	C	IE	INVERT ELEVATION	THRU	THROUGH
CAL	CALIBRATE	IMB	ICE MAKER BOX	TMV	THERMOSTATIC MIXING VALVE
CAP	CAPACITY	IN	INCHES	TOP	TOP OF PIPE
CCR	CONCENTRIC REDUCER	IN WC	INCHES (WATER COLUMN)	TSP	TOTAL STATIC PRESSURE
CCW	COUNTER CLOCKWISE	INS	INSULATION	TYP	TYPICAL
CIRC	CIRCULATING	INSTR	INSTRUMENT		U
CL	CENTER LINE	IP	IRON PIPE	UL	UNDERWRITERS LABORATORIES
CLG	CEILING	IPS	IRON PIPE SIZE	UNO	UNLESS NOTED OTHERWISE
CLR	CLEAR(ANCE)	ISO	ISOMETRIC	UR	URINAL
CLW	CLOCKWISE			UTIL	UTILITY
CO	CLEANOUT	K	KELVIN		V
CONSTR	CONSTRUCTION	KW	KILOWATT	VEL	VELOCITY
CONT	CONTINUATION	KWH	KILOWATT HOUR	VFD	VARIABLE FREQUENCY DRIVE
CONTR	CONTRACTOR			VTR	VENT THRU ROOF
COORD	COORDINATE				W
CP	CIRC PUMP	L		WATTS	WATTAGE
CS	CLINICAL SINK	LAV	LAVATORY	WB	WET BULB OR WALL BOX
CT	COOLING TOWER	LB(S)	POUND(S)	WC	WATER CLOSET
CTRL	CONTROL	LWT	LEAVING WATER TEMPERATURE	WCO	WALL CLEANOUT
CU FT	CUBIC FEET			WHA	WATER HAMMER ARRESTOR
CU IN	CUBIC INCH	M		WHY	WALL HYDRANT
	D	MAINT	MAINTENANCE	WMB	WASHING MACHINE BOX
%DEG	DEGREE	MAX	MAXIMUM	WPD	WATER PRESSURE DROP
°C	DEGREES CELSIUS	MBH	BRITISH THERMAL UNIT (1000/HR)	WT	WEIGHT
°F	DEGREES FAHRENHEIT	MB	MOP BASIN		Z
DB	DRY BULB	MC	MECHANICAL CONTRACTOR	ZVB	ZONE VALVE BOX
DDC	DIRECT DIGITAL CONTROLS	MCC	MOTOR CONTROL CENTER		
DEMO	DEMOLITION	MCA	MINIMUM CIRCUIT AMPS		
DF	DRINKING FOUNTAIN	MECH	MECHANICAL		
DFC	DRINKING FOUNTAIN CHILLER	MFR	MANUFACTURER		
DIA	DIAMETER	MH	MANHOLE		
DIAG	DIAGRAM	MIN	MINIMUM OR MINUTE		
DIP	DUCTILE IRON PIPE	MISC	MISCELLANEOUS		
DN	DOWN	MOCP	MAXIMUM OVERCURRENT PROTECTION		
DR	DRAIN	MOV	MOTOR OPERATED VALVE		
DS	DOWNSPOUT				
DV	DRAIN VALVE	N			
DW	DISHWASHER	NA	NOT APPLICABLE		
DWG	DRAWING	NC	NORMALLY CLOSED		
DWV	DRAIN WASTE & VENT	NG	NATURAL GAS		
	E	NIC	NOT IN CONTRACT		
EA	EACH	NO	NORMALLY OPEN		
EC	ELECTRICAL CONTRACTOR	NOM	NOMINAL		
ECCR	ECCENTRIC REDUCER	NTS	NOT TO SCALE		
EE	EMERGENCY EYEWASH			O	
EER	ENERGY EFFICIENCY RATIO	OD	OUTER DIAMETER OR OVERFLOW ROOF DRAIN		
EES	EMERGENCY EYEWASH SHOWER	OFCI	OWNER FURNISHED CONTRACTOR INSTALLED		
EF	ENERGY FACTOR	OFOI	OWNER FURNISHED OWNER INSTALLED		
ELEV	ELEVATION	OI	OIL INTERCEPTOR		
ELEC	ELECTRICAL	OWN	OWNER		
EQ	EQUAL			P	
EQUIP	EQUIPMENT				
EQUIV	EQUIVALENT				
ES	EMERGENCY SHOWER	PG	PRESSURE GAUGE OR PROPYLENE GLYCOL		
ET	EXPANSION TANK	PH	PHASE		
EWC	ELECTRIC WATER COOLER	PLBG	PLUMBING		
EWH	ELECTRIC WATER HEATER	PRV	PRESSURE RELIEF VALVE OR PRESSURE		
EWT	ENTERING WATER TEMPERATURE		REGULATING VALVE		
EX	EXISTING	PSI	POUNDS PER SQUARE INCH		
		PSIA	POUNDS PER SQUARE INCH ABSOLUTE		
		PSIG	POUNDS PER SQUARE INCH GAUGE		

PLUMBING SYMBOLS LEGEND	
→ ← - 2" CW ▶ - →	PIPE SIZE, SYSTEM TAG, AND FLOW
→ ← - - CW - - - →	DOMESTIC COLD WATER
→ ← - - HW - - - →	DOMESTIC HOT WATER
→ ← - - HWC - - - →	DOMESTIC HOT WATER - CIRCULATING
→ ← SAN →	SANITARY SEWER
→ ← - - - V - - - →	SANITARY VENT
→ ← (M) →	DOMESTIC WATER METER
→ ← (S) →	BALANCING VALVE
→ ← (B) →	BALL VALVE
→ ← (C) →	CHECK VALVE
6" CW UP → - o - - - →	ELBOW UP
6" HW DN → - c - - - →	ELBOW DOWN
→ ← (O) →	PIPE OFFSET UP
→ ← (C) →	PIPE OFFSET DOWN
→ ← (T) →	PIPE TEE TURNED UP
→ ← (S) →	PIPE TEE TURNED DOWN
→ ← (T) ↓ →	PIPE TEE
→ ← (C) →	PIPE CAP
→ ← (U) →	PIPE UNION
→ ← (N) →	PIPE TRANSITION
→ ← (K) →	KEYNOTE
→ ← (D) →	DETAIL NUMBER
→ ← (S) →	SHEET NUMBER ON WHICH THE DETAIL RESIDES

## PLUMBING

1. PIPING SHOWN IS IN SCHEMATIC FORM. NOT ALL RISERS AND DROPS ARE SHOWN. PROVIDE OFFSETS AS REQUIRED TO MEET SPACE REQUIREMENTS AND TO AVOID INTERFERENCE WITH OTHER TRADES. COORDINATE WITH OTHER TRADES PRIOR TO FABRICATION. THE CONTRACTOR SHALL PROVIDE COMPLETE FULLY FUNCTIONAL SYSTEMS.

2. PROVIDE ACCESSIBLE ISOLATION VALVES AT ALL BRANCH CONNECTIONS TO MAINS AND PIPING FIXTURE GROUPS. COORDINATE VALVE LOCATIONS ABOVE ACCESSIBLE CEILINGS OR COORDINATE WITH THE GC TO PROVIDE ACCESS PANELS.

3. REFER TO PLUMBING FIXTURE ROUGH-IN SCHEDULE FOR CONNECTION SIZES AT INDIVIDUAL FIXTURES.

4. PROVIDE WATER HAMMER ARRESTORS FOR EACH NEW PLUMBING FIXTURE OR GROUP OF FIXTURES. SIZE AND LOCATION REQUIREMENTS SHALL BE AS PER PDI STANDARD PDI-WH-201.

5. NEW FLOOR/WALL/CEILING PENETRATIONS REQUIRED FOR PIPING INSTALLATION SHALL BE CLEANLY BORED AT RIGHT ANGLES. AS NEW PIPING IS INSTALLED, NEW PIPING PENETRATIONS SHALL BE NEATLY CAULKED TO FILL VOID. WALL PENETRATIONS SHALL BE FINISHED WITH ESCUTCHEONS.

6. ALL NEW PIPING EXPOSED IN OCCUPIED SPACES SHALL HAVE PVC JACKETS INSTALLED OVER THE PIPING INSULATION. ANY PIPING REQUIRED TO BE EXPOSED SHALL BE INSTALLED VERTICALLY OR HORIZONTALLY IN LEAST VISIBLE LOCATION.

7. ALL EQUIPMENT AND ACCESSORIES SHALL BE INSTALLED TO BE EASILY ACCESSIBLE.

8. ALL WORK SHALL BE COMPLETED IN A SAFE WORKMANLIKE MANNER AND IN ACCORDANCE WITH ALL APPLICABLE STATE, LOCAL AND NATIONAL CODES, REGULATIONS AND ORDINANCES. IF ANY CONFLICTS ARISE BETWEEN THE CONTRACT DOCUMENTS AND THE APPLICABLE CODES, REGULATIONS OR ORDINANCE, THE CONTRACTOR SHALL BE RESPONSIBLE TO HAVE ALL WORK CONFORM TO THE STRICTER OF SAID REQUIREMENTS.

9. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS AS REQUIRED FOR PLUMBING INSTALLATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE BOTH A COMPLETE AND COMPLIANT INSTALLATION AS MAY BE DETERMINED BY THE AUTHORITY(S) HAVING JURISDICTION.

10. CONTRACTOR SHALL NOT PROCURE OR FABRICATE ANY PIPING OR EQUIPMENT WITHOUT FIRST VERIFYING ALL DIMENSIONS AND CONDITIONS WHETHER CURRENTLY EXISTING OR NOT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK, INCLUDING ANY REQUIRED REWORK.


11. MAINTAIN ALL MANUFACTURER RECOMMENDED EQUIPMENT SERVICE AND SAFETY CLEARANCES. DO NOT LOCATE ANY EQUIPMENT OR RUN MATERIALS ABOVE ANY ELECTRICAL PANELS OR SWITCHGEAR. MAINTAIN ALL NFPA/NEC CODE REQUIRED CLEARANCES.

12. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING, SCHEDULING AND SEQUENCING OF THEIR WORK WITH ALL OTHER TRADES. PROVIDE OFFSETS, EASEMENTS, OR RELOCATE TO AVOID CONFLICTS WITH WORK OF OTHER TRADES. FURNISH SUFFICIENT RESOURCES TO MEET ALL PROJECT MILESTONES AND DEADLINES.


13. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE WATERTIGHT AND WEATHER-PROOF INTEGRITY OF ROOFS, WALLS AND FLOORS DURING CONSTRUCTION. EACH TRADE SHALL LOCATE/DIMENSION/COORDINATE THEIR ROOF, FLOOR AND WALL OPENINGS WITH THE GENERAL CONTRACTOR (GC) OR CONSTRUCTION MANAGER.

14. PROTECT NEW WORK FROM DAMAGE OR DECONTAMINATION. PROVIDE TEMPORARY PROTECTIVE CAPPING OR TAPED POLYETHYLENE ENCLOSURES OVER OPEN PIPING ENDS AND EQUIPMENT. CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING PLUMBING SYSTEMS PRIOR TO PLACING THEM IN SERVICE.


15. IN A NEAT AND WORKMANLIKE MANNER: PATCH ANY REMAINING OPENINGS AND FILL EXCESSIVE GAPS; REWORK AND REFINISH TO MATCH ADJACENT STRUCTURES; FLASH AND SEAL ALL MECHANICAL AND ELECTRICAL PENETRATIONS THRU WALLS, CEILINGS AND FLOORS WITH METAL FRAMEWORK OR ESCUTCHEONS. ALL OPENINGS SHALL BE PROPERLY SEALED SO AS TO MEET FIRE RATING.



# 1 UNDER SLAB PLUMBING PLAN




# PLUMBING PLAN




## 1 PLUMBING SECTION - WATER SERVICE ENTERANCE

FIELD VERIFY INVERTS WITH THE GENERAL CONTRACTOR FOR CORES THROUGH THE FOUNDATIONS




## 2 PLUMBING SECTION - WATER HEATER

2 1/2" = 1'-0" 0




## 3 PLUMBING SECTION - CHASE PIPING (TYP 4)

3 1/2" = 1'-0" 0 3




## 4 PLUMBING SECTION - SEPTIC SYSTEM 1 INVERTS

FIELD VERIFY INVERTS WITH THE GENERAL CONTRACTOR FOR CORES THROUGH THE FOUNDATIONS




## PLUMBING SECTION - SEPTIC SYSTEM 2 INVERTS


1/4" = 1'-0" 0




1 BALANCING STATION DETAIL  
NOT TO SCALE




2 CLEANOUT DETAILS  
NOT TO SCALE




3 METAL ROOF PIPE PENETRATION  
NOT TO SCALE




4 IN-LINE CIRCULATING PUMP DETAIL  
NOT TO SCALE




5 INTERIOR WALL PIPE PENETRATION DETAIL  
NOT TO SCALE




6 INSULATED PIPE HANGER DETAIL  
NOT TO SCALE



7 TRAPEZE TYPE HANGER DETAIL  
NOT TO SCALE



8 PIPE PENETRATION IN CAST-IN-PLACE CONCRETE WALL  
NOT TO SCALE




9 WATER HEATER DETAIL  
NOT TO SCALE


PLUMBING FIXTURE SCHEDULE																
REMARKS: 1. WATER HAMMER ARRESTORS NOT SHOWN ON PLANS. REFER TO SPECIFICATIONS AND 2021 UPC. INSTALL ON BOTH COLD AND HOT WATER PIPING IN AN UPRIGHT POSITION. LOCATE AT THE ENDS OF PIPE RUNS OR NEAR A BATTERY OF FIXTURES. FOLLOW MANUFACTURER'S SPECIFICATIONS FOR LOCATION AND INSTALLATION. INSTALL IN AN ACCESSIBLE LOCATION. AIR CHAMBERS NOT ALLOWED. 2. NOT ALL CO, FCO, WCO, ECO ARE SHOWN ON PLANS, REFER TO SPECIFICATIONS AND 2021 UPC. CLEANOUT COVERS SHALL BE STAMPED OR ENGRAVED ON COVER AS "SAN". FIELD COORDINATE EXACT LOCATION OF FLOOR AND WALL CLEANOUTS WITH GENERAL CONTRACTOR.																
TAG	Fixture Type	Fixture				Description	Faucet / Flush Valve				PIPE CONNECTIONS / ROUGH-IN PIPE				Accessories Comments	
		Manufacturer	Model	Material			Manufacturer	Model No.	Finish		STM	San	Vent	CW	HW	
BFP-1	BACKFLOW PREVENTER	WATTS	LF909	CAST IRON	REDUCED PRESSURE ZONE BACKFLOW PREVENTER ASSEMBLY, GATE VALVES, FDA EPOXY COATED WYE STRAINER, AIR GAP ACCESSORY.									3"		
FCO-1	FLOOR CLEANOUT - ROUND	SIOUX CHIEF	854-64NR	CAST IRON	ADJUSTABLE LEVELING FLOOR CLEANOUT, CAST IRON BODY, WITH GAS AND WATERTIGHT ABS TAPERED THREAD PLUG, AND ROUND SCORIATED SECURED NICKEL BRONZE LIGHT-DUTY TOP. INSTALL FLUSH WITH FINISHED FLOOR.									4"		
FD-1	FLOOR DRAIN - ROUND	SIOUX CHIEF	842	CAST IRON	FLOOR DRAIN, 4 1/2" DIAMETER ADJUSTABLE STRAINER HEAD, NICKEL BRONZE STRAINER DEEP CAST IRON P-TRAP. SET TOP OF STRAINER FLUSH WITH FINISHED FLOOR.									2"	2"	
FD-2	FLOOR DRAIN - ROUND	SIOUX CHIEF	842	CAST IRON	SAME AS FD-1 EXCEPT 6 1/2" DIAMETER ADJUSTABLE STRAINER HEAD.									3"	2"	
LAV-1	LAVATORY - WALL HUNG - ADA	KOHLER	K-1722-0	WHITE VITREOUS CHINA	WALL MOUNT LAVATORY, 19 1/4" x 17-1/4", SINGLE CENTER HOLE, WHITE VITREOUS CHINA. MOUNT RIM AT 34" AFF. PROVIDE CHROME PLATED TAILPIECE, GRID DRAIN AND P-TRAP, LOOSE KEY ANGLE STOPS AND SUPPLIES, MOUNT AT ADA COMPLIANT HEIGHT. INSULATE WATER AND WASTE TO MEET ADA REQUIREMENTS USING ADA INSULATION KIT, TRUEBRO OR EQUIVALENT.		MOEN	M8884	CHROME	SINGLE HANDLE FAUCET, 0.5 GPM, SINGLE HOLE INSTALLATION, VANDAL RESISTANT, ADA COMPLIANT.		1 1/2"	1 1/2"	1/2"	1/2"	PROVIDE WITH ZURN CONCEALED ARM CARRIER, MODEL AS REQUIRED. PROVIDE WITH LEONARD MODEL 270 THERMAL MIXING VALVE SET TO DELIVER A MIXED HOT WATER TEMPERATURE OF 110°F.
MB-1	MOP BASIN	PROFLO	PFMB24X24	MOLDED COMPOSITE	24" x 24" x 10" CORNER INSTALLATION, VINYL BUMPER GUARDS, STAINLESS STEEL WALL GUARDS ON TWO SIDES, DRAIN BODY SHALL BE FACTORY INSTALLED, STAINLESS STEEL FLAT STRAINER, LEAD CAULKED JOINT FOR 3" WASTE CONNECTION, DEEP SEAL CAST IRON P-TRAP.		CHICAGO FAUCET CO	835-369CP	CHROME	WALL MOUNTED, 6" CENTERS, TOP MOUNTED SUPPLIES, INTEGRAL STOPS AND VACUUM BREAKER SPOUT WITH PAI HOOK AND WALL BRACE. VANDAL-PROOF, LEVER HANDLES.		3"	2"	3/4"	3/4"	PROVIDE STAINLESS STEEL MOP HANGER AND 3 RUBBER TOOL GRIPS, 30" LONG RUBBER HOSE WITH HOSE BRACKET AND RUBBER GRIP.
SH-1	SHOWER - FAUCET	-	-	-	-		ACORN	1741ADA	STAINLESS STEEL	42" X 11" SINGLE-PANEL WALL MOUNT, T/P TEMPERATURE/PRESSURE BALANCING MIXING VALVE, RECESSED SOAP DISH, UPPER SHOWER HEAD WITH LOWER HANDHELD SHOWER WITH 60" HOSE FOR ADA USE, VACUUM BREAKER, QUICK DISCONNECT, MOUNTING BRACKET, WALL SLEEVE. MOUNT AT ADA COMPLIANT HEIGHT.				1/2"	1/2"	
WC-1	WATER CLOSET - WALL HUNG - ADA	KOHLER	K-84454-0	WHITE VITREOUS CHINA	16 1/2" ELONGATED BOWL, WATERSENSE CERTIFIED 1.28 GPF, WHITE VITREOUS CHINA, 1 1/2" REAR SPUD, MOUNT RIM AT 17" AFF FOR ADA HEIGHT REQUIREMENTS.		SLOAN	S3914856	CHROME	CONCEALED MANUAL FLUSH VALVE, PUSH-BUTTON FLUSH ACTUATOR, 1.28 GPF, 1" I.P.S. WHEEL, HANDLE ANGLE STOP, 14 1/2" ROUGH-IN ABOVE FIXTURE BACK-CHECK ANGLE STOP, VACUUM BREAKER, WALL AND SPUD FLANGE, ADA COMPLIANT.		4"	2"	1"		PROVIDE WITH ZURN ADJUSTABLE HORIZONTAL CARRIER, ZZ1203-NL4(R4) MODEL AS REQUIRED. PROVIDE WITH REMIS SEAT, ELONGATED, ANTI-MICROBIAL SOLID PLASTIC, OPEN FRONT, WHITE HEAVY DUTY SELF-SUSTAINING CHECK HINGE WITH BUMPERS, NO COVER.
WHY-1	EXTERIOR WALL HYDRANT	WOODFORD	B67	STAINLESS STEEL	FREEZELESS, AUTOMATIC DRAINING, ASSE 1052 NIDEL 50HA HIGH FLOW DOUBLE CHECK BACKFLOW PREVENTER, WALL CLAMP AND LOCKABLE DOOR W/LOOSE TEE KEY. EXACT HEIGHT, LOCATION AND FINISH TO BE COORDINATED WITH BUILDING MATERIALS, ARCHITECTURAL FINISHES AND G.C.									3/4"		

WATER HEATER SCHEDULE - ELECTRIC																			
REMARKS: 1. INSTALL ON 4" CONCRETE HOUSE KEEPING PAD																			
WATER (°F)																			
MARK	STORAGE (GAL)		RECOVERY (GPH)		IN		OUT		ELEMENT KW		# OF ELEMENTS		ELECTRICAL DATA						
EWH-1	120		99		40		140		4		3		12		240		1 INTERNAL	EC/EC	AO SMITH DRE-120-12
EWH-2	120		99		40		140		4		3		12		240		1 INTERNAL	EC/EC	AO SMITH DRE-120-12


PLUMBING PUMP SCHEDULE																				
REMARKS: 1. PROVIDE WITH AQUASTAT AND TIMER. 115V, MAX 16A, COORDINATE WITH EC. 2. INSTALL PUMP PER MANUFACTURER'S INSTRUCTIONS. 3. STARTER, DISCONNECT AND TIMER INTERLOCK WIRING BY EC.																				
ELECTRICAL DATA																				
MARK	TYPE		GPM		HEAD (FT)		WATTS		FLA		RPM		VOLTS		PHASE		CONTROL OR STARTER	CONTROLLER OR STARTER FURNISHED / INSTALLED	DISCONNECT FURNISHED / INSTALLED	DESIGN BASIS
CP-1	IN-LINE		4.5		10		92		0.8		2940		115		1		AQUASTAT	MC/EC	EC/EC	BELL&GOSSET NBF-22

PLUMBING EXPANSION TANK SCHEDULE				
MARK	TYPE	TANK CAPACITY (GAL)	ACCEPTANCE CAPACITY (GAL)	DESIGN BASIS
ET-1	DIAPHRAGM	16.6	11.3	AMTROL ST-30VC-DD







2 PLUMBING ISOMETRIC - WATER UTILITY BAY  
NOT TO SCALE



NORTH

1 PLUMBING ISOMETRIC - DOMESTIC  
NOT TO SCALE






#### MECHANICAL DUCTWORK

1. UNLESS NOTED OTHERWISE: LIGHT LINES INDICATE EXISTING DUCTWORK OR EQUIPMENT WHICH IS TO REMAIN. BOLD LINES INDICATE DUCTWORK AND EQUIPMENT TO BE INSTALLED UNDER THIS CONTRACT.
2. DUCTWORK SHOWN IS IN SCHEMATIC FORM. NOT ALL RISERS AND DROPS ARE SHOWN. PROVIDE OFFSETS AS REQUIRED TO MEET SPACE REQUIREMENTS AND TO AVOID INTERFERENCE WITH OTHER TRADES. COORDINATE WITH OTHER TRADES PRIOR TO FABRICATION. THE CONTRACTOR SHALL PROVIDE COMPLETE FULLY FUNCTIONAL SYSTEMS.
3. INSTALL MANUAL VOLUME DAMPERS IN ALL SUPPLY, RETURN AND EXHAUST DUCT SYSTEMS AS REQUIRED FOR CONTROLLING AIR VOLUMES TO TRUNK DUCTS, BRANCH DUCTS, OUTLETS, AND INLETS. CONTRACTOR SHALL INSTALL A COMPLETE SYSTEM OF DAMPERS AS REQUIRED FOR BALANCING AIR SYSTEMS.
4. ALL FLOOR MOUNTED MECHANICAL EQUIPMENT SHALL BE MOUNTED ON MINIMUM 4" CONCRETE HOUSEKEEPING PAD(S).
5. ALL EQUIPMENT AND DUCTWORK SUSPENDED BELOW THE ROOF SHALL BE SUSPENDED FROM THE STRUCTURE AND NOT THE ROOF DECK.
6. ALL EQUIPMENT AND ACCESSORIES SHALL BE INSTALLED TO BE EASILY ACCESSIBLE.
7. ALL WORK SHALL BE COMPLETED IN A SAFE WORKMANLIKE MANNER AND IN ACCORDANCE WITH ALL APPLICABLE STATE, LOCAL AND NATIONAL CODES, REGULATIONS AND ORDINANCES. IF ANY CONFLICTS ARISE BETWEEN THE CONTRACT DOCUMENTS AND THE APPLICABLE CODES, REGULATIONS OR ORDINANCE, THE CONTRACTOR SHALL BE RESPONSIBLE TO HAVE ALL WORK CONFORM TO THE STRICKER OF SAID REQUIREMENTS.
8. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS AS REQUIRED FOR MECHANICAL INSTALLATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE BOTH A COMPLETE AND COMPLIANT INSTALLATION AS MAY BE DETERMINED BY THE AUTHORITY(S) HAVING JURISDICTION.
9. CONTRACTOR SHALL NOT PROCURE OR FABRICATE ANY DUCTWORK OR EQUIPMENT WITHOUT FIRST VERIFYING ALL DIMENSIONS AND CONDITIONS WHETHER CURRENTLY EXISTING OR NOT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK, INCLUDING ANY REQUIRED REWORK.
10. MAINTAIN ALL MANUFACTURER RECOMMENDED EQUIPMENT SERVICE AND SAFETY CLEARANCES. DO NOT LOCATE ANY EQUIPMENT OR RUN MATERIALS ABOVE ANY ELECTRICAL PANELS OR SWITCHGEAR. MAINTAIN ALL NFPA/NEC CODE REQUIRED CLEARANCES.
11. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING, SCHEDULING AND SEQUENCING OF THEIR WORK WITH ALL OTHER TRADES. PROVIDE OFFSETS, EASEMENTS, OR RELOCATE TO AVOID CONFLICTS WITH WORK OF OTHER TRADES. FURNISH SUFFICIENT RESOURCES TO MEET ALL PROJECT MILESTONES AND DEADLINES.
12. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE WATERTIGHT AND WEATHER-PROOF INTEGRITY OF ROOFS, WALLS AND FLOORS DURING CONSTRUCTION. EACH TRADE SHALL LOCATE/DIMENSION/COORDINATE THEIR ROOF, FLOOR AND WALL OPENINGS WITH THE GENERAL CONTRACTOR (GC) OR CONSTRUCTION MANAGER.
13. PROTECT NEW WORK FROM DAMAGE OR DECONTAMINATION. PROVIDE TEMPORARY PROTECTIVE CAPPING OR TAPED POLYETHYLENE ENCLOSURES OVER OPEN DUCTWORK ENDS AND EQUIPMENT. CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING DUCTWORK SYSTEMS PRIOR TO PLACING THEM IN SERVICE.
14. IN A NEAT AND WORKMANLIKE MANNER: PATCH ANY REMAINING OPENINGS AND FILL EXCESSIVE GAPS; REWORK AND REFISH TO MATCH ADJACENT STRUCTURES; FLASH AND SEAL ALL MECHANICAL AND ELECTRICAL PENETRATIONS THRU WALLS, CEILINGS AND FLOORS WITH METAL FRAMEWORK OR ESCUTCHEONS. ALL OPENINGS SHALL BE PROPERLY SEALED SO AS TO MEET FIRE RATING.
15. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE WATERTIGHT AND WEATHER-PROOF INTEGRITY OF ROOFS, WALLS AND FLOORS DURING CONSTRUCTION. EACH TRADE SHALL LOCATE/DIMENSION/COORDINATE THEIR ROOF, FLOOR AND WALL OPENINGS WITH THE GENERAL CONTRACTOR (GC) OR CONSTRUCTION MANAGER.
16. PROTECT NEW WORK FROM DAMAGE OR DECONTAMINATION. PROVIDE TEMPORARY PROTECTIVE CAPPING OR TAPED POLYETHYLENE ENCLOSURES OVER OPEN PIPING ENDS AND EQUIPMENT. CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING PIPING SYSTEMS PRIOR TO PLACING THEM IN SERVICE.
17. IN A NEAT AND WORKMANLIKE MANNER: PATCH ANY REMAINING OPENINGS AND FILL EXCESSIVE GAPS; REWORK AND REFISH TO MATCH ADJACENT STRUCTURES; FLASH AND SEAL ALL MECHANICAL AND ELECTRICAL PENETRATIONS THRU WALLS, CEILINGS AND FLOORS WITH METAL FRAMEWORK OR ESCUTCHEONS. ALL OPENINGS SHALL BE PROPERLY SEALED SO AS TO MEET FIRE RATING.


#### MECHANICAL PIPING

1. PIPING SHOWN IS IN SCHEMATIC FORM. NOT ALL RISERS AND DROPS ARE SHOWN. PROVIDE OFFSETS AS REQUIRED TO MEET SPACE REQUIREMENTS AND TO AVOID INTERFERENCE WITH OTHER TRADES. COORDINATE WITH OTHER TRADES PRIOR TO FABRICATION. THE CONTRACTOR SHALL PROVIDE COMPLETE FULLY FUNCTIONAL SYSTEMS.
2. PROVIDE ACCESSIBLE ISOLATION VALVES AT ALL BRANCH CONNECTIONS TO MAINS. COORDINATE VALVE LOCATIONS ABOVE ACCESSIBLE CEILINGS OR COORDINATE WITH THE GC TO PROVIDE ACCESS PANELS.
3. BREAK CONNECTIONS REQUIRED AT ALL MAJOR EQUIPMENT AND PIPING ITEMS THAT REQUIRE REMOVAL FOR MAINTENANCE.
4. PIPE REDUCTIONS ON HORIZONTAL PIPING GOING FROM LARGER TO SMALLER SHALL BE MADE WITH ECCENTRIC REDUCERS: TOP FLAT FOR LIQUID SYSTEMS, CONCENTRIC REDUCERS MAY BE USED FOR FLOW GOING FROM SMALL TO LARGER SIZE PIPE.
5. NEW FLOOR/WALL/CEILING PENETRATIONS REQUIRED FOR MECHANICAL PIPING INSTALLATION SHALL BE CLEANLY BORED AT RIGHT ANGLES. AS NEW PIPING IS INSTALLED, NEW PIPING PENETRATIONS SHALL BE NEATLY CAULKED TO FILL VOID. WALL PENETRATIONS SHALL BE FINISHED WITH ESCUTCHEONS.
6. ALL NEW PIPING EXPOSED IN OCCUPIED SPACES SHALL HAVE PVC JACKETS INSTALLED OVER THE PIPING INSULATION. ANY PIPING REQUIRED TO BE EXPOSED SHALL BE INSTALLED VERTICALLY OR HORIZONTALLY IN LEAST VISIBLE LOCATION.
7. ALL BRANCH PIPING TO EQUIPMENT TO BE A MINIMUM OF 3/4" UNLESS OTHERWISE NOTED.
8. EXTEND ALL DRAIN CONNECTIONS FOR MECHANICAL EQUIPMENT TO NEAREST FLOOR DRAIN, MOP SINK, ETC. PROVIDE P-TRAP AS REQUIRED BY MANUFACTURER. DRAIN PIPING TO BE SIZED PER CODE OR LINE SIZE, WHICHEVER IS LARGER.
9. ALL EQUIPMENT AND ACCESSORIES SHALL BE INSTALLED TO BE EASILY ACCESSIBLE.
10. ALL WORK SHALL BE COMPLETED IN A SAFE WORKMANLIKE MANNER AND IN ACCORDANCE WITH ALL APPLICABLE STATE, LOCAL AND NATIONAL CODES, REGULATIONS AND ORDINANCES. IF ANY CONFLICTS ARISE BETWEEN THE CONTRACT DOCUMENTS AND THE APPLICABLE CODES, REGULATIONS OR ORDINANCE, THE CONTRACTOR SHALL BE RESPONSIBLE TO HAVE ALL WORK CONFORM TO THE STRICKER OF SAID REQUIREMENTS.
11. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS AS REQUIRED FOR MECHANICAL INSTALLATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE BOTH A COMPLETE AND COMPLIANT INSTALLATION AS MAY BE DETERMINED BY THE AUTHORITY(S) HAVING JURISDICTION.
12. CONTRACTOR SHALL NOT PROCURE OR FABRICATE ANY PIPING OR EQUIPMENT WITHOUT FIRST VERIFYING ALL DIMENSIONS AND CONDITIONS WHETHER CURRENTLY EXISTING OR NOT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK, INCLUDING ANY REQUIRED REWORK.
13. MAINTAIN ALL MANUFACTURER RECOMMENDED EQUIPMENT SERVICE AND SAFETY CLEARANCES. DO NOT LOCATE ANY EQUIPMENT OR RUN MATERIALS ABOVE ANY ELECTRICAL PANELS OR SWITCHGEAR. MAINTAIN ALL NFPA/NEC CODE REQUIRED CLEARANCES.
14. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING, SCHEDULING AND SEQUENCING OF THEIR WORK WITH ALL OTHER TRADES. PROVIDE OFFSETS, EASEMENTS, OR RELOCATE TO AVOID CONFLICTS WITH WORK OF OTHER TRADES. FURNISH SUFFICIENT RESOURCES TO MEET ALL PROJECT MILESTONES AND DEADLINES.
15. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE WATERTIGHT AND WEATHER-PROOF INTEGRITY OF ROOFS, WALLS AND FLOORS DURING CONSTRUCTION. EACH TRADE SHALL LOCATE/DIMENSION/COORDINATE THEIR ROOF, FLOOR AND WALL OPENINGS WITH THE GENERAL CONTRACTOR (GC) OR CONSTRUCTION MANAGER.
16. PROTECT NEW WORK FROM DAMAGE OR DECONTAMINATION. PROVIDE TEMPORARY PROTECTIVE CAPPING OR TAPED POLYETHYLENE ENCLOSURES OVER OPEN PIPING ENDS AND EQUIPMENT. CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING PIPING SYSTEMS PRIOR TO PLACING THEM IN SERVICE.
17. IN A NEAT AND WORKMANLIKE MANNER: PATCH ANY REMAINING OPENINGS AND FILL EXCESSIVE GAPS; REWORK AND REFISH TO MATCH ADJACENT STRUCTURES; FLASH AND SEAL ALL MECHANICAL AND ELECTRICAL PENETRATIONS THRU WALLS, CEILINGS AND FLOORS WITH METAL FRAMEWORK OR ESCUTCHEONS. ALL OPENINGS SHALL BE PROPERLY SEALED SO AS TO MEET FIRE RATING.




# 2 MECHANICAL PIPING PLAN


A compass rose is shown, consisting of a circle divided into four quadrants by a horizontal and a vertical line intersecting at the center. The word "NORTH" is written in capital letters to the left of the horizontal line.




# 1 MECHANICAL HVAC PLAN




A compass rose with a horizontal line pointing to the right. The word "NORTH" is written to the left of the line.




1 PIPING DIAGRAM - IN-LINE PUMP  
NOT TO SCALE




2 HEAT PUMP PIPING DETAIL  
NOT TO SCALE




3 GEOTHERMAL LOOP HEADER DETAIL  
NOT TO SCALE





4 AIR SEPARATOR, EXPANSION TANK AND GLYCOL FEEDER DETAIL  
NOT TO SCALE




5 DRAIN PAN PIPING DETAIL  
NOT TO SCALE




6 INSULATED PIPE HANGER DETAIL  
NOT TO SCALE



7 ELBOW DETAILS  
NOT TO SCALE



8 MECHANICAL SECTION - VHP  
1/2" = 1'-0" 0 3'



9 MECHANICAL SECTION - PIPE CHASE  
1/2" = 1'-0" 0 3'

## HEAT PUMP SCHEDULE - WATER SOURCE

REMARKS:  
 1. SENSIBLE ENERGY RECOVERY WHEEL WITH BYPASS DAMPER, WATER COOLED HEAT PUMP, AND ELECTRIC REHEAT.  
 2. ALL MOTORS SHALL BE NEMA PREMIUM EFFICIENCY.  
 3. PROVIDE FACTORY MOUNTED DISCONNECT.  
 4. VHP-1 COOLING IS BASED ON 90°F EWT, HEATING IS BASED ON 40°F EWT. 30% PROPYLENE GLYCOL.  
 5. EER AND COP VALUE BASED ARI STANDARD CONDITIONS.  
 6. HEAT PUMP SHALL HAVE MODULATING CAPACITY WITH VFD. FANS SHALL BE VARIABLE SPEED ECM MOTORS.  
 7. ALL ALUMINUM INTERIOR.  
 8. PROVIDE WITH EXTRA SET OF FILTERS. REPLACE AT TIME OF OWNER ACCEPTANCE.

MARK	SUPPLY FAN DATA		EXHAUST FAN DATA		HEAT PUMP - COOLING						HOT GAS REHEAT			HEAT PUMP - HEATING						ENERGY RECOVERY WHEEL						ELECTRICAL INFORMATION																					
	CFM	EXTERNAL STATIC PRESSURE (IN. WG)	HP	CFM	EXTERNAL STATIC PRESSURE (IN. WG)	HP	WATER FLOW		EAT (°F)		LAT (°F)		CAPACITY (MBH)		EER	LAT (°F)	MBH	EAT DB (°F)	LAT DB (°F)	EWT (°F)	LWT (°F)	TOTAL MBH	COP	ELECTRIC PRE-HEAT KW	SUMMER OPERATION			WINTER OPERATION			VOLTS	PHASE	MCA	MOPC													
							GP	PD (FT H2O)	EWT (°F)	LWT (°F)	DB	WB	DB	WB	%									OUTSIDE AIR EAT (°F)	EXHAUST AIR EAT (°F)	TEMPERED AIR LAT (°F)	AIR LAT (°F)	EFFECTIVENESS %	TOTAL REC MBH																		
VHP-1	1600	1	1	1720	1	1.5	20	8.4	90	103	80	68.1	45.8	45.8	100.6	59	16.3	70	18.9	51	100.8	40	33	88.3	3.8	10	95	76	75	63	80	67	71	53.91	-10	-11	70	58	52.8	46.2	74	124.9	240	3	83.7	100	TRANE OAFB108D3

### MECHANICAL PUMP SCHEDULE

1. WELLFIELD PRESSURE DROP ASSUMED TO BE 25 FEET. CONTRACTOR TO VERIFY PRIOR TO ORDERING PUMP.

MARK	SYSTEM SERVED	TYPE	GPM	HEAD (FT)	MOTOR DATA				DESIGN BASIS	REMARKS
					HP	RPM	VOLTS	PHASE		
P-1	GEO THERMAL	IN-LINE	20	40	1	1760	240	1	TACO 1915	VFD BY EC
P-2	GEO THERMAL	IN-LINE	20	40	1	1760	240	1	TACO 1915	VFD BY EC

### GLYCOL FEED SYSTEM SCHEDULE

MARK	SYSTEM SERVED	TANK VOLUME (GAL)	PRESSURE RANGES (PSI)		ELECTRICAL DATA	DESIGN BASIS		
			CUT IN	CUT OUT				
GF-1	GEO THERMAL	50	10-45	20-60	120	1	0.33	NEPTUNE G-50-1

### AIR/DIRT SEPARATOR

MARK	PIPE SIZE (IN)	CAPACITY (GPM)	MAX PD (FT)	AIR REMOVAL (%)	DESIGN BASIS	REMARKS
AS-1	2	20	0.4	99%	SPIROTHERM VDN200	

### MECHANICAL PIPING EXPANSION TANK SCHEDULE

MARK	SYSTEM SERVED	TYPE	TANK CAPACITY (GAL)	ACCEPTANCE CAPACITY (GAL)	DESIGN BASIS
ET-1	GEO THERMAL	BLADDER	23	23	TACO CA-90

### GRAVITY INTAKE/RELIEF HOOD SCHEDULE


REMARKS:  
 1. PROVIDE WITH INSECT SCREEN AND 12" CURB.

2. PROVIDE WITH MOTORIZED DAMPER, GREENHECK MODEL ICD-45 WITH 24V/1PH ACTUATOR (OR EQUAL).

MARK	CFM	THROAT SIZE (WxL) (IN)	THROAT VELOCITY (FPM)	MAX PD (IN)	DESIGN BASIS
GRH-1	1925	18X18	856	0.15	GREENHECK WRH-18X18

### DIFFUSERS REGISTERS AND GRILLES SCHEDULE

MARK	MATERIAL	DESCRIPTION	FACTORY FINISH	DESIGN BASIS
A	ALUMINUM	3/4" SPACING DBL DEF	WHITE	TITUS 350FS
B	ALUMINUM	3/4" SPACING 35° DEF	WHITE	TITUS 300FS



## CONTROLS SCHEMATIC

NOT TO SCALE

### VENTILATION HEAT PUMP

#### RUN CONDITIONS - CONTINUOUS:

THE UNIT SHALL RUN CONTINUOUSLY BASED ON A USER DEFINED SCHEDULE.

#### SUPPLY FAN:

THE SUPPLY FAN SHALL RUN CONTINUOUSLY, UNLESS SHUTDOWN ON SAFETIES. OCCUPIED MODE: FAN SHALL OPERATE AT FULL SCHEDULED AIRFLOW. UNOCCUPIED MODE: FAN SHALL OPERATE AT 30% SCHEDULED AIRFLOW.

ALARMS SHALL BE PROVIDED AS FOLLOWS:  
 • SUPPLY FAN FAILURE: COMMENDED ON, BUT THE STATUS IS OFF.  
 • SUPPLY FAN IN HAND: COMMENDED OFF, BUT THE STATUS IS ON.

EXHAUST FAN:  
 THE EXHAUST FAN SHALL RUN WHENEVER THE SUPPLY FAN RUNS. OCCUPIED MODE: FAN SHALL OPERATE AT FULL SCHEDULED AIRFLOW. UNOCCUPIED MODE: FAN SHALL OPERATE AT 30% SCHEDULED AIRFLOW.

ALARMS SHALL BE PROVIDED AS FOLLOWS:  
 • EXHAUST FAN FAILURE: COMMENDED ON, BUT THE STATUS IS OFF.  
 • EXHAUST FAN IN HAND: COMMENDED OFF, BUT THE STATUS IS ON.

HEATING AND COOLING - VARIABLE COMPRESSOR:  
 THE CONTROLLER SHALL MODULATE THE COMPRESSOR TO MAINTAIN EXHAUST INTAKE AIR TEMPERATURE SETPOINT. THE COMPRESSOR SHALL RUN SUBJECT TO ITS OWN INTERNAL SAFETIES AND CONTROLS.

• COOLING MODE: 75°F (ADJ.) OCCUPIED / 78°F (ADJ.) UNOCCUPIED RETURN AIR TEMPERATURE  
 • HEATING MODE: 70°F (ADJ.) OCCUPIED / 67°F (ADJ.) UNOCCUPIED RETURN AIR TEMPERATURE

THE HEATING SHALL BE ENABLED WHENEVER:  
 • EXHAUST INTAKE AIR TEMPERATURE IS 2°F (ADJ.) LESS THAN SETPOINT  
 • AND THE FAN STATUS IS ON  
 • AND THE REVERSING VALVE IS IN HEAT MODE.

THE COOLING SHALL BE ENABLED WHENEVER:  
 • EXHAUST INTAKE AIR TEMPERATURE IS 2°F (ADJ.) MORE THAN SETPOINT  
 • AND THE FAN STATUS IS ON  
 • AND THE REVERSING VALVE IS IN COOL MODE.

ON MODE CHANGE, THE COMPRESSOR SHALL BE DISABLED AND REMAIN OFF UNTIL AFTER THE REVERSING VALVE HAS CHANGED POSITION.

DEHUMIDIFICATION:  
 THE CONTROLLER SHALL MEASURE THE EXHAUST INTAKE AIR HUMIDITY AND OVERRIDE THE COOLING SEQUENCE WHEN THE EXHAUST INTAKE AIR HUMIDITY IS AT OR ABOVE 60% RH (ADJ.). THE FANS SHALL OPERATE AT FULL AIRFLOW WHEN IN DEHUMIDIFICATION MODE. THE HP DISCHARGE AIR TEMPERATURE SHALL BE MAINTAINED AT 70°F (ADJ.) AND THE HOT GAS REHEAT COIL VALVE SHALL MODULATE TO MATCH AIR EXHAUST TAKE AIR TEMPERATURE SETPOINT. DEHUMIDIFICATION SHALL BE ENABLED WHENEVER THE SUPPLY FAN STATUS IS ON.

HGR DISCHARGE AIR TEMPERATURE:  
 THE CONTROLLER SHALL MONITOR THE HGR DISCHARGE AIR TEMPERATURE. ALARMS SHALL BE PROVIDED AS FOLLOWS:  
 • HIGH EXHAUST INTAKE AIR HUMIDITY: IF THE EXHAUST INTAKE AIR HUMIDITY IS GREATER THAN 70% (ADJ.).  
 • LOW EXHAUST INTAKE AIR HUMIDITY: IF THE EXHAUST INTAKE AIR HUMIDITY IS LESS THAN 35% (ADJ.).


EXHAUST AIR FILTER DIFFERENTIAL PRESSURE MONITOR:  
 THE CONTROLLER SHALL MONITOR THE DIFFERENTIAL PRESSURE ACROSS THE FILTER.

ALARMS SHALL BE PROVIDED AS FOLLOWS:  
 • FILTER CHANGE REQUIRED: FILTER DIFFERENTIAL PRESSURE EXCEEDS A USER DEFINABLE LIMIT (ADJ.).

EXHAUST DISCHARGE AIR TEMPERATURE:  
 THE CONTROLLER SHALL MONITOR THE EXHAUST DISCHARGE AIR TEMPERATURE.

ENERGY RECOVERY ECONOMIZER:  
 THE SENSIBLE ENERGY RECOVERY CORE BYPASS DAMPERS SHALL OPEN WHEN THE OUTSIDE AIR TEMPERATURE IS LESS THAN THE EXHAUST INTAKE AIR TEMPERATURE BY A USER DEFINABLE AMOUNT (ADJ.) IN COOLING MODE.

THE SENSIBLE ENERGY RECOVERY CORE BYPASS DAMPERS SHALL OPEN WHEN THE OUTSIDE AIR TEMPERATURE IS GREATER THAN THE EXHAUST INTAKE AIR TEM




2 MECHANICAL ISOMETRIC - DUCTWORK

1 MECHANICAL ISOMETRIC - GEOTHERMAL PIPING

NOT TO SCALE

MECHANICAL AND ELECTRICAL COORDINATION SCHEDULE																
GENERAL NOTES:																
A. MOCP SIZES SHOWN BELOW ARE FOR BIDDING PURPOSES ONLY. VERIFY MOCP WITH EQUIPMENT NAME PLATE DATA PRIOR TO ORDERING EQUIPMENT.																
B. MINIMUM WIRE SIZE SHALL BE #12 AWG AND MINIMUM CONDUIT SIZE SHALL BE 3/4".																
C. INCLUDE A SEPARATE, GREEN, CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT CONDUITS.																
ABBREVIATIONS:																
EC - ELECTRICAL CONTRACTOR																
MC - MECHANICAL CONTRACTOR																
MFR - MANUFACTURER																
TCC - TEMPERATURE CONTROL CONTRACTOR																
OWN - OWNER																
REMARKS:																
1. XXX.																
2. XXX.																
EQUIPMENT SCHEDULE																
MARK	VOLTAGE	PHASE	FLA	MCA	MOCP	HP	KVA	CONDUIT AND WIRE SIZE	CONTROL OR STARTER	CONTROLLER OR STARTER FURNISHED / INSTALLED	DISCONNECT TYPE	DISCONNECT FURNISHED / INSTALLED	REMARKS			
CP-1	120	1	0.8	1	15	-	0.092	2#12, 1#12GND, 3/4"	AQUASTAT	MC/EC	NEMA 1, MS	EC/EC	XXX			
EWH-1	240	1	50	62.5	70	-	12	2#4, 1#8GND, 1"	INTERNAL	-	NEMA 1, MS	EC/EC	XXX			
EWH-2	240	1	50	62.5	70	-	12	2#4, 1#8GND, 1"	INTERNAL	-	NEMA 1, MS	EC/EC	XXX			
GF-1	120	1	7.2	9	20	0.33	0.864	2#12, 1#12GND, 3/4"	INTERNAL	-	NEMA 1, MS	EC/EC	XXX			
P-1	240	1	8	10	20	1	1.92	2#12, 1#12GND, 3/4"	VFD	EC/EC	NEMA 1, MS	EC/EC	XXX			
P-2	240	1	8	10	20	1	1.92	2#12, 1#12GND, 3/4"	VFD	EC/EC	NEMA 1, MS	EC/EC	XXX			
VHP-1	240	3	68	83.7	100	-	28.267	2#3, 1#8GND, 1"	VFD	MFR/EC	NEMA 3R, F	MFR/EC	XXX			



A4 ONE-LINE DIAGRAM  
NOT TO SCALE

## ELECTRICAL

1. ALL WORK SHALL BE IN CONFORMANCE WITH THE NATIONAL ELECTRICAL CODE - LATEST EDITION ADOPTED BY THE STATE, THE STATE AMENDMENTS, LOCAL/MUNICIPAL CODES AND ORDINANCES, AND THE AUTHORITY HAVING JURISDICTION. THE COMPLETE INSTALLATION SHALL BE IN ACCORDANCE WITH THE ADAAG (AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES).
2. IT IS THE INTENT OF THESE DOCUMENTS TO COMPLY WITH THE APPLICABLE CODES. WHERE DISCREPANCIES OCCUR, NOTIFY THE ENGINEER/ARCHITECT IN WRITING FOR INTERPRETATION. CORRECT ANY INSTALLATION THAT FAILS TO COMPLY WITH THE CODES AND STANDARDS AT NO ADDITIONAL COST TO THE OWNER.
3. CONTRACTOR SHALL PROVIDE ALL WORK NECESSARY INCLUDING ALL LABOR, MATERIALS, PERMITS, TAXES, FEES, INSPECTIONS, HARDWARE, AND COST FOR INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM.
4. ALL MATERIALS FURNISHED BY THE CONTRACTOR SHALL BE NEW, COMPLETE WITH MANUFACTURER'S GUARANTEE OR WARRANTY AND SHALL BE LISTED BY A NATIONALLY RECOGNIZED TESTING LABORATORY (NRTL).
5. COORDINATE ELECTRICAL INSTALLATION WITH ALL TRADES PRIOR TO INSTALLATION. IF ELECTRICAL WORK INSTALLED INTERFERES WITH OTHER TRADES AFTER INSTALLATION, THE CONTRACTOR SHALL MAKE ALL NECESSARY CHANGES TO CORRECT THE CONDITION AT NO ADDITIONAL COST TO THE OWNER.
6. DRAWINGS ARE DIAGRAMMATIC. ALL DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL VERIFY ALL FURNITURE, MODULAR FURNITURE, AND EQUIPMENT LOCATIONS WITH ARCHITECTURAL PLANS, ELEVATIONS AND REVIEWED SHOP DRAWINGS. PRIOR TO MAKING THE ACTUAL ELECTRICAL INSTALLATION THIS CONTRACTOR SHALL ADJUST CONNECTION LOCATIONS TO ACCOMMODATE FURNITURE AND/OR EQUIPMENT.
7. ALL ELECTRICAL PANELS WITH ANY BRANCH CIRCUIT/LOAD REVISIONS (DEMOLITION OR NEW WORK) SHALL HAVE A NEW TYPED UPDATED CIRCUIT DIRECTORY CARD INSTALLED INSIDE THE DOOR OF THE ELECTRICAL PANEL. THE CONTRACTOR SHALL VERIFY THAT ALL UNUSED CIRCUIT BREAKERS ARE TURNED 'OFF' AND PROPERLY INDICATED AS 'SPARE' ON THE NEW CIRCUIT DIRECTORY CARD. THE CONTRACTOR SHALL INSTALL FILLER PLATES WHERE BREAKERS ARE REMOVED AS PART OF THIS PROJECT OR HAVE BEEN REMOVED PREVIOUSLY.
8. NO ENERGIZED CONDUCTORS SHALL BE EXPOSED AT ANYTIME EXCEPT WHEN THE IMMEDIATE AREA IS UNDER THE SUPERVISION OF A QUALIFIED ELECTRICIAN.
9. WHERE CONDUIT IS SURFACE MOUNTED TO A WALL AND RUN VERTICALLY DOWN TO A SWITCH/OUTLET BOX, UTILIZE 1-HOLE OR 2-HOLE CONDUIT STRAPS.
10. REFER TO THE ARCHITECTURAL DRAWINGS FOR LOCATIONS OF BUILDING EXPANSION JOINTS. ALL CONDUITS CROSSING EXPANSION JOINTS SHALL BE INSTALLED WITH EXPANSION FITTINGS, UNLESS THE CONDUIT IS BELOW SLAB IN THE COMPAKTED GRANULAR FILL. EXPANSION FITTINGS SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, AND MANUFACTURE'S WRITTEN RECOMMENDATIONS.
11. PENETRATIONS THROUGH FIRE RATED WALLS BY DIVISION 26 CONTRACTOR SHALL BE SEALED WITH APPROPRIATE FIRE PROOFING MATERIAL TO RESTORE FIRE RATING. REFER TO ARCHITECTURAL DRAWINGS FOR FIRE RATED WALLS.
12. THE CONTRACTOR SHALL KEEP THE WORK AREA CLEAN OF ALL DEBRIS ON A DAILY BASIS. ALL NEW MATERIALS AWAITING INSTALLATION SHALL BE KEPT IN AREAS DESIGNATED BY THE OWNER.
13. THESE DRAWINGS SHALL NOT BE SCALED TO OBTAIN DIMENSIONS. REFER TO DIMENSIONED ARCHITECTURAL FLOOR PLANS. IF THE DIMENSIONS CANNOT BE DETERMINED BY THE INFORMATION GIVEN, CONTRACTOR SHALL CONTACT THE ENGINEER FOR ADDITIONAL INFORMATION.
14. PERIODIC SITE OBSERVATION BY THE ENGINEER IS SOLELY FOR THE PURPOSE OF DETERMINING IF THE WORK OF THE CONTRACTOR IS PROCEEDING IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. THIS LIMITED SITE OBSERVATION SHOULD NOT BE CONSTRUED AS EXHAUSTIVE OR CONTINUOUS TO CHECK THE QUALITY OR QUANTITY OF THE WORK, BUT RATHER PERIODIC IN AN EFFORT TO GUARD THE OWNER AGAINST DEFECTS OR DEFICIENCIES IN THE WORK OF THE CONTRACTOR.
15. THE INFORMATION CONTAINED ON THE ELECTRICAL DRAWINGS IS IN ITSELF INCOMPLETE AND VOID UNLESS USED IN CONJUNCTION WITH ALL OTHER DISCIPLINE DRAWINGS, THE SPECIFICATIONS, TRADE PRACTICES, OR APPLICABLE STANDARDS, CODES, ETC., AND SHALL BE CONSIDERED THE CONTRACT DOCUMENTS AND WITH ALL THEREIN BY REFERENCE, WHICH THE CONTRACTOR CERTIFIES KNOWLEDGE OF BY SIGNING THE CONTRACT.
16. CONTRACTOR IS TO ASSUME FULL RESPONSIBILITY, UNRELIEVED BY REVIEW OF SHOP DRAWINGS OR PERIODIC OBSERVATION OF CONSTRUCTION, FOR COMPLIANCE WITH THE CONTRACT DOCUMENTS, FOR DIMENSIONS TO BE CONFIRMED AND CORRELATED ON THE JOB SITE AND BETWEEN INDIVIDUAL DRAWINGS OR SETS OF DRAWINGS FOR FABRICATION PROCESSES AND CONSTRUCTION TECHNIQUES (INCLUDING EXCAVATION, SHORING, SCAFFOLDING, BRACING, ERECTION, FORM WORK, ETC.), FOR COORDINATION OF THE VARIOUS TRADES, AND FOR SAFE CONDITIONS ON THE JOB SITE. VARIATIONS IN FIELD CONDITIONS RELATIVE TO THE CONTRACT DOCUMENTS SHALL BE REPORTED TO THE ENGINEER AS SOON AS THEY ARE FOUND. WORK SHALL NOT PROGRESS UNTIL WRITTEN PERMISSION FROM THE ENGINEER IS OBTAINED.

## ELECTRICAL DEMOLITION

1. LIGHT LINES INDICATE EXISTING WALLS AND EQUIPMENT TO REMAIN. DASHED LINES INDICATE WALLS, EQUIPMENT, AND ELECTRICAL ITEMS TO BE REMOVED.
2. COORDINATE PATCHING REQUIREMENTS FOR UNUSED OPENINGS WITH THE GENERAL CONTRACTOR. GENERAL CONTRACTOR SHALL PATCH ALL UNUSED OPENINGS. PATCHWORK SHALL MATCH MATERIALS, FINISH, AND TEXTURE OF ADJACENT SURFACES.
3. FIRE ALARM - REMOVE EXISTING CEILING MOUNTED DEVICES TO PERMIT REMOVAL OF CEILING. WALL MOUNTED NOTIFICATION DEVICES SHALL BE DEMOLISHED. COORDINATE WORK WITH PROJECT PHASING TO MAINTAIN FIRE ALARM SYSTEM PROTECTION OF SPACES AT ALL TIMES. INCLUDE COSTS OF ALL TEMPORARY DEVICES IN THE BID.
4. SECURITY/SURVEILLANCE - EXISTING DEVICES TO BE REMOVED BY SYSTEMS VENDOR. CONTRACTOR SHALL REMOVE ASSOCIATED CABLING, ROUGH-IN, AND POWER WIRING. PRIOR TO ANY DEMOLITION IDENTIFY AND PROTECT CABLING REQUIRED TO MAINTAIN THE SYSTEM IN AREAS THAT WILL NOT BE REMODELED.
5. COORDINATE DISPOSAL OF ALL ITEMS NOT REQUESTED AS SALVAGE BY THE OWNER.
6. TELEPHONE AND DATA HORIZONTAL CABLING SHALL BE REMOVED COMPLETELY BACK TO THE FIRST REMAINING DISTRIBUTION FRAME. PROTECT FIBER OPTIC AND COPPER TRUNK CABLING SERVING DISTRIBUTION RACKS.
7. LIGHTING FIXTURES AND CONTROLS - REMOVE EXISTING LIGHT FIXTURES, WALL SWITCHES, OCCUPANCY SENSORS, AND ASSOCIATED WIRING. VERIFY AND MAINTAIN CONNECTION TO EXISTING LIGHTING THAT WILL NOT BE REMOVED BUT ARE ON COMMON CIRCUITS WITH ITEMS TO BE REMOVED.
8. DISCONNECT OUTLETS, WIRING, AND OTHER NOTED EQUIPMENT TO PERMIT DEMOLITION OF WALLS. VERIFY AND MAINTAIN CONNECTION TO EXISTING OUTLETS THAT WILL NOT BE REMOVED BUT ARE ON COMMON CIRCUITS WITH ITEMS TO BE REMOVED.
9. DRAWINGS DO NOT IDENTIFY ALL OUTLETS, SWITCHES, CABLING, OR EQUIPMENT TO BE REMOVED. CONTRACTOR SHALL BECOME FAMILIAR WITH THE SITE PRIOR TO BIDDING AND INCLUDE LABOR AND MATERIAL NECESSARY FOR REQUIRED DEMOLITION IN THEIR BID.
10. WIRING SHALL BE REMOVED BACK TO SERVING PANEL. INSTALLATION OF NEW CONDUCTORS IN EXISTING CONDUITS WILL BE PERMITTED AS DESCRIBED IN THE DIVISION 26 SPECIFICATIONS.
11. HVAC EQUIPMENT NOTED FOR REMOVAL IS FOR REFERENCE ONLY. THE ELECTRICAL CONTRACTOR SHALL REVIEW THE MECHANICAL SYSTEMS DEMOLITION PLANS AND INCLUDE ALL LABOR AND MATERIAL NECESSARY TO FACILITATE REMOVAL OF EQUIPMENT AS SHOWN ON THOSE DRAWINGS. THIS SHALL INCLUDE ALL ITEMS NOTED ON EITHER THE PLUMBING OR MECHANICAL SERIES OF DRAWINGS.


**SITE ELECTRICAL**

1. ALL UTILITY FEEDERS INDICATED ON PLANS ARE DIAGRAMMATIC IN NATURE AND RELEVANT UTILITIES SHALL BE IDENTIFIED AND STAKED PRIOR TO NEW CONSTRUCTION.


2. LINE TYPE KEY:

- NEW WORK UNDERGROUND BY THIS CONTRACTOR (DARK LONG DASHED LINE)
- WORK BY OTHERS AND/OR EXISTING TO REMAIN (GRAYSCALE DASHED LINE)


KEYNOTES	
KEY	NOTE
E01	PULL NEW FEEDERS THROUGH EXISTING IN PLACE (3) 3" HDPE CONDUIT WITH FULL STRING AND TRACER WIRE. REFER TO SHEET E500 FOR FULL ONE-LINE DIAGRAM. VERIFY EXISTING CAPED CONDUIT LOCATION ON SITE PRIOR TO NEW INSTALLATION.



1 ELECTRICAL SITE PLAN



1 SOLAR ROOF PLAN  
1/8" = 1'-0" 0



2 SHOWERHOUSE LIGHTING, POWER & SYSTEMS PLAN  
1/4" = 1'-0" 0

#### POWER

- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THIS DRAWING.
- WHERE CONNECTED TO A 20A BRANCH CIRCUIT SUPPLYING AN INDIVIDUAL RECEPTACLE (SIMPLEX OR DUPLEX), THE RECEPTACLE SHALL BE RATED AT 20A.
- VERIFY LOCATIONS AND ROUGH-IN REQUIREMENTS OF ALL OWNER FURNISHED EQUIPMENT PRIOR TO ROUGH-IN.
- PROVIDE HOUSEKEEPING PADS FOR ALL FLOOR MOUNTED AND GRADE MOUNTED ELECTRICAL EQUIPMENT. MINIMUM REQUIREMENTS: 4" HIGH, 4% AIR ENTRAINED, POLYFIBER REINFORCED CONCRETE, 4" WIDER AND 4" LONGER THAN EQUIPMENT TO BE PLACED ON IT. REFER TO ELECTRICAL DETAIL DRAWINGS FOR TRANSFORMER, GENERATOR, OR SWITCHGEAR PADS THAT MAY EXCEED THESE REQUIREMENTS.
- CONDUIT AND WIRE SHALL NOT BE INSTALLED BELOW FLOOR SLAB UNLESS INDICATED ON PLAN BY DASHED CONDUIT.
- ANY MODIFICATIONS TO THE NUMBER, SIZE, AND TYPE OF WIRES OR CONDUITS FROM THOSE INDICATED ON THIS DRAWING ARE PROHIBITED.

#### SYSTEMS

- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THE DRAWINGS, EXCEPT FOR SECURITY DEVICES. PROVIDE ROUGH-IN ONLY FOR SECURITY DEVICES, CAMERAS AND CARD READERS.
- MAXIMUM NUMBER OF 4 INFORMATION OUTLET LOCATIONS PER CONDUIT HOME RUN TO MDF OR IDF IS PERMITTED. CONDUIT SHALL BE SIZED AS FOLLOWS:
  - 1 INFORMATION OUTLET LOCATION: 1"
  - 2 INFORMATION OUTLET LOCATIONS: 1 1/4"
  - 3 INFORMATION OUTLET LOCATIONS: 1 1/2"
- INSTALL CONDUIT WITH NO MORE THAN (2) 90° BENDS BETWEEN PULL BOXES, AND NO MORE THAN 100'-0" BETWEEN PULL BOXES. PULL BOXES SHALL BE INSTALLED FOR STRAIGHT THRU PULLS ONLY.
- ALL COMMUNICATIONS CABLES SHALL BE INSTALLED IN CONDUIT, CABLE TRAY, OR SUPPORTED BY CABLE HOOKS. PROVIDE BUSHINGS AT THE ENDS OF ALL CONDUIT WHERE STUBBED ABOVE ACCESSIBLE CEILINGS OR WHERE DROPPED INTO CABLE TRAY. PROVIDED CABLE HOOKS ABOVE ACCESSIBLE CEILINGS FOR CABLE INSTALLATION WHERE NOT INSTALLED IN CONDUIT OR CABLE TRAY.
- FIRE ALARM WIRING DOES NOT NEED TO BE IN CONDUIT.

#### KEYNOTES

KEY	NOTE
E02	700 WATT SOLAR MODULE MOUNTED TO PRECAST ROOF. MOUNT PER PRECAST AND MODULE MANUFACTURER RECOMMENDATIONS.
E03	NEW INVERTER TO BE CONNECTED TO EXISTING SOLAR EDGE INVERTERS ON EXISTING GROUND MOUNTED SOLAR INSTALLATION. FURNISH AND INSTALL MEDIA CONVERTERS AND UTILIZE EXISTING FIBER NETWORK TO CONNECT THE INVERTERS.